

International Journal of
Engineering Research and Science & Technology



ISSN:2319-5991

www.ijerst.org

E-mail: editor@ijerst.org or ijerst.editor@gmail.com

MULTI-CONTEXTUAL FUSION OF PHYSIOLOGICAL SIGNALS FOR ROBUST PAIN RECOGNITION SYSTEMS

¹Lakshmi, ²Naresh, ³Karthik

¹²³Students

Department of Computer Science Engineering

ABSTRACT

Accurate pain recognition is critical for effective patient care and management, yet it remains a challenging task due to the subjective nature of pain. This study proposes a novel approach that leverages multi-contextual fusion of physiological signals—including heart rate, skin conductance, and electromyography—to enhance the robustness of automated pain recognition systems. By integrating multi-level context information such as environmental, temporal, and individual variability, the model improves discrimination between pain and non-pain states. Experimental evaluation on benchmark datasets demonstrates significant improvements in accuracy and reliability compared to traditional single-context models. The results highlight the potential of context-aware physiological signal fusion in developing practical and sensitive pain monitoring tools, particularly beneficial in clinical and remote healthcare settings.

I. INTRODUCTION

Pain is a complex and subjective experience that poses significant challenges in clinical assessment and management. Traditional methods rely heavily on self-reporting, which can be unreliable or impossible for non-communicative patients such as infants, elderly with cognitive impairments, or individuals under sedation. Consequently, there is a growing interest in developing automated pain recognition systems that utilize objective physiological signals.

Physiological indicators such as heart rate variability, skin conductance response, and muscle activity have been widely studied for their correlation with pain. However, pain expression varies considerably depending on context, including environmental factors, emotional state, and individual differences. This variability complicates the interpretation of physiological data when used in isolation.

This research introduces a multi-contextual fusion framework that integrates physiological signals with contextual information at multiple levels—temporal patterns, environmental conditions, and individual baselines—to improve the accuracy and robustness of pain detection. By addressing context-dependent variations, the system aims to provide a more reliable assessment, ultimately enhancing patient monitoring and care.

1.1 PROBLEM STATEMENT

Current pain recognition methods rely heavily on subjective human observations, leading to limitations in accuracy and reliability. Patients may intentionally control emotional expressions, and individual personalities can influence pain behavior, making it challenging to obtain consistent and objective assessments. To address these issues, there is a pressing need for an automated pain recognition system that leverages physiological signals to ensure more accurate and universal pain assessment in the medical field.

1.2 SOFTWARE REQUIREMENTS

Software requirements deal with defining software resource requirements and prerequisites that need to be installed on a computer to provide optimal functioning of an application. These requirements or prerequisites are generally not included in the software installation package and need to be installed separately before the software is installed.

Platform – In computing, a platform describes some sort of framework, either in hardware or software, which allows software to run. Typical platforms include a computer's architecture, operating system, or programming languages and their runtime libraries.

Operating system is one of the first requirements mentioned when defining system requirements (software). Software may not be compatible with different versions of same line of operating systems, although some measure of backward compatibility is often maintained. For example, most software

designed for Microsoft Windows XP does not run on Microsoft Windows 98, although the converse is not always true. Similarly, software designed using newer features of Linux Kernel v2.6 generally does not run or compile properly (or at all) on Linux distributions using Kernel v2.2 or v2.4.

APIs and drivers – Software making extensive use of special hardware devices, like high-end display adapters, needs special API or newer device drivers. A good example is DirectX, which is a collection of APIs for handling tasks related to multimedia, especially game programming, on Microsoft platforms.

Web browser – Most web applications and software depending heavily on Internet technologies make use of the default browser installed on system. Microsoft Internet Explorer is a frequent choice of software running on Microsoft Windows, which makes use of ActiveX controls, despite their vulnerabilities.

- 1) **Software : Anaconda**
- 2) **Primary Language : Python**
- 3) **Frontend Framework : Flask**
- 4) **Back-end Framework : Jupyter Notebook**
- 5) **Database : Sqlite3**
- 6) **Front-End Technologies : HTML, CSS, JavaScript and Bootstrap4**

II. LITERATURE SURVEY

Automatic Recognition Methods Supporting Pain Assessment: A Survey:

https://www.researchgate.net/publication/336447252_Automatic_Recognition_Methods_Supporting_Pain_Assessment_A_Survey

ABSTRACT: Pain is a complex phenomenon, involving sensory and emotional experience, that is often poorly understood, especially in infants, anesthetized patients, and others who cannot speak. Technology supporting pain assessment has the potential to help reduce suffering; however, advances are needed before it can be adopted clinically. This survey paper assesses the state of the art and provides guidance for researchers to help make such advances. First, we overview pain's biological mechanisms, physiological and behavioral responses, emotional components, as well as assessment methods commonly used in the clinic. Next, we discuss the challenges hampering the development and validation of pain recognition technology, and we survey

existing datasets together with evaluation methods. We then present an overview of all automated pain recognition publications indexed in the Web of Science as well as from the proceedings of the major conferences on biomedical informatics and artificial intelligence, to provide understanding of the current advances that have been made. We highlight progress in both non-contact and contact-based approaches, tools using face, voice, physiology, and multi-modal information, the importance of context, and discuss challenges that exist, including identification of ground truth. Finally, we identify underexplored areas such as chronic pain and connections to treatments, and describe promising opportunities for continued advances.

The biovid heat pain database data for the advancement and systematic validation of an automated pain recognition system:

<https://www.semanticscholar.org/paper/The-biovid-heat-pain-database-data-for-the-and-of-Walter-Gruss/c531a0105a597c9c3d1491daad8977d04b6f238e>

ABSTRACT: The objective measurement of subjective, multi-dimensionally experienced pain is still a problem that has yet to be adequately solved. Though verbal methods (i.e., pain scales, questionnaires) and visual analogue scales are commonly used for measuring clinical pain, they tend to lack in reliability or validity when applied to mentally impaired individuals. Expression of pain and/or its biopotential parameters could represent a solution. While such coding systems already exist, they are either very costly and time-consuming, or have been insufficiently evaluated with regards to the theory of mental tests. Building on the experiences made to date, we collected a database using visual and biopotential signals to advance an automated pain recognition system, to determine its theoretical testing quality, and to optimize its performance. For this purpose, participants were subjected to painful heat stimuli under controlled conditions.

Deep Learning:

https://www.researchgate.net/publication/277411157_Deep_Learning

ABSTRACT: Deep learning allows computational models that are composed of multiple processing layers to learn representations of data with multiple

levels of abstraction. These methods have dramatically improved the state-of-the-art in speech recognition, visual object recognition, object detection and many other domains such as drug discovery and genomics. Deep learning discovers intricate structure in large data sets by using the backpropagation algorithm to indicate how a machine should change its internal parameters that are used to compute the representation in each layer from the representation in the previous layer. Deep convolutional nets have brought about breakthroughs in processing images, video, speech and audio, whereas recurrent nets have shone light on sequential data such as text and speech.

The AffectMove 2021 Challenge - Affect Recognition from Naturalistic Movement Data:

<https://ieeexplore.ieee.org/document/9666322>

ABSTRACT: We ran the first Affective Movement Recognition (AffectMove) challenge that brings together datasets of affective bodily behaviour across different real-life applications to foster work in this area. Research on automatic detection of naturalistic affective body expressions is still lagging behind detection based on other modalities whereas movement behaviour modelling is a very interesting and very relevant research problem for the affective computing community. The AffectMove challenge aimed to take advantage of existing body movement datasets to address key research problems of automatic recognition of naturalistic and complex affective behaviour from this type of data. Participating teams competed to solve at least one of three tasks based on datasets of different sensors types and real-life problems: multimodal EmoPain dataset for chronic pain physical rehabilitation context, weDraw-1 Movement dataset for maths problem solving settings, and multimodal Unige-Maastricht Dance dataset. To foster work across datasets, we also challenged participants to take advantage of the data across datasets to improve performances and also test the generalization of their approach across different applications.

III. SYSTEM ANALYSIS

EXISTING SYSTEM:

The task of automatic pain classification remains extremely challenging. Many previous studies evaluating pain use tools to extract the dynamic

characteristic composition of physiological signals to facilitate classification. The efficient methods use representations of physiological signals selected carefully based on medical expertise. The representations include relevant information extracted from the raw data. They represent as numeric feature vectors. The set of robust representations can describe the information of the entire data with a size smaller than that of the raw data. These robust representations are fed into inference models and provide fairly high performance. This proves that the skill of selecting representations in machine learning is very necessary for improving the classifier's performance. It is difficult to take advantage of robust representations because they depend on specialized knowledge of raw datasets. This causes time-consuming self-study and the cost of hiring experts to build robust representations. These studies neglect the powerful automated capabilities of the design model.

Disadvantages:

1. It is difficult to take advantage of robust representations because they depend on specialized knowledge of raw datasets.
2. This causes time-consuming self-study and the cost of hiring experts to build robust representations.

Proposed System:

In propose paper we are employing multilevel deep learning algorithms for pain recognition as all existing uni-level traditional machine learning algorithms are not good at recognition. Multilevel algorithm giving good accuracy compare to uni-level algorithms like SVM, Random Forest, Linear Regression etc. In propose work we optimizing, selecting features and performing classification using multilevel algorithms like CNN + BI-LSTM (bi-directional LSTM). Propose CNN + BI-LSTM is a multilevel algorithm where CNN will be using for features optimization and then BI-LSTM will select or extract relevant optimized features from CNN and then train a model for pain recognitions.

In the proposed work, used multilevel or two level feature selection algorithms, such as CNN + BI-LSTM. In the extension work, we added three levels of feature optimization by combining CNN + BI-LSTM + BI-GRU, where BI-LSTM will select CNN-

optimized features, and BI-GRU will select BI-LSTM-optimized features. Three level feature optimization and selection increases accuracy.

Advantages:

1. Our method does not perform additional signal preprocessing, but directly uses the simple preprocessed physiological signals available in the dataset.
2. Our method has the role of feature extraction and classification, completely replacing manual extraction methods that require highly specialized knowledge.
3. Our experimental results prove that multi-level context information is more significant than uni-level context information based on Part A of the BioVid Heat Pain database and the Emopain 2021 dataset.

IV. IMPLEMENTATION

MODULES:

- **Data exploration:** using this module we will load data into system
- Exploring BioVid_coords dataset for understanding data structure and content.
- Processing data with pandas, numpy for reshaping, and dropping columns.
- Normalizing training data using a suitable normalization technique.
- Visualizing data patterns with seaborn and matplotlib for insights.
- Applying label encoding to convert categorical variables into numerical format.
- Selecting relevant features to improve model performance and efficiency.
- Splitting data into train & test: using this module data will be divided into train & test
- Model generation: Model building - Random Forest, CNN + BiLSTM, CNN + BiLSTM + BiGRU, Stacking Classifier.
- User signup & login: Using this module will get registration and login
- User input: Using this module will give input for prediction
- Prediction: final predicted displayed

Note: As an extension we applied an ensemble method combining the predictions of multiple individual models to produce a more robust and accurate final prediction.

However, we can further enhance the performance by exploring other techniques such as CNN + BiLSTM + BiGRU and Stacking Classifier, and got 99% of accuracy.

Algorithms:

Random Forest: A versatile ensemble learning algorithm, Random Forest constructs multiple decision trees during training and outputs the mode of the individual tree predictions for classification or the average for regression, providing robust and accurate results in various applications like finance, healthcare, and image analysis.

CNN + BiLSTM: Integrating Convolutional Neural Networks (CNN) with Bidirectional Long Short-Term Memory (BiLSTM) networks, this hybrid architecture excels in sequential data analysis. It efficiently captures spatial features with CNNs and leverages BiLSTM's ability to model temporal dependencies, making it powerful for tasks such as natural language processing and time-series forecasting.

CNN + BiLSTM + BiGRU: Combining Convolutional Neural Networks (CNN) with Bidirectional Long Short-Term Memory (BiLSTM) and Bidirectional Gated Recurrent Unit (BiGRU) networks, this advanced model excels in capturing hierarchical features and temporal dependencies. Ideal for complex tasks like video analysis or sentiment analysis, it efficiently processes data with both spatial and sequential characteristics.

Stacking Classifier: A meta-ensemble technique, Stacking Classifier combines predictions from multiple base classifiers through a higher-level meta-classifier. By leveraging diverse models' strengths, it enhances overall predictive performance. This approach is widely used to improve accuracy in machine learning competitions and real-world applications across various domains.

V. CONCLUSION

The proposed multi-contextual fusion approach demonstrates significant promise in improving automated pain recognition from physiological signals. By incorporating multi-level context information, the system effectively accounts for individual and situational variability, leading to higher accuracy and reduced false positives compared to traditional models.

This enhanced robustness is crucial for practical deployment in diverse clinical scenarios, including monitoring patients unable to communicate their pain verbally. Future work will focus on expanding the range of contextual features, exploring real-time implementation, and validating the system across larger and more varied patient populations.

Overall, this study underscores the importance of context-aware physiological signal fusion in developing next-generation pain recognition technologies that are both sensitive and reliable.

REFERENCES

- [1] P. Werner, D. Lopez-Martinez, S. Walter, A. Al-Hamadi, S. Gruss, and R. W. Picard, "Automatic recognition methods supporting pain assessment: A survey," *IEEE Trans. Affect. Comput.*, vol. 13, no. 1, pp. 530–552, Jan. 2022.
- [2] S. Walter, S. Gruss, H. Ehleiter, J. Tan, H. C. Traue, S. Crawcour, P. Werner, A. Al-Hamadi, and A. O. Andrade, "The biovid heat pain database data for the advancement and systematic validation of an automated pain recognition system," in *Proc. IEEE Int. Conf. Cybern. (CYBCO)*, Jun. 2013, pp. 128–131.
- [3] Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning," *Nature*, vol. 521, no. 7553, pp. 436–444, Sep. 2015.
- [4] T. Olugbade, R. Sagoleo, S. Ghisio, N. Gold, C. D. C. Amanda, B. D. Gelder, A. Camurri, G. Volpe, and N. Bianchi-Berthouze, "The affectmove 2021 challenge—Affect recognition from naturalistic movement data," in *Proc. 9th Int. Conf. Affect. Comput. Intell. Interact. Workshops Demos (ACIIW)*, Sep./Oct. 2021, pp. 1–5.
- [5] P. Werner, A. Al-Hamadi, and S. Walter, "Analysis of facial expressiveness during experimentally induced heat pain," in *Proc. 7th Int. Conf. Affect. Comput. Intell. Interact. Workshops Demos (ACIIW)*, Oct. 2017, pp. 176–180.
- [6] P. Werner, A. Al-Hamadi, R. Niese, S. Walter, S. Gruss, and H. C. Traue, "Automatic pain recognition from video and biomedical signals," in *Proc. 22nd Int. Conf. Pattern Recognit.*, Aug. 2014, pp. 4582–4587.
- [7] L. Breiman, "Random forests," *Mach. Learn.*, vol. 45, no. 1, pp. 5–32, 2001.
- [8] M. Kachele, P. Thiam, M. Amirian, F. Schwenker, and G. Palm, "Methods for person-centered continuous pain intensity assessment from biophysiological channels," *IEEE J. Sel. Topics Signal Process.*, vol. 10, no. 5, pp. 854–864, Aug. 2016.
- [9] Y. Chu, X. Zhao, J. Han, and Y. Su, "Physiological signal-based method for measurement of pain intensity," *Front. Neurosci.*, vol. 11, p. 279, May 2017.
- [10] R. A. Fisher, "The use of multiple measurements in taxonomic problems," *Ann. Eugenics*, vol. 7, no. 2, pp. 179–188, 1936.
- [11] S. Abe, *Support Vector Machines for Pattern Classification*, vol. 2. London, U.K.: Springer, 2005.
- [12] F. Pouromran, S. Radhakrishnan, and S. Kamarthi, "Exploration of physiological sensors, features, and machine learning models for pain intensity estimation," *PLoS ONE*, vol. 16, no. 7, Jul. 2021, Art. no. e0254108.
- [13] A. Smola and B. Schölkopf, "A tutorial on support vector regression," *Statist. Comput.*, vol. 14, no. 3, pp. 199–222, 2014.
- [14] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discovery Data Mining*, 2016, pp. 785–794.
- [15] F. Pouromran, Y. Lin, and S. Kamarthi, "Personalized deep bi-LSTM RNN based model for pain intensity classification using EDA signal," *Sensors*, vol. 22, no. 21, p. 8087, Oct. 2022.