



International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 21 No. 3 (1) 2025



ijerst.editor@gmail.com
editor@ijerst.com

Research Paper**ELECTRIC VEHICLES ENERGY REGENERATION SYSTEM
USING DC-DC CONVERTER WITH SUPER-CAPACITORS****Gugulothu Santhosh¹ Thota Rajesh²**¹M. Tech Student, Department of Electrical and Electronics Engineering, Vaagdevi College of Engineering, Khammam - Warangal Hwy, Road, Bollikunta, Telangana 506005²Associate Professor, Department of Electrical and Electronics Engineering, Vaagdevi College of Engineering, Khammam - Warangal Hwy, Road, Bollikunta, Telangana 506005

Abstract Electric cars (EVs) are a relatively new and promising strategy to the devastating environmental and social influences of conventional vehicles. This studies compared and analysed many DC-DC topologies from distinctive domain names and sought strategies to beautify their performance; DC-DC converters play a important position in electric powered cars. Because of these research and designs, researchers inside the car industry will have a higher idea of which DC-DC converter topology to use which will reap the specified power density. Renewable strength can also get greater attention if efforts were made to improve the efficiency and performance of DC-DC converters for use in electric powered vehicles. This will result in a greener, greater sustainable transportation enterprise typical, with less demand for fossil fuels, fewer emissions, and improved air quality. The efficiency of electrical cars has been the using pressure for this undertaking's research on strength regeneration gadgets employing first rate-capacitors. In this publish, we can study a technique for recharging electric power that includes two supercapacitors. This era may reduce contemporary flowing to the battery by way of storing the regenerative strength in the supercapacitor. By enhancing the enter voltage of the inverter in step with the speed of rotation of the motor, it further decreases strength loss among the two additives. The utility of capacitors and the method for controlling voltage inside the proposed circuit are defined in this article. The experimental findings validate the right operation of the bidirectional DC-DC converter in the proposed circuit.

Key words: DC-DC converter, Super capacitor, EV, MATLAB, DC-DC converter, fuzzy logic

Received:05-07-2025

Accepted:19-07-2025

Published: 07-08-2025

1. INTRODUCTION

Fuel elements are being depleted and perilous environmental troubles are getting more common as the arena economic system becomes extra interconnected. It has additionally endorsed the development of environmentally friendly generation, which has improved certainly one of the most important assets of carbon emissions—the transportation quarter [1, 2]. So, to reduce the effect of carbon-based fuels at the environment, electric powered automobiles (EVs) have become extra popular [2, 3]. Electric cars also offer a new chance for people to extend the value-powerful lifespan of transportation [1, 3]. Historically, the inadequacies of BT and power shaping

technology were the primary obstacles to the economic viability of EVs. But inside the previous couple of a long time, BT has evolved to have a high strength density, a low weight, and a excessive efficiency [4]. When coupled with the right energy shaping circuit, an green power storage tool further boosts common overall performance. Researchers and groups use a dc-dc energy conditioning setup that has reliability, more suitable charging-discharging cycles, low power losses, and a protracted lifespan [1]-[4]. These days, constrained using levels with effective fast charges are used since humans are involved about their protection. For both static and dynamic EV charging, the present day scenario requires typologies based

totally on inductive energy transfer (IPT) to make sure the safety of the battery price (BC). In order to improve the converter's ordinary efficiency, repayment networks are included to lessen the circuit impedance. Nevertheless, the configuration's complexity is directly proportional to the amount of active and passive circuit additives [5].

With the proper repair, those issues can be further progressed: stop-user economics, reduced carbon footprint, upkeep cycle, and driving range. Consequently, the marketplace float of electrical automobiles is substantially tormented by converter picks. Consequently, it skilfully aids the discount of transportation-associated environmental issues [6]. Because of its easy production and operational balance for varied coil distances, the traditional collection-collection capacitor repayment based IPT topology is one of the maximum desired community arrangements utilised via agencies [7]. Although this network gives a budget-pleasant alternative, it sacrifices efficiency, electricity transfer talents, control precision for variable hundreds, and strong resonant peaks. To enhance efficiency bandwidth, a method for section manage is given in [7], however the fee is a complicated manage approach for variable frequency. The manipulate boundary is described in the ideal frequency variety to save you difficulties because of fluctuating frequency in [8]. Improved efficiency through the renovation of zero voltage switching (ZVS) for IPT structures is the handiest intention of the manipulate strategies provided in [7] and [8]. Using an intermediate L-C collection compensated structure at both ends, a unique coil help network has superior the topology in [9]. In order to lessen the delivered vehicle aspect weight, as shown in [10], both coils need to be installed on the principle aspect. While the answers given in [9] and [10] do help with magnetic flux underneath misalignment conditions, they make calculations and

manipulate operations less lovely and complicated. In [11], the issues with the usage of an isolated tank community to help IPT are solved by using combining an H-bridge high-frequency transformer with an L-C tank community, that is a way to the troubles defined in [9] and [10]. But overall device length, weight, and volume all pass up, and peak efficiency is going down. Hence, to address the problems as a result of an additional magnetically separated resonant tank, a method like reconstructing the network of the passive aspect is obtainable in [12]-[17]. For long-time period performance development, a symmetrical filter community is cascaded with loosely connected transformer coils in [12] and [13]. But those topologies use magnetically separated inductors, which can be bulky, inefficient, and add complexity to the tuning technique. In order to restore these problems, the authors of [14] and [15] used the LCC-C network setup to provide asymmetrical compensation. For the identical coil design, the LCC-LCC network is suitable for desk bound IPT at the same time as the LCC-C community is appropriate for dynamic IPT, in line with the comparative take a look at of claims given in [12]-[15] in [16] and [17].

On the alternative hand, even as dealing with differences in vehicle facet topology and clearance, it will become distorted. Hence, Li et al. [17] and Zhang et al. [16] recommend using series C-C repayment to discover an alternative approach. For a strongly coupled transformer-based dc-dc converter, the authors of [18]-[20] offer a way to stabilise soft switching during a big running range at the same time as concurrently enhancing performance and overall performance. The auxiliary community is used to enhance the overall performance of the resonant IPT topology in [21] and [22], that are based totally on [18]-[20]. Stable operation with better performance has been performed, however the non-stop losses have been multiplied because of the installation of

magnetics. Similarly, [23] affords an answer for a chain C-C compensated topology based totally on resonant IPT. From this vantage factor, problems in networks primarily based on voltage source inverter (VSI) fed converters can be reduced via using IPT with an auxiliary circuit. The paper proposes a topology that combines zero modern-day switching (ZCS) with zero voltage switching (ZVS) by means of classical series L-C compensation the use of auxiliary additives of minimum size. The recommended architecture keeps a regular output voltage irrespective of the input voltage's fluctuation. Because the input aspect voltage may be used to regulate the output modern-day, a excessive-power CPU isn't always had to control operation, and the converter's fee is efficiently reduced. A running prototype has been created and examined in a controlled environment for whole BC range underneath resistive and battery masses. Two tiers of the converter had been independently regulated the usage of modified pulsewidth modulation (MPWM), as shown in Fig. 1, which provides a vast review of the advised structure. Achieving 0-voltage 0-cutting-edge switching (ZVZCS) and delivering electricity up to 1.1 kW is achieved with the aid of producing pulses at an 85 kHz switching frequency in MPWM mode. The overall performance results are then shown.




Fig 1: General configuration of wireless battery charger topology

2. ELECTRIC VEHICLE

To circulate forward, an electric powered vehicle (EV) makes use of a motor or motors

which can be powered by using electricity. Some EVs use a collector system to get energy from resources out of doors the auto, even as others are completely self-sufficient, the use of just batteries, solar panels, or turbines to show gas into strength. Electric motors consist of a wide range of vehicles, along with those who pass on land or rail, boats both above and under water, planes and spaceships powered by means of power.

Originally evolved within the mid-19th century, electric powered vehicles supplied a level of convenience and simplicity of use that gasoline-powered motors of the time could not match. This caused the upward thrust of energy as a favoured motor vehicle propulsion approach. Electric electricity has remained everyday in various car sorts, consisting of railroads and smaller automobiles of a wide variety, despite the fact that cutting-edge inner combustion engines were the dominating way of motor automobile propulsion for nearly a century.

The upward push of renewable power resources and technical advancements in the new century contributed to a renaissance within the popularity of electrical automobiles. A tiny organization of do-it-your self (DIY) engineers commenced sharing technical records for electric powered automobile conversions as demand for these vehicles skyrocketed. The US and the EU, amongst others, instituted adoption incentives to inspire extra people to get their pets.

3. CONTROL DESIGN

3.1 Operating principle of the proposed converter

Forming a traditional H-bridge are active switches $S1 \rightarrow S4$ on the principle facet and diodes $D5 \rightarrow D8$ at the secondary side.. $Ca1$ and $Ca2$ also break up the ability at the enter of the circuit with auxiliary LA and TA so that the

soft-switching function may be maintained with BC. L1 and L2 are linked to C1 and C2, respectively, on the main and secondary sides of the circuit. In [22], MPWM is used to regulate the functioning of the converter. The counseled converter's working principle can be understood by means of deliberating the subsequent assumptions. 1) All gadgets, whether or not lively or passive, are most beneficial. This includes the inner transfer diode and capacitance in addition to the transformer, dc supply, switches, and diodes. Secondly, the inductor's electrical series resistance and the transformer's interwinding capacitance are neglected. 3) Making sure the input and output terminals of the converter have a consistent voltage calls for huge voltage divider capacitors ($C_a = C_{a1} = C_{a2}$) and CF. 4) We do no longer remember the influences of TA's magnetising inductance.

A. Operation of Proposed Converter

Figure 2 suggests the eight modes (modes I–VIII) that make up the proposed topology's operating principle in steady country, and Figure three suggests = 0, modern-day IL1 + ILA 2 finds its manner through discharging capacitors CS3, CS4, and turning at the diodes D2, D4. The equation that gives the voltage pressure across the switch is as follows: Subtracting v_{C1} from v_{S4} , we get $v_{S1} = -v_{C1}$. In Figure 2(f), Mode IV ($t_3 \leq t < t_4$) is proven. Here, the voltage across S4 is near 0, and D4 is switched on, consequently S4 is turned on with zero voltage drop. Once the auxiliary inductor modern-day (ILA) reaches its terrible peak, it starts to rise linearly within the fine direction. S3 is activated with ZVS in Mode V ($t_4 \leq t < t_5$), as seen in Figure 2(g). As its direction is completed, the voltage throughout S3, S4 is 0, and IAB starts to comply with a sinusoidal wave form. 6) Mode VI, visible in Figure 2(h) and (i), when t_5 is much less than or identical to t_6 . To input this mode, simply switch off S3. This will reason CS3 to charge as much as VDC att51. In the case of a ZCS transfer-off, the auxiliary

inductor cutting-edge (ILA) is falling after attaining its most and IL1, which in flip causes IS4 to drop.




Fig. 2. Operating modes of proposed battery charger topology. (a) Mode I ($t_0 \leq t < t_1$). (b) Mode II (part-1) ($t_1 \leq t < t_{11}$). (c) Mode II (part-2) ($t_{11} \leq t < t_2$). (d) Mode III (part-1) ($t_2 \leq t < t_{21}$). (e) Mode III (part-2) ($t_{21} \leq t < t_3$). (f) Mode IV ($t_3 \leq t < t_4$). (g) Mode V ($t_4 \leq t < t_5$). (h) Mode VI (part-1) ($t_5 \leq t < t_{51}$). (i) Mode VI (part-2) ($t_{51} \leq t < t_6$). (j) Mode VII (part-1) ($t_6 \leq t < t_{61}$). (k) Mode VII (part-2) ($t_{61} \leq t < t_7$). (l) Mode VIII ($t_7 \leq t < t_8$).

7) Mode VII ($t_6 \leq t < t_7$), Fig. 2(j) and (k): In this mode, S4 turned OFF at ZCS and VCS4 rises up to VDC att61. After t_{61} , ILA starts incriminating in positive direction. The diodes D1 and D2 turned ON and power is feedback to the source.

8) Mode VIII ($t_7 \leq t < t_8$), Fig. 2(l): During this mode of operation, switch S2 is turned ON with ZVS and current shifts from D2 to S2. During

mode, I to VIII constant voltage and current are maintained in the battery.




Fig 3: Simplified network with battery load referred at transmitter coil inside




Fig 4: Proposed network configuration of EV battery charger

4. SIMULATION RESULTS AND DISCUSSION




Fig 5: simulation model diagram




Fig 6: Out Put Voltage, Out Put Current, Series Capacitor, Parallel Capacitor, Series Mode and Parallel Model

Extension With Solar Generation




Fig.7 Simulation model with solar input




Fig.8 Out Put Voltage, Out Put Current, Series Capacitor, Parallel Capacitor, Series Mode and Parallel Mode

Through the use of modelling, simulation, and hardware testing, the cautioned converter structure has its operational principle confirmed. In order to comprehend the converter's behaviour, the simulation and hardware circuit settings are adjusted to an operational point. A. Outcomes of the Simulation As seen in Figure 10, the recommended structure has been simulated in MATLAB/Simulink the usage of fundamental additives. In Fig. Four and Table I, the ZVS is turned on for S1 via S4. Placing the resistor ($n\Omega$) and inductor (nH) in collection is the fine configuration for the dc supply. To model the H-bridge thing of the dc-dc converter, the SimPowerSystem Library's MOSFET switches with a zero Ω resistance and an 870 pF capacitance have been used as snubbers. Due to mutual inductance, the linear transformer, transmitter coils, and reception coils compress the auxiliary transformer. For every of the four switches within the ZVS turn-ON sequence (S1–S4), the gate pulse is applied while the voltage across the transfer drops to zero

The ZCS flip-ON for switches S2 and S4. Prior to the completion of the gate pulse, the contemporary flowing via the switch is 0. Accordingly, the suggested wi-fi converter is stated to uphold ZCZVS. The performance of VC1 is used to pick out the compensating capacitor voltage height price. The principal network's enter side function is proven in Figure 13. These findings display that the converter's overall performance is unaffected via the tiny fee of the enter dc-link capacitors. We will see how well the converter works with BC. The traditional charger has disturbances inside the BC voltage and current, which shortens the battery life and reduces the charger's efficiency. In evaluation, the character of the battery voltage and cutting-edge. You may additionally modify the output electricity and output performance for constant parameters by adjusting the input voltage and switching frequency, respectively. The control parameters had been positioned the usage of a research desk.

5. CONCLUSION

This article proposes a wi-fi electric powered vehicle (EV) battery charger primarily based on the voltage fed collection compensation structure and info the way to track it. Improvements in performance over a extensive variety of input versions were performed when suitable modifications were proposed for the full-bridge dc-dc converter. Another manner to decrease the entire fee is by way of removing the need for a effective CPU. In order to gain ZVZCS with less manipulate complexity, the theoretical evaluation and fashions had been given. For the entire load variety, the simulation outcomes confirmed that the advised topology is in ZVZCS circumstance. Since the proposed approach made use of a low-value dc link and clear out capacitance values, there was reduced enter/output voltage and current ripple. For both battery and resistive

hundreds, a first-rate efficiency of ninety one.26 percentage changed into reached.

REFERENCES

- [1] M. Granovskii, I. Dincer, and M. A. Rosen, "Economic and environmental comparison of conventional, hybrid, electric and hydrogen fuel cell vehicles," *J. Power Sources*, vol. 159, no. 2, pp. 1186–1193, 2006.
- [2] S. B. Peterson, J. Whitacre, and J. Apt, "The economics of using plug-in hybrid electric vehicle battery packs for grid storage," *J. Power Sources*, vol. 195, no. 8, pp. 2377–2384, 2010.
- [3] Y. Zhou, M. Wang, H. Hao, L. Johnson, and H. Wang, "Plug-in electric vehicle market penetration and incentives: A global review," *Mitigation Adaptation Strategies Global Change*, vol. 20, no. 5, pp. 777–795, 2015.
- [4] B. Nykvist and M. Nilsson, "Rapidly falling costs of battery packs for electric vehicles," *Nature Climate Change*, vol. 5, no. 4, pp. 329–332, 2015.
- [5] W. Zhang and C. C. Mi, "Compensation topologies of high-power wireless power transfer systems," *IEEE Trans. Veh. Technol.*, vol. 65, no. 6, pp. 4768–4778, Jun. 2016.
- [6] K. Mude and K. Aditya, "Comprehensive review and analysis of two-element resonant compensation topologies for wireless inductive power transfer systems," *Chin. J. Elect. Eng.*, vol. 5, no. 2, pp. 14–31, 2019.
- [7] Y. Jiang, L. Wang, Y. Wang, J. Liu, X. Li, and G. Ning, "Analysis, design, and implementation of accurate ZVS angle control for EV battery charging in wireless high-power transfer," *IEEE Trans. Ind. Electron.*, vol. 66, no. 5, pp. 4075–4085, May 2019.
- [8] Y. Jiang, L. Wang, Y. Wang, J. Liu, M. Wu, and G. Ning, "Analysis, design, and implementation of WPT system for EV's battery charging based on optimal operation frequency range," *IEEE Trans. Power Electron.*, vol. 34, no. 7, pp. 6890–6905, Jul. 2019.
- [9] D. H. Tran, V. B. Vu, and W. Choi, "Design of a high-efficiency wireless power transfer

system with intermediate coils for the on-board chargers of electric vehicles,” IEEE Trans. Power Electron., vol. 33, no. 1, pp. 175–187, Jan. 2018.

[10] S. Moon and G.-W. Moon, “Wireless power transfer system with an asymmetric four-coil resonator for electric vehicle battery chargers,” IEEE Trans. Power Electron., vol. 31, no. 10, pp. 6844–6854, Oct. 2016.

[11] O. C. Onar, M. Chinthavali, S. L. Campbell, L. E. Seiber, and C. P. White, “Vehicular integration of wireless power transfer systems and hardware interoperability case studies,” IEEE Trans. Ind. Appl., vol. 55, no. 5, pp. 5223–5234, Sep./Oct. 2019.

[12] S. Li, W. Li, J. Deng, T. D. Nguyen, and C. C. Mi, “A double-sided LCC compensation network and its tuning method for wireless power transfer,” IEEE Trans. Veh. Technol., vol. 64, no. 6, pp. 2261–2273, Jun. 2015.

[13] C. Liu, S. Ge, Y. Guo, H. Li, and G. Cai, “Double-LCL resonant compensation network for electric vehicles wireless power transfer: Experimental study and analysis,” IET Power Electron., vol. 9, no. 11, pp. 2262–2270, 2016.

[14] C. Xiao, D. Cheng, and K. Wei, “An LCC-C compensated wireless charging system for implantable cardiac pacemakers: Theory, experiment, and safety evaluation,” IEEE Trans. Power Electron., vol. 33, no. 6, pp. 4894–4905, Jun. 2018.

[15] Y. Chen, H. Zhang, S.-J. Park, and D.-H. Kim, “A switching hybrid LCC-S compensation topology for constant current/voltage EV wireless charging,” IEEE Access, vol. 7, pp. 133924–133935, 2019.

[16] Y. Zhang, Z. Yan, T. Kan, Y. Liu, and C. C. Mi, “Modelling and analysis of the distortion of strongly-coupled wireless power transfer systems with SS and LCC–LCC compensations,” IET Power Electron., vol. 12, no. 6, pp. 1321–1328, 2019.

[17] W. Li, H. Zhao, J. Deng, S. Li, and C. C. Mi, “Comparison study on SS and double-sided

LCC compensation topologies for EV/PHEV wireless chargers,” IEEE Trans. Veh. Technol., vol. 65, no. 6, pp. 4429–4439, Jun. 2016.

[18] G. N. B. Yadav and N. L. Narasamma, “An active soft switched phaseshifted full-bridge dc–dc converter: Analysis, modeling, design, and implementation,” IEEE Trans. Power Electron., vol. 29, no. 9, pp. 4538–4550, Sep. 2014.

[19] M. Pahlevaninezhad, P. Das, J. Drobnik, P. K. Jain, and A. Bakhshai, “A novel ZVZCS full-bridge dc/dc converter used for electric vehicles,” IEEE Trans. Power Electron., vol. 27, no. 6, pp. 2752–2769, Jun. 2012.

[20] V. R. K. Kanamarlapudi, B. Wang, P. L. So, and Z. Wang, “Analysis, design, and implementation of an APWM ZVZCS full-bridge dc–dc converter for battery charging in electric vehicles,” IEEE Trans. Power Electron., vol. 32, no. 8, pp. 6145–6160, Aug. 2017.

[21] J. K. Nama, M. Srivastava, and A. K. Verma, “Modified inductive power transfer topology for electrical vehicle battery charging using auxiliary network to achieve zero-voltage switching for full load variations,” IET Power Electron., vol. 12, no. 10, pp. 2513–2522, 2019.

[22] M. Srivastava, P. S. Tomar, and A. K. Verma, “A modified duty cycle frequency control soft switching of full bridge dc-dc converter for electric vehicle battery charging,” in Proc. 8th IEEE India Int. Conf. Power Electron, 2018, pp. 1–5.

[23] J. K. Nama, P. S. Tomar, M. Srivastava, and A. K. Verma, “An efficient wireless topology for electric vehicle battery charging,” in Proc. 8th IEEE India Int. Conf. Power Electron., 2018, pp. 1–6.

[24] Parashar Vidyut Udyog, Litz Wire—pdf catalogue, 2020. [Online]. Available: <https://pdf.indiamart.com/impdf/9435952930/MY-10389389/litz-wire.pdf>