International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 21 No. 4 (2025)



ijerst.editor@gmail.com

editor@ijerst.com

International Journal of Engineering Research and Science & Technology

ISSN 2319-5991 www.ijerst.com
Vol. 21, No. 4, 2025
© 2025 IJERST. All Rights Reserved

Research Paper

SEISMIC PERFORMANCE ASSESSMENT OF BRACED AND DAMPED STEEL STRUCTURES

Nangunoori Sandhya Rani[1], B. Naresh[2]

[1]M. Tech Student, Department of Civil engineering, JB Institute of Engineering and Technology, Hyderabad, Telangana 500075

[2]Assistant Professor, Department of Civil engineering, JB Institute of Engineering and Technology, Hyderabad, Telangana 500075

Abstract *Buildings may be higher protected against earthquakes if they may be constructed to face up to such natural screw ups. Although it's miles not possible to construct a building with a purpose to be completely safe towards earthquakes, earthquake-resistant production pursuits to create buildings which can be extra resilient to seismic pastime. Structures ought to be designed to face up to the maximum importance earthquake that is possibly to arise at their web site based on a given possibility on the way to comply with building requirements. Thus, inside the case of rare earthquakes, it's miles vital to avoid constructing collapse if you want to minimise casualties, and in the case of greater common earthquakes, it's far similarly critical to restrict the lack of functioning. Currently, earthquake resistant structures are generally designed using steel bracings or shear wall structures. These techniques are easy to put in, lessen deflection and shear, and are usually used in earthquake resistant construction. In this study, we examine those two structures with trendy constructing practices in excessive seismic zones.*

In this research, a G+20 storey metallic constructing is modelled the usage of ETABS software and analysed in push over evaluation in Zone IV condition. The design of earthquake resistant systems is then compared to 3 varieties of homes: general, steel bracings, and dampers. Story waft, tale shear, story second, building torsion, term, and model stiffness have been a number of the metrics assessed across the three constructing models: popular, bracings, and dampers.

Key words: *Earthquake, story drift, story shear, story moment, building torsion, time period, model stiffness.*

Received: 05-11-2025 Accepted: 15-12-2025 Published: 22-12-2025

1. INTRODUCTION

Earthquakes are herbal screw ups which can shake the principles of a constructing. Hot and in a molten circumstance, the Earth's indoors is. Lava rises to the surface, cools, and ultimately will become new land. In order for newly created land to keep floating, fresh material need to be able to attain the surface. Plate tectonics postulates that the entire Earth's surface is dynamically much like a chain of transferring plates. Earthquakes occur whilst those tectonic plates move in near proximity to each other or crash at their borders. So, areas towards the plate borders are more seismically active, even as the ones farthest from the bounds are less so. Subterranean explosions are one of the capacity reasons of earthquakes. Geology encompasses the study of earthquakes, which includes their causes and locations.

Earthquake engineering focusses on analyzing the features of earthquake ground motion and how it impacts constructed homes. Particularly, earthquake resistant structural layout focusses on how earthquakes affect homes and a way to construct them such that they could endure earthquakes with very little damage. Secondary damage to homes from herbal disasters like floods and landslides is regularly now not

included. A simple computer-based totally push-over evaluation is one way to design building frames which are at risk of seismic stresses in a performance-primarily based manner. Push over analysis has been pretty popular in the previous couple of a long time because of its effectiveness and ease of usage. Various eccentric steel frames constructed according to IS-800 (2007) are analysed for push-over and ductility behaviour within the modern have a look at.

Bracing system

When a constructing need to resist lateral forces like wind or seismic pressure, a braced frame is regularly the structural method of choice. Typically, structural steel—which may be used correctly in each anxiety and compression—makes up the members of a braced body.

Vertical masses are supported via the body's beams and columns, at the same time as lateral loads are taken up by the bracing machine. On the alternative hand, bracing may be a pain to position on the grounds that they mess with the façade's design and establishing placement. In response, bracing has turn out to be a ubiquitous indoors and outside architectural element of excessive-tech and publish-modernist buildings.

Dampers

Using dampers is one way to lessen the lateral pressure precipitated by using an earthquake, that's an vital attention in seismic structural upgrading. The building reviews a great quantity of stress during an earthquake. The shape absorbs or amortises this energy, which comes in forms: kinetic and capacity (strain). Material damping reduces vibration, which might otherwise be non-stop in a creation that doesn't have any damping. The following equation indicates the input electricity that a building gets from an earthquake:

$$E = E_k + E_s + E_n + E_d$$

The variables in this equation are the earthquake input electricity (E), the kinetic electricity (Ek), the amount of misplaced strength (Eh) as a result of inelastic deformation (Es), the quantity of amortised energy (Ed), and the reversible stress power (Es) in the elastic range. The use of strength dissipation systems, that are essential to seismic isolation structures, has been reserved for them. A variety of techniques exist for boosting damping, inclusive of the glide of a pliable metallic, the friction among metals, the movement of a piston inner a slimy substance, or the viscoelastic behaviour of substances like rubber.

Objectives of the study

The project's primary goals are as follows:

1. Investigating how buildings react to seismic events in accordance with IS 1893:2016
2. In zone IV, to design a building that can withstand earthquakes by making use of steel bracings.
3. Investigate the effects of seismic stress on multi-story G+20 steel buildings 3
4. In order to evaluate seismically resistant structures, we will compare their findings for story drift, shear force, bending moment, and building torsion.
5. Use pushover analysis to investigate ETABS's multi-story structures.

2. LITERATURE STUDY

JayaramNayak B et al.,(2018) This studies appears at how extraordinary bracing heights affect the seismic performance of metallic body structures with 3 dimensions. As a ways as bracing goes, there are 3 ranges: one storey, stories, and three stories. The studies compares the seismic performance of bare body structures to that of X-braced and diamond-braced frames with thing ratios (the ratio of the shape's height to its base width) starting from one to 4.

Mohd Mubeen et al.,(2015) This thesis presents the outcomes of a nonlinear pushover evaluation for excessive-upward push metal-framed homes that use various eccentric bracing designs. Steel bracings can be arranged in n approaches, along with diagonal, X, K, and V configurations, as well as chevron kind eccentric bracings. This

research located that a Special Moment Resisting Frame, which includes metallic bracing as a lateral load resisting mechanism, can restriction the displacement of the metal bare frame version.


Santosh shet et al.,(2017) Due to its high electricity and substantial use in metal body building in India, carbon steel frames are selected for this studies. We compared the outcomes of modelling the metal frame under push over analysis the use of Seismostruct software.

3. METHODOLOGY USED IN THE STUDY

Pushover analysis

A static non-linear approach, pushover analysis includes regularly growing the amplitude of structural hundreds within the lateral path of the structure according to a given preset sample. Conventional information is that a structure's fundamental mode governs its behaviour, with the predetermined sample defined as storey shear or basic mode bureaucracy. As the lateral force increases in amplitude, the non-linear behaviour of different structural parts is recorded, bearing in mind the identification of susceptible points and failure mechanisms. Furthermore, the ability of a structure to undergo a sure amount of enter motion, as described with the aid of a reaction spectrum, can be decided the use of pushover evaluation.

There are two styles of pushover evaluation: pressure managed and displacement managed. Gradual applications of the whole lateral force to the structure are achieved by way of pressure control. To offer the necessary horizontal force to push the shape laterally, the displacement control incrementally will increase the displacement of the pinnacle storey of the shape. In a fundamental horizontal translational mode, the distance across which the structure is pushed is proportional to l. Upon transitioning from an elastic to an inelastic country, the structure's stiffness matrix may additionally need to be adjusted in both forms of pushover analyses for each increment of the burden or displacement. Because it is feasible to run the analysis up to the appropriate amount of displacement (see fig. 3), displacement managed pushover analyses are frequently favoured over fore controlled ones.



Displacement

4. DESIGN CONSIDERATIONS AND MODELS USED

Analyses of G+ 20-story buildings in Zone IV seismic zones are conducted in ETABS in this paper.


Basic parameters considered for the analysis are

1. Utility of Buildings : Residential Building
2. No of Storey :21Stories (G+20Building)
3. Grade of concrete : M30
4. Grade of Reinforcing steel : Fe250
5. Type of construction : Steel framed structure
6. Dimensions of beam : ISWB400
7. Dimensions of column : ISWB600
8. Thickness of slab : 150mm
9. Height of bottom story : 4m
10. Height of Remaining story : 3m
11. Building height :63.3m
12. Live load : 3.5 KN/m^2
13. Dead load : 2 KN/m^2
14. Density of concrete : 25 KN/m^3
15. Loads considered in Buildings : Dead load, Live load, Floor load Earthquake ,Wind load
16. Seismic Zones : Zone IV and Zone V
17. Site type : II
18. Importance factor : 1
19. Response reduction factor : 5
20. Damping Ratio : 5%
21. Structure class : B


22. Basic wind speed : 44m/s
23. Wind design code : IS 875: 1987 (Part 3)
24. RCC design code : IS 456:2000
25. Steel design code : IS 800: 2007
26. Earth quake design code : IS 1893 : 2002 (Part 1).

Models in ETABS Software


General Building



Bracings Building



Dampers Building



5. RESULTS AND ANALYSIS

Pushover Analysis Plots and Results

FEMA 440 General Building results


Sd	Sa/g	Period sec
0	0	0
192.188	0.2454	1.776
364.809	0.44066	1.826



General Building

FEMA 440 Bracings Building results

Sd	Sa/g	Period sec
0	0	0
71.767	0.15221	1.378
87.061	0.18452	1.378




Bracings building

FEMA 440 Dampers Building results

Sd	Sa/g	Period sec
0	0	0
191.974	0.20857	1.925
194.002	0.21077	1.925

International Journal of Engineering Research and Science & Technology



Dampers building

The following graphs demonstrate the results of several models' pushover analyses performed on Zone IV. The graphs compare the highest values of base shear and time period in this seismic zone.


Target displacement Values



General Building




Bracings building



Dampers building

Comparison of base shear


S. No	Model Type	Base Shear Values in kN
1	General Building	364.8
2	Bracings Building	219.94
3	Dampers Building	305.3



Both the table and the graph show that, according to the pushover 440 FEMA plots, the general building model has a high base shear value but a low intensity value.

Comparison of Time period

S. No	Model Type	Time period Values
1	General Building	0.44
2	Bracings Building	0.466
3	Dampers Building	0.331



According to the data shown in the table and graph, the intensity of the value of the time period is lower in buildings with dampers and higher in buildings with high bracings, according to the pushover 440 FEMA plots.

6. CONCLUSIONS

The following findings had been drawn from the aforementioned research:

1. Earthquake resistant constructing design is possible with the help of bracing and dampers installed in G+20 structures, which lessen the effect of seismic hundreds at the buildings.

2. Compared to ordinary buildings and dampers, bracing in G+20 systems consequences in decrease displacement values.

3. From the pinnacle storey to the bottom storey in G+20, the fee of storey glide diminishes. Bracing structures lessen the severity of storey waft due to the fact the lateral load rises from the bracings.

4. In G+20, the fee of storey acceleration drops as one movements down the storeys. As a end result of the additional bracing pressure, the lateral load rises in damper structures, resulting in less extreme storey float.

Five. The storey shear force V is much less severe in dampers systems due to the fact the lateral load rises thanks to the presence of extra bracing load.

6. When using pushover analysis, it is seen that the storey bending second M is less excessive in bracings than in dampers.

7. Dampers have a storey torsion T cost with less depth.

8. In assessment to models with bracing systems and dampers, the bottom shear values derived from the model with out these additives are the largest.

REFERENCES

1. C. V. Alkuntel, M. V. Dhimate, M. B. Mahajan, S. Y. Shevale, S. K. Shinde and A. A. Raskar, “Seismic Analysis of Multi-storey Building having Infill wall, shear wall and Bracing” Imperial Journal of Interdisciplinary Research (IJIR), Volume: 02, Issue: 06, pp. 1522-1524, ISSN: 2454-1362, 2016
2. Saket Yadav, Dr. Vivek Garg, “Advantage of Steel Diagrid Building Over Conventional Building” International Journal of Civil and Structural Engineering Research (ISSN), Volume: 03, Issue: 01, pp. 394-406, September 2015
3. Anil Baral, Dr. S. K. Yajdani, “Seismic Analysis of RC framed building for different positions for shear wall” International Journal Of Innovative Research In Science (IJIRSET), volume: 04, Issue: 05, pp. 3346-3353, eISSN: 2319-8753, p-ISSN: 2347-6710, May 2015
4.]Rohit Kumar Singh, Vivek Garg, Abhay Sharma, “Analysis and Design of Concrete diagrid building and its comparison” International Journal of Science, Engineering and Technology (IJSET), Volume: 02, Issue; 06, ISSN: 2348-4098, pp. 1330-1337, August 2014.
5. Ugale Ashish B., RautHarshalata R., “Effect of Steel Plate Shear Wall on Behaviour of Structure” International Journal of Civil Engineering Research, Volume: 05, Issue: 02, pp. 295-300, ISSN: 2278-3652, November 2014.
6. G.S Hiremath, Md. Saddam Hussain, “Effect of Change in Shear Wall Location With Uniform and Varying Thickness In High Rise Building” International Journal of Science and Research (IJSR), Volume: 3, Issue: 10, pp. 284-288, ISSN: 2319-7064, October 2014.

7. U. L. Salve, R.S. Londhe, " Effect of Curtailed Shear Wall on Storey Drift of High Rise Buildings Subjected to Seismic Loads", IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE), Volume 11, Issue 4, pp. 45-49, e-ISSN: 2278-1684, p-ISSN: 2320-334, July 2014.
8. Nishith B. Panchal, Vinubhai R. Patel, "Diagrid Structural System: Strategies to Reduce Lateral Forces on High-Rise Buildings" International Journal of Research in Engineering and Technology (IJRET), Volume: 03, Issue: 04, pp. 374-378, April 2014
9. Nitin Choudhry, MahendraWadia, "Pushover Analysis of R.C. Framed Building with Shear Wall" IOSR Journal of Mechanical and Civil Engineering (IOSR-JMCE), Volume: 11, Issue: 02, pp.09-13, e-ISSN: 2278-1684, pISSN: 2320-334X, March-April 2014