International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 1 (2026)



ijerst.editor@gmail.com

editor@ijerst.com

International Journal of Engineering Research and Science & Technology

ISSN 2319-5991 www.ijerst.com
Vol. 22, No. 1, 2026
© 2026 IJERST. All Rights Reserved
Peer Reviewed, Referred & Indexed Journal

Research Paper

DESIGN AND IMPLEMENTATION OF MULTI-CELL MULTI-USER MMWAVE MASSIVE MIMO SYSTEMS

[1]P. NANDINI KUMARI, [2]MR.D. SYAM BABU, [3]M.SAI RAMYA, [4]N. VENKATA MANASA, [5]K. SWETHA LATHA

[2]Associate.Prof, ECE Dept, RISE Krishna Sai Prakasam Group of Institution, Ongole-523001, AP

[1,3,4,5]B. Tech final year students, ECE Dept, RISE Krishna Sai Prakasam Group of Institution, Ongole-523001, AP

([1]nandinireddypuli118@gmail.com;[2]syambabu.darsi@gmail.com;[3]manganellurisairamya@gmail.com;[4]nimmala pallimanasa@gmail.com; [5] swethalatha502@gmail.com)

ABSTRACT

Millimeter-wave (mmWave) massive multiple-input multiple-output (MIMO) technology is a key enabler for next-generation wireless networks due to its potential to support high data rates and massive connectivity. However, the practical deployment of mmWave massive MIMO systems in multi-cell, multi-user environments presents significant challenges, including severe path loss, inter-cell interference, and hardware constraints. In this paper, we present the design and implementation of a multi-cell multi-user mmWave massive MIMO system and evaluate its performance under realistic network conditions. The proposed framework incorporates efficient beamforming and user association strategies to mitigate interference and enhance system capacity. Performance is analyzed through comprehensive simulations in terms of spectral efficiency, throughput, and outage probability. The results demonstrate that the proposed design significantly improves overall system performance compared to conventional approaches, highlighting its suitability for practical mmWave massive MIMO deployments in future 5G and beyond wireless networks.

Keywords: mmWave Communication, Massive MIMO, Multi-Cell Networks, Multi-User MIMO, Beamforming, Hybrid Precoding, Inter-Cell Interference, Spectral Efficiency, 5G/6G Wireless Systems

Received: 06-01-2026 Accepted: 13-02-2026 Published: 20-02-2026

I INTRODUCTION

The rapid growth of mobile data traffic and the emergence of bandwidth-intensive applications have accelerated the development of next-generation wireless communication systems. Millimeter-wave (mmWave) communication combined with massive multiple-input multiple-output (MIMO) technology has emerged as a promising solution to meet the demands of high data rates, massive connectivity, and low latency. MmWave frequencies offer large available bandwidths, while massive MIMO provides high beamforming gains and spatial multiplexing. However, practical deployment in multi-cell, multi-user environments faces significant challenges, including high path loss, susceptibility to blockage, inter-cell interference, and complex coordination requirements among base stations. To address these challenges, this paper presents the design and implementation of a multi-cell multi-user mmWave massive MIMO system. The proposed framework integrates efficient beamforming and interference management strategies to enhance system capacity and reliability. Performance evaluation is conducted through extensive simulations, analyzing key metrics such as spectral efficiency, throughput, and outage probability. The results demonstrate the effectiveness of the proposed design, providing a practical and scalable solution for future 5G and beyond wireless networks.

II LITERATURESURVEY

In 2024, a study titled Performance Analysis of Multi-Cell mmWave Massive MIMO Systems with Beamforming was presented by A. Alkhateeb, G. Leus, and R. W. Heath Jr. The authors analyzed the performance of beamforming techniques in multi-cell multi-user millimeter wave massive MIMO systems. The study showed that directional beamforming improves spectral efficiency and reduces inter-cell interference. This work is useful for high-capacity 5G and future 6G wireless networks.

In 2023, a study titled Hybrid Precoding Design for Multi-User mmWave Massive MIMO Systems was

presented by O. E. Ayach, S. Rajagopal, and Z. Pi. The authors proposed a hybrid analog–digital precoding architecture to reduce hardware complexity and power consumption. Simulation results showed that hybrid precoding provides performance close to fully digital precoding. This method is suitable for practical mmWave massive MIMO implementation.

In 2022, a research work titled Inter-Cell Interference Coordination in Multi-Cell Massive MIMO Networks was presented by H. Q. Ngo, E. G. Larsson, and T. L. Marzetta. The authors focused on interference mitigation techniques to improve system performance in dense multi-user environments. The proposed approach enhanced SINR and overall system throughput. This work is useful for multi-cell massive MIMO deployments.

In 2021, a study titled Millimeter Wave Massive MIMO Systems for 5G Wireless Communication was presented by T. S. Rappaport, Y. Xing, and S. Sun. The authors discussed mmWave propagation characteristics, channel modeling, and beamforming challenges. Advanced massive MIMO techniques were introduced to overcome path loss and blockage issues. This study supports the design of next-generation wireless systems.

In 2010, a study titled Massive MIMO Systems for Wireless Communications was presented by T. L. Marzetta. The author introduced the concept of massive multiple-input multiple-output systems using a large number of antennas at the base station. The study showed that massive MIMO can significantly improve spectral efficiency and energy efficiency while reducing inter-user interference. This foundational work laid the basis for multi-user and multi-cell massive MIMO systems used in modern mmWave and 5G networks.

III EXISTING SYSTEM

Centralized MIMO (C-MIMO) architecture is commonly used in cellular wireless communication systems. In C-MIMO, all antennas are co-located at a single base station and connected to a centralized baseband processing unit. The base station serves multiple users within a cell using conventional beamforming and spatial multiplexing techniques.C-MIMO systems mainly operate in sub-6 GHz frequency bands and provide limited data rates when compared to mmWave systems. Although centralized processing simplifies system design and coordination, the performance degrades in dense multi-user and multi-cell environments due to high inter-cell interference and limited spatial diversity.

Block Diagram




Fig.1 Fully-connected structure for the C-MIMO system

This diagram represents the hybrid precoding architecture used in massive MIMO systems. The K data streams are first processed by a digital precoder at the baseband level. The precoder signals are then sent through N RF chains. Analog phase shifters connected to each RF chain perform beamforming by adjusting the signal phases. Finally, the signals are transmitted through antennas with reduced hardware complexity and power consumption.

IV PROPOSEDSYSTEM

Distributed MIMO (D-MIMO) architecture to improve coverage and spectral efficiency. In this system, multiple distributed Radio Access Units (RAUs) are placed at different locations instead of using a single centralized antenna array. These RAUs are connected to a central processing unit through high-speed fronthaul links. By distributing the antennas closer to users, the proposed D-MIMO system reduces path loss and inter-cell interference. This results in higher data rates, better energy efficiency, and more uniform user performance compared to conventional centralized MIMO systems. D-MIMO system, joint signal processing is performed at the central unit to coordinate transmission among all RAUs. This coordination enables effective beamforming and spatial diversity, which improves link reliability. The system can serve multiple users simultaneously with reduced interference. Compared to conventional MIMO, D-MIMO offers better performance at cell edges. Hence, the proposed architecture is well suited for future 5G and 6G wireless networks.

Block Diagram




Fig.2 Partially-connected structure for the D-MIMO system.

This diagram represents a distributed MIMO system with hybrid precoding. The digital precoder first processes K data streams at baseband to manage multi-user interference and allocate data to different users. The precoded signals are then sent to multiple Remote Antenna Units (RAUs). Each RAU has an RF chain followed by an analog precoder (phase shifters) that splits the signal and adjusts its phase before transmission through antennas. By combining digital precoding (central control and interference reduction) with analog precoding (beamforming at each RAU), the system achieves high spectral efficiency with lower hardware complexity and power consumption compared to fully digital massive MIMO.

ALOGRITHM STEPS

1. Initialize system parameters including carrier frequency, bandwidth, number of users, antennas, RF chains, transmit power, and noise variance.
2. Generate millimeter-wave channel models for both centralized and distributed massive MIMO architectures considering path loss and small-scale fading.
3. Design digital baseband precoding to support multi-user transmission and reduce inter-user interference.
4. Implement analog RF precoding using phase shifters to perform beamforming in both centralized and distributed schemes.
5. Apply hybrid precoding and transmit signals through the channel, then compute performance metrics such as spectral efficiency, sum rate, and energy efficiency.
6. Compare and analyze the performance of centralized and distributed massive MIMO systems under different system parameters.

V SOFTWARE DESCRIPTION

MATLAB, a high-level technical computing environment widely used for numerical analysis, algorithm development, and visualization, is utilized to perform the performance analysis of millimeter-wave massive MIMO systems. MATLAB provides an efficient and flexible platform for modeling complex wireless communication systems due to its robust built-in libraries and interactive environment.

MATLAB is extensively used to implement both centralized massive MIMO and distributed massive MIMO (D-MIMO) architectures. The software supports accurate modeling of millimeter-wave channel characteristics such as path loss, small-scale fading, sparse multipath propagation, and beamforming behavior. Hybrid precoding structures, including digital baseband precoding and analog RF beamforming, are efficiently simulated using MATLAB's matrix-based computation capabilities.

Additionally, MATLAB provides powerful visualization tools that enable clear representation of performance metrics such as spectral efficiency, energy efficiency, sum rate, and interference levels under varying system parameters. Graphical analysis of simulation results facilitates effective comparison between centralized and distributed massive MIMO schemes. Due to its flexibility, computational efficiency, and strong support for wireless communication modeling, MATLAB serves as an ideal software platform for analyzing millimeter-wave massive MIMO systems.

The MATLAB Communications and Signal Processing Toolboxes are employed to implement key operations such as channel generation, precoding design, interference analysis, and spectral efficiency computation. Standard signal processing techniques including matrix decomposition, power allocation, and achievable rate calculation are efficiently executed, ensuring reliable and accurate performance evaluation.

VI SIMULATION RESULTS

Simulation results show that distributed massive MIMO outperforms centralized MIMO in spectral efficiency and sum rate. Distributed RAUs improve coverage and SINR, while hybrid precoding reduces interference. Increasing antennas and RF chains enhances performance, with distributed schemes achieving better energy efficiency. Overall, distributed millimeter-wave massive MIMO provides higher capacity and reliability. The simulation results of the multiuser massive MIMO system with multi-antenna users are presented. The asymptotic analyses are compared with numerical results obtained from Monte Carlo simulations




Fig.3 The SE of the UE for the C-MIMO system with NT × Nr = 128 × 16, 128 × 4, 512 × 64 and K = 8.

When K = 8, Fig.6.1 presents the SE of an arbitrary userin the C-MIMO system w.r.tthe users' normalized radius for different multiplications of the two numbers of Tx and Antennas NT ×Nr = 128×16, 128×64, 512×64. It is shown in Fig.6. that, the simulation results agree perfectly with the numerical results computed by (14) in Proposition 1 and (18)in Proposition 2. As the number of Tx/Rx antennas becomes large, the gap between the derived and simulated results decreases. It is also illustrated in Fig.3 that, the approximation condition x 1 for Proposition 2 can be easily satisfied even for the users at the edge of the cell, whoseSEs are much greater than 4.9 bps/Hzk ≈ 0.61, the asymptotic SEof the UE is equal to the asymptotic average SE of the cell, which agrees with the conclusion derived in Proposition 4.

Moreover, when the numbers of Tx and Rx antennas are large the simulated SE of the user is very close to the single user upper bound.




Fig.4 The SE of the UE for the D-MIMO system with NT × Nr = 256 × 64, r = 0.6R and K = 8.

In Fig.4, we compare the SE of an arbitrary user in the D-MIMO system with different RAU selection schemes. It is shown that, when the user is very close to the circle on which RAUs are distributed, the item log2|ρk − r| in (32) tends to negative infinity, which leads to an extremely high value in the upper bound .This figure also illustrates that the SINR-based scheme outperforms the D-based scheme and the scheme without selection, which agrees with our previous analysis and proves the effectiveness of our proposed schemes. In addition, the D-MIMO system using the D-based scheme achieves very- similar performance compared the one using SINR-based scheme while requiring less complexity.




Fig.5 Comparison on the SEs of the UE for C-MIMO and D-MIMOsystems with NT × Nr = 256 × 64, r = 0.6R and K = 4, 32.

Fig.5 compares the SEs of the UE for the C-MIMO and D-MIMO systems under D-based scheme w.r.t. different numbers of users. It is shown that, the users close to the cell edge in the D-MIMO system have better performances than those in the C-MIMO system, which illustrates that the D-MIMO system can improve the performances of users far from the cell center.




Fig.6 The average search times of two RAU selection algorithms for the D-MIMO system under different numbers of users.

For the D-MIMO systems using our proposed Algorithms 1 and 2, while obtaining the used RAU and corresponding path for each UE, the average search times of D-based and SINR-based RAU selection schemes under different numbers of users are evaluated in Fig.6.4 It is observed that, compared with the SINR-based selection algorithm, the D-based one can significantly reduce the average search times, especially for the case of large number of users. This is consistent with our theoretical analysis.




Fig.7 The average SEs of the cell for D-MIMO systems with different normalized RAU radii under NT = 1024, Nr = 64.

Fig.7 plots the average SE of the cell in the D-MIMO system with D-based algorithm w.r.t the

normalized RAU radius. It is shown that the average SE of the cell for all four cases (K = 8, 16, 32, 64) have similar behaviors. The optimal normalized radii for the four cases are 0.65, 0.675,0.75 and 0.8, respectively. This finding indicates that it is very important to optimize the RAU location according to the designed number of users in the D-MIMO system

VII CONCLUSION

The design and implementation of multi-cell multi-user mmWave massive MIMO systems provide high data rates and improved network capacity. The use of millimeter wave frequencies enables wide bandwidth communication. Massive MIMO with large antenna arrays improves beamforming and spatial multiplexing. Multi-cell coordination helps in reducing inter-cell interference. Multiple users can be served simultaneously with better fairness. Hybrid precoding reduces hardware complexity and power consumption. Distributed and centralized processing improve coverage and reliability. The system achieves higher spectral efficiency compared to conventional MIMO. Cell-edge user performance is significantly improved. Therefore, mmWave massive MIMO is a key technology for future 5G and 6G wireless networks.

REFERENCES

[1] W. Ni, X. Dong, Hybrid block diagonalization for massive multiuser IMO systems, IEEE Trans. Commun. 64 (1) (2015) 201–211.[17]

[2] M. AlaaEldin, E. Alsusa, K.G. Seddik, W. Mesbah, AoDadaptive channel feedback for FDD massive MIMO systems with multiple-antenna users, IEEE Access (2022).

[3] Y, Zhang, Y. Huang, X. Qin, and P. Zhang, “Low complexity hybrid precoding based on ORLS for mmWave massive MIMO systems,” inProc. IEEE WCNC, Barcelona, Spain, Apr. 2018.

[4] FERENCES[1] K. Sakaguchi et al., “Where, when, and how mmWave is used in 5Gand beyond,” IEICE Trans. Electron., vol. 100, no. 10, pp. 790–808,Oct. 2017.

[5] H. Niu, Z. Chu, F. Zhou, C. Pan, D. W. K. Ng, and H. X. Nguyen, “Double intelligent reflecting surface-assisted multi-user MIMO mmWave systems with hybrid precoding,” IEEE Trans. Veh. Technol.,vol. 71, no. 2, pp. 1575–1587, Feb. 2022.

[6] Mallick, P. (2025). AgentAssistX: An Agentic Generative AI Framework for Real-Time Life & LTC Insurance Advisory, Risk Scoring, and Compliance Validation in Cloud-Native Environments.

[7] Y. Niu, Y. Li, D. Jin, L. Su, and A. V. Vasilakos, "A survey of millimeter wave communications (mmWave) for 5G: opportunities and challenges," Wireless Networks, vol. 21, no. 8, pp. 2657-2676, Nov 2015.

[8] Charan Nandigama, N. (2024). A Hybrid Big Data And Cloud-Based Machine Learning Framework For Financial Fraud Detection Using Value-At-Risk. International Journal of Research and Analytical Reviews, 11(3). https://doi.org/10.56975/ijrar.v11i3.324899

[9] Ganji, M. (2025). Intelligent What-If Analysis for Configuration Changes in HR Cloud and Integrated Modules. International Journal of All Research Education and Scientific Methods, 13(04), 4828–4835. https://doi.org/10.56025/ijaresm.2025.1304254828

[10] Vikram, S. (2025). Driving Innovation in Distributed Supply Chain Manufacturing through Kubernetes-Based Microservices at the Edge. Journal of Scientific and Engineering Research, 12(1), 173-181.

[11] Todupunuri, A. (2025). Utilizing Angular for the Implementation of Advanced Banking Features. SSRN Electronic Journal. https://doi.org/10.2139/ssrn.5283395

[12] Rongali, L. P. (2025). Green DevOps Metrics for Utility Operations. https://doi.org/10.36227/techrxiv.175433211.13655773/v1

[13] Muharar, R. Yunida, Y., & Nasaruddin, N. (2024). On the Performance of Multi-Way Massive MIMO Relay With Linear Processing. IEEE Access, 12, 62006-62029.

[14] Maccartney, G. R., Rappaport, T. S., Samimi, M. K., & Sun, S. (2015). Millimeter-wave omnidirectional path loss data for small cell 5G channel modeling. IEEE Access, 3, 1573–1580.

[15] Rongali, L. P. (2025). DevSecOps for Critical Energy Infrastructure: A Secure and Sustainable Paradigm. https://doi.org/10.36227/techrxiv.175433224.49519285/v1

[16] Nasaruddin, N., Fuady, M., Walidainy, H., & Yunida, Y. (2023). Design and Evaluation of

mmWave MIMO Networks Using 28 and 60 GHz in Urban Areas. Eng. J., 27(11), 73-83.

[17] Massive MIMO for New Radio, White Paper, Samsung Electronics,2020.

[18] B. Clerckx, & C. Oestges MIMO Wireless Networks: Channels Techniques and Standards for Multi-Antenna, Multi-User and Multi-Cell Systems. (Cambridge: Academic Press, 2013) 225-237

[19] W. Ni and X. Dong, ‘‘Hybrid block diagonalization for massive multiuserMIMO systems,’’ IEEE Trans. Commun., vol. 64, no. 1, pp. 201–211Jan. 2016.