CUSTOMER SEGMENTATION FOR ONLINE E-COMMERCE USING CLUSTERING ALGORITHMS

[1]Dr. B.R.S.REDDY, [2]JANYAVULA REETHIKA, [3]KONDAVEETI BALA NAGA TRIPURA SUNDARI, [4]YALAVARTHI KUMAR SWAMY,[5]PUTTI MOHAN KUMAR

[1]Professor, [2345]Students, Department of Computer Science and Engineering, SRI VASAVI INSTITUTE OF ENGINEERING & TECHNOLOGY, NANDAMURU, ANDHRA PRADESH

ABSTRACT

The rapid expansion of online e-commerce platforms has generated massive volumes of customer transactional and behavioral data, creating new opportunities for data-driven business decision-making. However, many organizations struggle to effectively utilize this data for understanding customer purchasing patterns and developing personalized marketing strategies. Traditional segmentation techniques based on demographic attributes or manual rules often fail to capture the complexity of modern consumer behavior, resulting in ineffective targeting and reduced customer engagement. This study proposes a machine learning-based approach for customer segmentation in online e-commerce environments using clustering algorithms. The system utilizes unsupervised learning techniques, specifically K-Means clustering and hierarchical clustering, to identify meaningful customer groups without requiring predefined labels. The dataset undergoes several preprocessing steps including missing value handling, duplicate removal, normalization, and feature engineering through Recency, Frequency, and Monetary (RFM) analysis to enhance clustering effectiveness. The optimal number of clusters is determined using the Elbow Method and Silhouette Score to ensure accurate segmentation. Additionally, Principal Component Analysis (PCA) is applied to reduce dimensionality and visualize clusters for better interpretability. The proposed system enables businesses to categorize customers into distinct behavioral groups such as high-value customers, frequent buyers, and low-engagement users. These insights help organizations design targeted marketing campaigns, improve customer retention strategies, and enhance overall business performance. Experimental results demonstrate that clustering-based segmentation provides valuable insights into customer purchasing patterns and supports data-driven decision-making in e-commerce platforms. The proposed approach highlights the effectiveness of machine learning techniques in transforming raw transactional data into actionable customer intelligence.

I INTRODUCTION

The growth of digital commerce has transformed the global retail landscape, enabling businesses to collect vast volumes of consumer transaction data through online platforms [1]. E-commerce websites continuously generate data related to customer purchases, browsing behavior, and product preferences, providing valuable information for analyzing customer behavior and improving business strategies [2]. Organizations increasingly rely on data analytics to extract meaningful insights from this information to enhance customer experience and increase profitability [3]. Customer segmentation is a critical process that divides customers into groups based on similar characteristics, allowing businesses to design

personalized marketing strategies and improve service delivery [4]. Traditional segmentation methods often rely on demographic attributes such as age, gender, and location, which may not fully capture behavioral patterns in modern online markets [5]. As e-commerce environments become more competitive, businesses must adopt advanced analytical approaches to understand complex purchasing behaviors [6]. Data mining techniques play an important role in identifying hidden patterns and relationships within large datasets [7]. Machine learning algorithms have emerged as powerful tools for discovering insights from large-scale data generated by online platforms [8]. These techniques enable automated analysis of customer behavior without requiring manual intervention [9]. Unsupervised learning methods such as clustering are particularly effective for grouping customers with similar characteristics when labeled data is unavailable [10]. Clustering techniques allow organizations to identify customer groups based on behavioral similarity rather than predefined assumptions [11]. K-Means clustering is one of the most widely used algorithms for customer segmentation due to its simplicity and efficiency [12]. Hierarchical clustering provides another approach that organizes customers into nested groups based on similarity relationships [13]. The combination of clustering techniques with feature engineering methods can significantly improve segmentation accuracy [14]. Recency, Frequency, and Monetary (RFM) analysis is widely used to capture customer purchasing behavior in marketing analytics [15].

Recent advancements in data science have further enhanced the ability of organizations to perform large-scale customer analysis using machine learning algorithms [16]. By analyzing purchasing frequency, spending behavior, and engagement patterns, businesses can identify high-value customers and design targeted promotional campaigns [17]. Effective segmentation helps companies allocate resources efficiently and improve customer retention strategies [18]. Visualization techniques such as Principal Component Analysis (PCA) help represent complex data structures in lower dimensions for easier interpretation [19]. These visualization tools assist analysts in understanding cluster structures and identifying behavioral trends among customers [20]. Data preprocessing techniques such as normalization, duplicate removal, and missing value handling play a crucial role in improving model performance [21]. Without proper preprocessing, clustering algorithms may produce inaccurate or misleading segmentation results [22]. Determining the optimal number of clusters is another important step in clustering-based segmentation [23]. Evaluation methods such as the Elbow Method and Silhouette Score are commonly used to determine the most appropriate cluster configuration [24]. These evaluation techniques ensure that clusters are meaningful and well separated [25]. The use of clustering algorithms in e-commerce has shown promising results in identifying valuable customer groups and predicting purchasing behavior [26]. Businesses can use segmentation results to design personalized recommendations and targeted marketing campaigns [27]. This leads to improved customer engagement and higher conversion rates [28]. Moreover, data-driven segmentation allows organizations to better understand evolving consumer preferences in dynamic online markets [29]. Therefore, the application of machine learning-based clustering methods provides a powerful solution for analyzing large customer datasets and supporting strategic decision-making in modern e-commerce systems [30].

II LITERATURE SURVEY

Customer segmentation has been widely studied in marketing analytics as an effective technique for understanding consumer behavior and improving targeted marketing strategies [1]. Early research primarily focused on demographic-based segmentation methods that grouped customers according to basic attributes such as age, gender, income, and location [2]. While these approaches provided useful insights, they often failed to capture behavioral differences among customers with similar demographic characteristics [3]. With the rapid development of data mining technologies, researchers began exploring behavioral segmentation techniques using transactional data [4]. Data mining methods enable the extraction of hidden patterns from large datasets generated by online retail platforms [5]. Clustering algorithms have become a fundamental tool for performing unsupervised segmentation when labeled training data is unavailable [6]. Among various clustering methods, the K-Means algorithm has gained significant popularity due to its computational efficiency and ease of implementation [7]. K-Means partitions data into clusters based on similarity measures, allowing businesses to identify distinct groups of customers with similar purchasing behaviors [8]. Researchers have also explored hierarchical clustering approaches to reveal nested relationships among customer segments [9]. Hierarchical clustering constructs a tree-like structure that provides a comprehensive view of similarities among customers [10]. Several studies have demonstrated the effectiveness of combining clustering algorithms with behavioral metrics such as RFM analysis [11]. The RFM model evaluates customer value based on recency of purchases, purchase frequency, and total monetary spending [12]. This model has been widely adopted in marketing research to identify valuable and loyal customers [13]. Integrating RFM features with clustering algorithms helps improve segmentation accuracy and interpretability [14]. Recent studies have also incorporated dimensionality reduction techniques such as Principal Component Analysis to enhance visualization of customer segments [15].

In recent years, machine learning techniques have been increasingly applied to e-commerce analytics to address the challenges of large-scale customer data analysis [16]. Researchers have investigated hybrid clustering approaches that combine multiple algorithms to improve segmentation performance [17]. Some studies have proposed combining K-Means with hierarchical clustering to achieve more accurate cluster formation [18]. Others have explored density-based clustering algorithms for identifying complex cluster structures in customer datasets [19]. Data preprocessing has been recognized as an essential step in ensuring reliable clustering results [20]. Techniques such as normalization, feature scaling, and outlier removal help improve the quality of clustering models [21]. Determining the optimal number of clusters remains a key challenge in segmentation analysis [22]. Various evaluation methods such as the Elbow Method, Silhouette Score, and Davies-Bouldin Index have been proposed to address this issue [23]. These metrics help researchers evaluate cluster cohesion and separation to select the most appropriate segmentation structure [24]. Visualization techniques also play an important role in interpreting clustering results and communicating insights to business stakeholders [25]. PCA and multidimensional scaling are commonly used to represent high-dimensional data in two-dimensional space [26]. Several studies have shown that clustering-based segmentation can significantly improve marketing campaign effectiveness [27]. Businesses can identify high-

value customers and develop personalized product recommendations using segmentation insights [28]. Furthermore, segmentation models enable companies to optimize resource allocation and improve customer relationship management strategies [29]. Therefore, the integration of machine learning algorithms with advanced data analytics techniques provides a powerful framework for understanding customer behavior in modern e-commerce platforms [30].


III METHODOLOGY

The proposed system for customer segmentation in online e-commerce environments follows a systematic methodology consisting of data collection, preprocessing, feature engineering, clustering, and visualization stages. Initially, the dataset containing customer transaction records is collected from the e-commerce platform, including attributes such as purchase history, transaction dates, product categories, and spending amounts. During the preprocessing phase, the raw dataset is cleaned by handling missing values, removing duplicate records, and eliminating inconsistent entries that could negatively affect clustering performance. Feature scaling and normalization techniques are applied to ensure that all variables contribute equally to the clustering process. After preprocessing, feature engineering is performed using the Recency, Frequency, and Monetary (RFM) model to represent customer purchasing behavior effectively. Recency measures how recently a customer made a purchase, frequency represents how often purchases occur, and monetary value indicates the total amount spent by the customer. These features provide meaningful behavioral indicators that improve the effectiveness of clustering algorithms. Once the features are prepared, the optimal number of clusters is determined using evaluation methods such as the Elbow Method and Silhouette Score, which measure cluster compactness and separation. The K-Means clustering algorithm is then applied to group customers into distinct segments based on their behavioral similarities. In addition, hierarchical clustering is used to validate cluster structures and explore relationships among different customer groups. To enhance interpretability, Principal Component Analysis (PCA) is employed to reduce the dimensionality of the dataset and visualize cluster distributions in two-dimensional space. The resulting clusters are analyzed to identify customer segments such as high-value customers, frequent buyers, and low-engagement users. These insights allow businesses to design targeted marketing strategies, personalized recommendations, and customer retention programs. The overall methodology ensures that large volumes of e-commerce data can be effectively transformed into actionable customer intelligence for strategic decision-making.

IV SYSTEM DESIGN

The system design for the proposed customer segmentation framework is structured into multiple interconnected modules that collectively enable efficient processing and analysis of e-commerce customer data. The first component of the system is the data acquisition module, which collects transactional and behavioral data from the e-commerce platform. This dataset includes customer identifiers, purchase timestamps, product information, and transaction values. Once the data is collected, it is transferred to the data preprocessing module, where several cleaning operations are performed to ensure data quality. These operations include removing duplicate entries, handling missing values, and correcting inconsistent records. Data normalization techniques are also applied to standardize feature scales,

ensuring that variables with larger numerical values do not dominate the clustering process. Following preprocessing, the feature engineering module extracts meaningful behavioral indicators using the Recency, Frequency, and Monetary (RFM) model. This step transforms raw transactional data into structured features that effectively represent customer purchasing behavior. The engineered features are stored in a structured dataset that serves as input for clustering algorithms. The system also includes a cluster optimization module that determines the optimal number of clusters using evaluation metrics such as the Elbow Method and Silhouette Score. This module ensures that the segmentation results are both meaningful and statistically valid.



The next component of the system design is the clustering module, which performs customer segmentation using unsupervised machine learning algorithms. In this module, the K-Means clustering algorithm is implemented to partition customers into groups based on similarity in their behavioral attributes. The algorithm iteratively assigns customers to clusters and updates cluster centroids until convergence is achieved. Hierarchical clustering is also incorporated to provide an alternative segmentation perspective and validate cluster relationships. Once the clustering process is completed, the visualization module presents the segmentation results in an interpretable format. Principal Component Analysis (PCA) is applied to reduce the dimensionality of the dataset, enabling clusters to be visualized in two-dimensional space through scatter plots. These visualizations help analysts understand the structure and distribution of customer groups more clearly. Finally, the insights generated from the segmentation process are delivered through the analytics module, which provides business-oriented interpretations of each customer segment. For example, clusters may represent high-value customers, frequent buyers, occasional shoppers, or low-engagement users. These insights assist businesses in designing targeted marketing strategies, optimizing promotional campaigns, and improving customer relationship management. The modular design of the system ensures scalability, flexibility, and efficient processing of large-scale e-commerce datasets.

V PROPOSED SYSTEM

The proposed system introduces an intelligent machine learning framework for customer segmentation in online e-commerce platforms using clustering algorithms. The primary objective of the system is to analyze large volumes of customer transaction data and automatically group customers based on similarities in their purchasing behavior. Unlike traditional segmentation methods that rely on manual rules or predefined

demographic categories, the proposed system uses unsupervised learning techniques to discover hidden patterns in customer data. The system begins by collecting transactional data from the e-commerce platform, which includes purchase frequency, transaction amounts, product categories, and customer activity timelines. This data is then processed through a comprehensive preprocessing stage to remove noise and inconsistencies. Data cleaning operations such as duplicate removal, missing value handling, and feature normalization ensure that the dataset is suitable for machine learning analysis. After preprocessing, feature engineering is performed using the Recency, Frequency, and Monetary (RFM) model to capture key aspects of customer behavior. These RFM features provide a structured representation of customer engagement and purchasing value, which significantly improves clustering accuracy. The system then determines the optimal number of clusters using evaluation techniques such as the Elbow Method and Silhouette Score. These techniques analyze cluster compactness and separation to identify the most suitable segmentation structure.

Following the cluster optimization process, the K-Means clustering algorithm is applied to segment customers into distinct groups based on behavioral similarity. Each cluster represents a specific category of customers with similar purchasing characteristics. For example, one cluster may represent high-value customers who frequently purchase products and spend large amounts, while another cluster may represent occasional shoppers with lower spending patterns. Hierarchical clustering is also used to analyze relationships among clusters and validate segmentation results. To enhance interpretability, the proposed system integrates visualization techniques using Principal Component Analysis (PCA), which reduces high-dimensional data into a two-dimensional representation. This allows analysts to visually observe the separation between clusters and understand customer group distributions more effectively. The system also generates analytical reports describing the characteristics of each cluster, enabling businesses to develop targeted marketing strategies for different customer segments. By identifying valuable customer groups, organizations can design personalized promotions, loyalty programs, and recommendation systems that increase customer engagement and sales performance. Furthermore, the proposed system supports scalable data analysis, allowing it to process large e-commerce datasets efficiently. Overall, the integration of machine learning algorithms with advanced data preprocessing and visualization techniques provides an effective solution for understanding customer behavior and improving decision-making in modern e-commerce platforms.


VI RESULTS & DISCUSSION

The experimental results demonstrate the effectiveness of clustering algorithms in identifying meaningful customer segments within the e-commerce dataset. After preprocessing and feature engineering using the RFM model, the K-Means algorithm successfully grouped customers into distinct clusters based on their purchasing behavior. The optimal number of clusters was determined using the Elbow Method and Silhouette Score, which ensured well-defined and clearly separated clusters. Visualization using Principal Component Analysis provided a clear representation of cluster distributions and enabled better interpretation of segmentation results. The analysis revealed different types of customer groups such as high-value loyal customers, frequent buyers, moderate spenders, and low-engagement customers. These

segmentation insights help businesses design targeted marketing campaigns and personalized recommendations for each group. The results confirm that machine learning-based clustering techniques can effectively transform large volumes of raw e-commerce data into actionable business intelligence for improving customer relationship management and increasing overall sales performance.











VII CONCLUSION

Customer segmentation plays a vital role in modern e-commerce platforms by enabling businesses to better understand consumer behavior and develop personalized marketing strategies. This study presented a machine learning-based framework for customer segmentation using clustering algorithms to analyze large volumes of transactional data generated by online retail platforms. The proposed system utilized data preprocessing techniques to clean and normalize the dataset, ensuring reliable analysis. Feature engineering using the Recency, Frequency, and Monetary (RFM) model provided meaningful behavioral indicators that improved the accuracy of customer segmentation. The K-Means clustering algorithm was employed to group customers into distinct segments based on similarities in purchasing patterns, while hierarchical clustering was used to validate cluster relationships. Evaluation methods such as the Elbow Method and Silhouette Score helped determine the optimal number of clusters and ensured effective segmentation. Additionally, Principal Component Analysis was used for dimensionality reduction and visualization of clustering results, enabling clearer interpretation of customer groups. The experimental results demonstrated that clustering-based segmentation can successfully identify valuable customer

categories such as high-value customers, frequent buyers, and low-engagement users. These insights provide businesses with valuable information for designing targeted promotional campaigns, improving customer retention strategies, and enhancing customer relationship management. The proposed approach highlights the importance of data-driven decision-making in e-commerce environments and demonstrates the potential of machine learning techniques in transforming raw transactional data into actionable customer intelligence. Future work may involve integrating advanced deep learning techniques and real-time data analytics to further improve segmentation accuracy and support dynamic customer behavior analysis.

REFERENCES

1. Wedel, M., & Kamakura, W. (2012). Market Segmentation. Springer.
2. Han, J., Pei, J., & Kamber, M. (2011). Data Mining: Concepts and Techniques. Morgan Kaufmann.
3. Tan, P., Steinbach, M., & Kumar, V. (2019). Introduction to Data Mining. Pearson.
4. Kotler, P., & Keller, K. (2016). Marketing Management. Pearson.
5. Ngai, E., Xiu, L., & Chau, D. (2009). Application of data mining techniques in customer relationship management. Expert Systems with Applications.
6. Xu, R., & Wunsch, D. (2005). Survey of clustering algorithms. IEEE Transactions on Neural Networks.
7. Jain, A. (2010). Data clustering: 50 years beyond K-means. Pattern Recognition Letters.
8. Aggarwal, C. (2015). Data Mining: The Textbook. Springer.
9. Berry, M., & Linoff, G. (2011). Data Mining Techniques. Wiley.
10. Berson, A., Smith, S., & Thearling, K. (2000). Building Data Mining Applications for CRM. McGraw-Hill.
11. Hughes, A. (1994). Strategic Database Marketing. McGraw-Hill.
12. Fader, P., Hardie, B., & Lee, K. (2005). RFM and CLV. Marketing Science.
13. Chen, D., Sain, S., & Guo, K. (2012). Data mining for retail industry. International Journal of Information Management.
14. Dolnicar, S. (2003). Using cluster analysis for market segmentation. Marketing Bulletin.
15. Punj, G., & Stewart, D. (1983). Cluster analysis in marketing research. Journal of Marketing Research.
16. Kotu, V., & Deshpande, B. (2014). Predictive Analytics and Data Mining. Morgan Kaufmann.
17. Rokach, L., & Maimon, O. (2005). Clustering methods. Data Mining and Knowledge Discovery Handbook.
18. Larose, D. (2014). Discovering Knowledge in Data. Wiley.
19. Han, J., Kamber, M., & Pei, J. (2012). Data Mining Concepts and Techniques. Elsevier.
20. Witten, I., Frank, E., & Hall, M. (2016). Data Mining: Practical Machine Learning Tools. Morgan Kaufmann.

21. Tan, P. (2018). Introduction to Data Mining. Pearson.

22. Hastie, T., Tibshirani, R., & Friedman, J. (2009). The Elements of Statistical Learning. Springer.

23. Bishop, C. (2006). Pattern Recognition and Machine Learning. Springer.

24. James, G., Witten, D., Hastie, T., & Tibshirani, R. (2013). An Introduction to Statistical Learning. Springer.

25. Shmueli, G., Bruce, P., & Patel, N. (2016). Data Mining for Business Analytics. Wiley.

26. Provost, F., & Fawcett, T. (2013). Data Science for Business. O'Reilly.

27. Liu, B. (2011). Web Data Mining. Springer.

28. Davenport, T., & Harris, J. (2007). Competing on Analytics. Harvard Business

29. Press.

30. Chen, H., Chiang, R., & Storey, V. (2012). Business intelligence and analytics. MIS Quarterly.

31. Kelleher, J., Mac Namee, B., & D'Arcy, A. (2015). Fundamentals of Machine Learning. MIT Press.

32. Mahesh Ganji. (2025). Enhancing Oracle Cloud HR Reporting Through AI-Driven Automation. Journal of Science & Technology, 10(6), 28–36. https://doi.org/10.46243/jst.2025.v10.i06.pp28-36

33. Todupunuri, A. (2025). THE ROLE OF AGENTIC AI AND GENERATIVE AI IN TRANSFORMING MODERN BANKING SERVICES. American Journal of AI Cyber Computing Management, 5(3), 85–93. https://doi.org/10.64751/ajaccm.2025.v5.n3.pp85-93

34. Todupunuri, A. . (2024). Artificial Intelligence Ethics: Investigating Ethical Frameworks, Bias Mitigation, and Transparency in AI Systems to Ensure Responsible Deployment and Use of AI Technologies. International Journal of Innovative Research in Science,Engineering and Technology, 13(09), 1–14. https://doi.org/10.15680/ijirset.2024.1309002

35. Sushma Babburi. (2025). Token-Based Data Accounting System For Transparent Model Training And Cost Allocation. American Journal of AI Cyber Computing Management, 5(4), 463–474. https://doi.org/10.64751/ajaccm.2025.v5.n4.pp463-474

36. Snigdha Gaddam. (2025). SOFTWARE STACK PREPARED FOR AI TRANSITIONING FROM MODULES TO MODELS. American Journal of AI Cyber Computing Management, 5(4), 451–462. https://doi.org/10.64751/ajaccm.2025.v5.n4.pp451-462

37. Gaddam, S. INTELLIGENT SYSTEMS AND APPLICATIONS IN ENGINEERING.

38. Bajarang Bhagwat, V. (2023). Optimizing Payroll to General Ledger Reconciliation: Identifying Discrepancies and Enhancing

Financial Accuracy. JOURNAL OF ADVANCE AND FUTURE RESEARCH, 1(4). https://doi.org/10.56975/jaafr.v1i4.501636

39. Srinivasa Kalyan Immadi. (2025). Harnessing Artificial Intelligence In Oracle Hcm: Revolutionising Workforce Management With Automation And Predictive Analytics. International Journal of Data Science and IoT Management System, 4(4), 7–13. https://doi.org/10.64751/ijdim.2025.v4.n4.pp7-13

40. S. M. K. P. (2025). Cryptography in iOS: A Study of Secure Data Storage and Communication Techniques. International Journal on Science and Technology, 16(1). https://doi.org/10.71097/ijsat.v16.i1.1403

41. Suhasnadh Reddy Veluru, Sai Teja Erukude, and Viswa Chaitanya Marella. 2025. Multimodal Detection of Fake Reviews using BERT and ResNet-50. In 2025 4th International Conference on Innovative Mechanisms for Industry Applications (ICIMIA). IEEE, 877–882.

42. Cyril, H. P. (2025). Event-Driven Provisioning Architectures For Modern Telecom Networks: Overcoming Legacy Limitations And Enabling Autonomous 6g Operations. International Journal of Advanced Research in Computer Science, 16(6), 75–82. https://doi.org/10.26483/ijarcs.v16i6.7389

43. Jay Bharat Mehta. (2025). AUTONOMOUS PATCH VALIDATION FOR ZERO-DAY EXPLOITS IN ENTERPRISE CLOUDS. International Journal of Applied Mathematics, 38(4s), 1270–1285. https://doi.org/10.12732/ijam.v38i4s.685

44. Reddy, S. K. (2025). Hyperpersonalization driven by AI is expected to be at the Lead in shaping the future of loyalty rewards. Journal of Emerging Technologies and Innovative Research.

45. Reddy, S. K. R. (2021). Strengthening the Security of Loyalty Reward Systems: An In-Depth Analysis of Emerging Cyber Threats and Protection Mechanisms. Journal of Computational Analysis and Applications, 29(6).

46. Poojari, R. (2026). Privacy-Preserving Generative AI in Healthcare Systems Using Federated Learning Approaches. International Journal of Data Science and IoT Management System, 5(1), 78-88.

47. Uday Kumar Kalae. (2025). AN AUTOMATED SYSTEM FOR MANAGING HIGH-AVAILABILITY CLOUD INFRASTRUCTURE THROUGH INFRASTRUCTURE-ASCODE (IAC) PRACTICES. American Journal of AI Cyber Computing Management, 5(2), 42–50. https://doi.org/10.64751/ajaccm.2025.v5.n2.pp42-50

48. Saikumar, B. (2024). Optimizing Crew Scheduling and Absence Management using Microservices: Enhancing Reliability and Efficiency in Crew Management Systems. International Journal of Enhanced Research in Management & Computer Applications, 13(11), 50–55. https://doi.org/10.55948/ijermca.2024.0116

49. Saikumar, B. (2023). Enhancing Client Engagement through AI-Driven Real-Time Reporting and Automated Alerts. International Journal of Enhanced Research in Science, Technology & Engineering, 12(11), 111–117. https://doi.org/10.55948/ijerste.2023.1115