International Journal of Engineering Research and Science & Technology

AN EFFICIENT CYBERBULLYING DETECTION MODEL USING TWEET CONTEXT AND NETWORK STRUCTURE

1. **P.Sashi Rekha, Asst.prof CSE dept,Gokula Krishna College Of Engineering, M.Tech(CSE),Sullurpeta,Tirupati District,AP**
2. **G.Naga Mokshayani, T.Bhanu, G.Chenchu Harika, M.Morarji Desai, B.Srinivasulu,CSE dept,Gokula Krishna College Of Engineering,Sullurpeta, Tirupati District,AP**

ABSTRACT

The rapid expansion of social media platforms has intensified the prevalence and complexity of cyberbullying, necessitating more intelligent and context-aware detection mechanisms. While existing approaches primarily focus on textual features or limited multi-modal inputs, they often fail to capture the conversational dynamics and behavioral patterns underlying abusive interactions. To address these limitations, this study proposes an enhanced cyberbullying detection framework that integrates multi-modal learning with conversation-driven analysis. Building upon deep learning architectures such as BiLSTM and hierarchical attention networks for feature extraction, the proposed system introduces a novel three-phase mechanism that incorporates conversation graph modeling, bullying score estimation, and a centrality-based user identification strategy. Unlike traditional methods that classify isolated posts, the model evaluates interactions within conversational threads, enabling more accurate detection of implicit and evolving bullying behavior. Additionally, the inclusion of contextual relationships and user-level influence measures improves the identification of persistent offenders. Experimental insights indicate that combining textual, comment-level, and contextual graph features significantly enhances detection performance and scalability. The proposed framework not only improves classification accuracy but also provides a comprehensive understanding of cyberbullying patterns in social networks, making it suitable for real-time monitoring and intervention systems.

Keywords- Cyberbullying Detection, Multi-Modal Learning, Social Media Analysis, Hierarchical Attention Networks, BiLSTM, Conversation Graph Modeling, Sentiment Analysis, User Behavior Analysis, Deep Learning, Network Centrality Measures, Context-Aware Computing, Text Mining, Machine Learning, Online Harassment Detection, Social Network Security

I. INTRODUCTION

The exponential growth of social networking platforms has significantly transformed the way individuals communicate, interact, and share information in the digital era. However, this widespread adoption has also led to the emergence of harmful online behaviors, among which cyberbullying has become a critical concern. Cyberbullying refers to the repeated use of digital technologies to harass, threaten, or intimidate individuals or groups, often resulting in severe psychological and emotional consequences. Recent studies indicate that a substantial percentage of adolescents and young users have experienced cyberbullying incidents on platforms such as Twitter, Instagram, and Facebook [1], [2]. The persistent and pervasive nature of online content further exacerbates its impact, making cyberbullying a significant public health and societal issue [3].

Traditional approaches to cyberbullying detection have primarily relied on textual content analysis, where machine learning techniques such as Support Vector Machines (SVM), Naïve Bayes, and Logistic Regression are employed to classify harmful content based on linguistic features [7]–[12]. These approaches often utilize feature extraction techniques such as Term Frequency–Inverse Document Frequency (TF-IDF), Bag-of-Words (BoW), and lexical analysis to identify abusive patterns [13]. While these methods have demonstrated reasonable performance, they suffer from several limitations, particularly in handling contextual ambiguity, sarcasm, and evolving language patterns commonly observed in social media communications.

To overcome these challenges, deep learning techniques have been increasingly adopted due to their ability to learn complex representations from large-scale data. Models such as Convolutional Neural Networks (CNN), Recurrent Neural Networks (RNN), and hybrid architectures have shown improved performance in capturing semantic and syntactic information from textual data [6]–[19]. Additionally, attention mechanisms have been introduced to enhance model interpretability by focusing on relevant features within text sequences, thereby improving detection accuracy [2], [20]. Despite these advancements, most existing models still rely heavily on single-modal data, which limits their ability to fully understand the multi-faceted nature of cyberbullying.

In real-world scenarios, cyberbullying is not confined to textual content alone but often involves multiple modalities, including images, videos, user interactions, and temporal information. Recent research has highlighted the importance of integrating multi-modal data to capture richer contextual information and improve detection performance [4], [5], [11]. Multi-modal frameworks combine textual, visual, and metadata

features to provide a more comprehensive understanding of online behavior. For instance, hierarchical attention networks (HAN) have been utilized to model comment-level interactions, while embedding techniques are employed to encode visual and contextual features [6], [7].

Building upon these developments, this work proposes an enhanced cyberbullying detection mechanism that integrates multi-modal learning with conversation-based contextual analysis. Unlike traditional systems that analyze isolated posts, the proposed approach considers the conversational structure of interactions, enabling the identification of implicit and evolving bullying patterns. By incorporating graph-based modeling, sentiment analysis, and centrality measures, the system captures both content-level and user-level behavioral characteristics. This holistic approach not only improves detection accuracy but also enables the identification of influential users involved in cyberbullying activities.

Furthermore, the proposed framework addresses key limitations of existing systems by integrating contextual relationships and leveraging deep learning architectures for feature extraction. The combination of textual, visual, and conversational features enhances the robustness and scalability of the model, making it suitable for real-time applications in social media monitoring. Overall, this research contributes to the development of intelligent and adaptive cyberbullying detection systems that can effectively mitigate harmful online interactions and promote safer digital environments.

II. LITERATURE SURVEY

Cyberbullying detection has been an active area of research, with numerous studies exploring different computational approaches to identify abusive behavior in online platforms. Early research primarily focused on traditional machine learning techniques that rely on textual feature extraction and classification. Methods such as TF-IDF, Bag-of-Words, and lexical analysis have been widely used to represent textual data, followed by classifiers like Support Vector Machines (SVM), Naïve Bayes, and Logistic Regression [7]–[12]. These approaches demonstrated effectiveness in detecting explicit abusive language but often failed to capture contextual nuances and implicit forms of cyberbullying.

Chavan and Shylaja [13] proposed a machine learning-based approach that utilizes lexical features and classification techniques to identify aggressive comments on social media. Similarly, Burnap and Williams [7], [10] explored statistical modeling and machine classification to detect cyber hate speech on Twitter. While these methods provided valuable insights, their reliance on handcrafted features limited their adaptability to dynamic social media environments.

To address these limitations, researchers began incorporating network-based features and user behavior analysis into cyberbullying detection models. Chelmis et al. [15] investigated patterns of cyberbullying by analyzing social network structures, while Algaradi et al. [14] combined user behavior, network metrics, and textual features to improve detection accuracy. Cheng et al. [11] further extended this approach by constructing heterogeneous networks that integrate user profiles, content, and interaction data, demonstrating the importance of contextual and relational information in identifying cyberbullying.

The advent of deep learning techniques marked a significant advancement in this domain. Convolutional Neural Networks (CNN) have been employed to capture local semantic features in text, while Recurrent Neural Networks (RNN) and Long Short-Term Memory (LSTM) models are used to model sequential dependencies [16]–[19]. Hybrid architectures, such as RCNN, combine the strengths of CNN and RNN to improve classification performance [19]. Park and Fung [20] introduced a hybrid model that integrates character-level and word-level representations to handle noisy and misspelled text commonly found in social media.

Attention mechanisms have further enhanced deep learning models by enabling them to focus on relevant parts of the input data. Zhou et al. [20] proposed an attention-based BiLSTM model for relation classification, which was later adapted for cyberbullying detection by Zhang et al. [3]. These models demonstrated improved performance by assigning higher importance to critical words and phrases associated with abusive behavior.

More recently, multi-modal approaches have gained attention as they consider multiple sources of information beyond text. Soni and Singh [5] proposed an audio-visual-textual framework for cyberbullying detection, highlighting the significance of integrating visual and auditory cues. Li et al. [4] explored the parent-child relationship between comments to capture contextual dependencies, while Cheng et al. [7] utilized hierarchical attention networks to model comment-level interactions. These studies emphasize the importance of incorporating contextual and multi-modal data to improve detection accuracy.

Despite these advancements, existing approaches still face challenges in effectively integrating multiple modalities and capturing the dynamic nature of cyberbullying. Many models either focus on limited modalities or fail to consider the conversational context of interactions. Additionally, identifying influential users involved in cyberbullying remains an underexplored area.

To overcome these challenges, the proposed work builds upon multi-modal learning and introduces a conversation-based graph modeling approach. By integrating textual, visual, and contextual features with centrality-based user analysis, the proposed system aims to provide a more comprehensive and accurate cyberbullying detection framework. This approach addresses the limitations of previous studies and contributes to the development of

more robust and scalable solutions for real-world applications.

III. PROPOSED METHODOLOGY

A. Overview of the Proposed Framework

The proposed cyberbullying detection system introduces a hybrid multi-modal and conversation-aware architecture designed to overcome the limitations of traditional text-only models. The framework integrates content-level learning (text, comments, media, metadata) with context-level analysis (conversation graph and user behavior modeling) to improve detection accuracy and interpretability.

The overall system operates in three major phases:

- Multi-Modal Feature Encoding
- Conversation Graph Modeling and Bullying Score Computation
- Centrality-Based Bully Identification and Classification

Unlike existing approaches that classify isolated posts, the proposed model analyzes interactions among users within conversations, enabling detection of implicit, repeated, and context-driven cyberbullying.




Figure.1: System Architecture Diagram

The architecture illustrates how multi-modal features (text, comments, media, metadata) are extracted using deep learning models like BiLSTM and HAN, and then integrated for analysis. It further shows the incorporation of conversation graph modeling and centrality-based classification to accurately identify cyberbullying and detect influential bully users.

B. Multi-Modal Feature Representation

Each social media post is represented as a composite structure:

$$P_i = \{T_i, C_i, M_i, O_i\}$$

Where:

T_i: Textual content
C_i: Set of comments
M_i: Media information (images/videos)
O_i: Metadata (timestamps, user profile, likes, etc.)

The objective is to learn a function:

$$F(P_i) \rightarrow Y_i$$

Where:

$Y_i \in \{0,1\}$, indicating non-bullying (0) or bullying (1)




Figure.2: Data Flow Diagram (DFD)

The data flow diagram represents the step-by-step transformation of input social media data into meaningful features and structured conversation graphs. It highlights how processed data flows through feature extraction, graph construction, and decision modules to produce final cyberbullying detection outcomes.

C. Text Encoding using BiLSTM with Attention

To capture contextual dependencies in textual data, a Bidirectional Long Short-Term Memory (BiLSTM) network is employed.

The hidden states are computed as:

$$\overrightarrow{h_t} = \text{LSTM}(x_t), \quad \overleftarrow{h_t} = \text{LSTM}(x_t)$$

The combined representation:

$$h_t = [\overrightarrow{h_t}; \overleftarrow{h_t}]$$

Attention Mechanism

To focus on important words:

$$u_t = \tanh(W_w h_t + b_w)$$

$$\alpha_t = \frac{\exp(u_t^T u_w)}{\sum_k \exp(u_k^T u_w)}$$

Final text representation:

$$v_t = \sum_t \alpha_t h_t$$

Analysis:
This mechanism assigns higher weights to abusive or offensive words, improving detection of subtle bullying expressions.

D. Comment Modeling using Hierarchical Attention Network (HAN)
Comments are treated as a structured sequence of interactions. Each comment
c_i consists of words
***wit* Word-level encoding:**
h_{it} = **BiGRU(**x_{it}**)**
Word attention:

$$u_{it} = \tanh(W_w h_{it} + b_w)$$

$$\alpha_{it} = \frac{\exp(u_{it}^T u_w)}{\sum_t \exp(u_{it}^T u_w)}$$

Comment representation:

$$s_i = \sum_t \alpha_{it} h_{it}$$

Comment-level attention:

$$u_i = \tanh(W_c s_i + b_c)$$

$$\beta_i = \frac{\exp(u_i^T u_c)}{\sum_i \exp(u_i^T u_c)}$$

Final comment vector:

$$v_c = \sum_i \beta_i s_i$$

Analysis:
HAN captures hierarchical structure (word → comment → conversation), enabling detection of contextual bullying patterns across replies.

E. Media and Metadata Encoding
Media and metadata are encoded using feature embedding and dense layers:

$$v_m = \sigma(W_m M_i + b_m)$$
$$v_o = \sigma(W_o O_i + b_o)$$

Analysis:
This step incorporates visual cues and contextual attributes, which are often ignored in traditional systems.




Figure.3: Activity Diagram

The activity diagram describes the sequential workflow of the system, starting from data collection to final classification and report generation. It emphasizes decision-making steps such as bullying score computation and conditional identification of bully users based on learned patterns.

F. Conversation Graph Modeling
A key novelty of the proposed system is the introduction of a conversation graph:
$G = (U, E)$
Where:
U: Set of users
E: Interactions between users
Each edge weight represents interaction strength:
$w_{ij} = f(S_{ij}, L_{ij})$
Where:
S_{ij}: Sentiment score
L_{ij}: Frequency of abusive terms
Bullying Score:
$B_{ij} = \lambda_1 S_{ij} + \lambda_2 L_{ij}$
Analysis:
This allows the model to:

- Capture repeated aggression
- Detect conversation-level bullying
- Identify patterns over time

G. Centrality-Based User Identification (A&M Measure)
To identify influential bullies, a centrality score is computed:

$$C(u_i) = \sum_j w_{ij}$$

Enhanced centrality (Attitude & Merit):

$$AM(u_i) = \gamma_1 C(u_i) + \gamma_2 B(u_i)$$

Analysis:
Identifies dominant bully users
Differentiates between victims and aggressors

Improves user-level classification

H. Multi-Modal Fusion and Classification

All modality vectors are combined:

$v = [v_t; v_c; v_m; v_o]$

Final prediction:

$$\hat{Y} = \sigma(W_f v + b_f)$$

Loss function:

$$\mathcal{L} = -\sum [y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})]$$

The proposed system integrates deep learning, graph theory, and behavioral analysis into a unified framework. By combining multi-modal feature extraction with conversation-level understanding, the model provides a more accurate, context-aware, and scalable solution for cyberbullying detection compared to traditional approaches.

IV. EXPERIMENTAL RESULTS AND ANALYSIS

A. Experimental Setup

The proposed cyberbullying detection framework was evaluated using multi-modal datasets collected from social media platforms such as Twitter, Instagram, and Vine, as described in the base study. The dataset contains a mixture of textual posts, comments, media tags, and user interaction data, enabling comprehensive evaluation of the proposed system. The dataset was divided into training and testing sets using an 80:20 ratio, ensuring unbiased model validation. Word embeddings were initialized using pre-trained vector representations, and deep learning models were trained using optimized hyperparameters.

B. Evaluation Metrics

To evaluate model performance, standard classification metrics were used:

1. Accuracy

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

2. Precision

$$Precision = \frac{TP}{TP + FP}$$

3. Recall

$$Recall = \frac{TP}{TP + FN}$$

4. F1-Score

$$F1 = \frac{2 . Precision \times Recall}{Precision + Recall}$$

Where:

TP = True Positives

TN = True Negatives

FP = False Positives

FN = False Negatives

Analysis:

F1-score is emphasized due to class imbalance in cyberbullying datasets, ensuring balanced evaluation.

C. Performance Comparison with Baseline Models

Table 1: Performance Comparison of Models

Model	Accuracy (%)	Precision (%)	Recall (%)	F1-Score (%)
Naïve Bayes	71.2	69.5	68.3	68.9
SVM	75.6	73.8	72.4	73.1
Logistic Regression	77.4	75.9	74.8	75.3
Random Forest	80.2	79.1	78.5	78.8
LSTM	84.3	82.7	81.5	82.1
HAN	86.1	84.9	83.6	84.2
Proposed Model	**92.1**	**90.8**	**89.6**	**90.2**

Analysis

The proposed model significantly outperforms traditional machine learning and deep learning models. The improvement is primarily due to:

- Multi-modal feature integration
- Attention-based learning
- Conversation graph modeling

The increase in F1-score demonstrates better handling of imbalanced data and improved detection of subtle bullying patterns.




Figure.4: Bar Graph of Performance Comparison of Models

The bar graph compares different machine learning and deep learning models, showing that the proposed model achieves the highest accuracy, precision, recall, and F1-score. This demonstrates the effectiveness of combining multi-modal features, attention mechanisms, and graph-based analysis over traditional approaches.

D. Impact of Multi-Modal Features.

Table 2: Contribution of Different Modalities

Modality Used	Accuracy (%)	F1-Score (%)
Text Only	81.5	79.8
Text + Comments	85.7	83.9
Text + Media	84.2	82.5

Modality Used	Accuracy (%)	F1-Score (%)
Text + Comments + Metadata	88.6	87.1
All Modalities (Proposed)	**92.1**	**90.2**

Analysis

The results indicate that:

- Text alone is insufficient for accurate detection
- Comments significantly enhance contextual understanding
- Full multi-modal fusion yields the best performance

This confirms that cyberbullying is a context-driven phenomenon, not just a textual problem.




Figure.5: Pie Chart of Feature Contributions

The pie chart illustrates the contribution of different feature combinations, where multi-modal integration (text, comments, metadata) provides the largest impact on performance. It highlights that relying on text alone is insufficient, while combining multiple modalities significantly enhances cyberbullying detection.

E. Effect of Conversation Graph and Centrality Measure

Table 3: Impact of Graph-Based Enhancement

Method	Accuracy (%)	F1-Score (%)
Without Graph	86.4	84.7
With Conversation Graph	89.8	88.5
With Graph + Centrality (Proposed)	**92.1**	**90.2**

Analysis

The introduction of conversation graph modeling improves detection by capturing:

- Repeated interactions
- User relationships
- Temporal patterns

The centrality-based A&M measure further enhances performance by identifying influential bully users rather than only classifying posts.




Figure.6: Line Graph of Impact of Graph-Based Methods

The line graph shows a steady improvement in accuracy and F1-score when moving from no graph to graph-based and centrality-enhanced methods. This indicates that incorporating conversation graphs and user centrality measures improves detection by capturing interaction patterns and user behavior.

F. Confusion Matrix Analysis

The confusion matrix is used to analyze classification errors:

$$Error\ Rate = \frac{FP + FN}{Total}$$

The proposed model reduces:

- False Positives (misclassifying normal content)
- False Negatives (missing bullying cases)

This indicates improved reliability in real-world applications.

The proposed cyberbullying detection framework achieves superior performance across all evaluation metrics. By integrating multi-modal data, conversation context, and user behavior analysis, the system provides a robust, scalable, and highly accurate solution for detecting cyberbullying in social networks. The results validate the effectiveness of combining deep learning with graph-based techniques for real-world applications.

V. CONCLUSION

The proposed cyberbullying detection framework presents a comprehensive and intelligent solution by integrating multi-modal learning with conversation-aware analysis and graph-based user modeling. Unlike conventional approaches that rely solely on textual features, this system effectively combines textual content, comments, media information, and metadata to capture the complex and dynamic nature of cyberbullying behavior. The incorporation of BiLSTM and hierarchical attention networks enables the model to identify contextually significant patterns, while the introduction of conversation graph modeling enhances the understanding of user interactions and repeated abusive behavior. Furthermore, the centrality-based Attitude and Merit (A&M) measure plays a crucial role in identifying influential bully users, thereby extending detection beyond content-level classification to user-level analysis.

Experimental results demonstrate that the proposed approach significantly outperforms traditional machine learning and existing deep learning models in terms of accuracy, precision, recall, and F1-score. The integration of multi-modal features and graph-based techniques not only improves detection performance but also enhances the robustness and scalability of the system for real-world applications. Overall, the framework provides a reliable and efficient mechanism for identifying cyberbullying in social networks, contributing to safer online environments and improved digital well-being. The model can be further enhanced by incorporating real-time streaming data processing and explainable AI techniques to improve transparency, adaptability, and early cyberbullying intervention.

VI. REFERENCES

[1] S. Salawu, Y. He, and J. Lumsden, "Approaches to automated detection of cyberbullying: A survey," IEEE Trans. Affect. Comput., 2020.
[2] H. Dani, J. Li, and H. Liu, "Sentiment informed cyberbullying detection in social media," Springer, 2017.
[3] A. Mangaonkar et al., "Collaborative detection of cyberbullying behavior in Twitter data," IEEE, 2015.
[4] Z. Li et al., "Cyberbullying detection using parent-child relationship between comments," ACM, 2016.
[5] D. Soni and V. K. Singh, "Audio-visual-textual cyberbullying detection," ACM, 2018.
[6] Z. Yang et al., "Hierarchical attention networks for document classification," NAACL, 2016.
[7] P. Burnap and M. L. Williams, "Cyber hate speech on Twitter," 2015.
[8] M. Dadvar et al., "Hybrid approach to detect cyberbullies," 2014.
[9] R. Zhao et al., "Automatic detection of cyberbullying," 2016.
[10] P. Burnap and M. L. Williams, "Identifying cyber hate," 2016.
[11] L. Cheng et al., "XBully: Cyberbullying detection," ACM, 2019.
[12] Y. Li and J. Ye, "Adversarial networks for text classification," 2018.
[13] V. S. Chavan and S. Shylaja, "ML approach for cyber aggression detection," 2015.
[14] M. A. Al-Garadi et al., "Cybercrime detection in online communications," 2016.
[15] C. Chelmis et al., "Mining patterns of cyberbullying," IEEE, 2017.
[16] L. Xu et al., "Deep learning for text representation," 2024.
[17] B. Gambäck and U. K. Sikdar, "CNN for hate speech detection," 2017.
[18] H. Hosseinmardi et al., "Cyberbullying analysis on Instagram," 2014.
[19] R. Zhang et al., "Dependency-sensitive CNN," 2016.
[20] J. H. Park and P. Fung, "Abusive language detection," 2017.