International Journal of Engineering Research and Science & Technology

ISSN 2319-5991 www.ijerst.com
Vol. 22, No. 2, 2026
© 2026 IJERST. All Rights Reserved
Peer Reviewed, Referred & Indexed Journal

FABRICATION OF MULTI-TERRAIN SPY ROVER WITH PYTHON-BASED CONTROL SYSTEM

A. NARAYANA SWAMY, S. SUBHAHAN VALI, K. ANIL, G. BHARADWAJ.
Dr . L. BALASUBRAMANMYAM M.Tech.,Ph.D
1.Student, Dept. of Mechanical Engineering, P.V.K.K Institute of Technology, Road, Alamuru Anantapur, Andhra Pradesh
2. Professor, Dept. of Mechanical Engineering, P.V.K.K Institute of Technology, Road, Alamuru Anantapur, Andhra Pradesh

ABSTRACT

This project presents the design and fabrication of a **Multi-Terrain Spy Rover with a Python-Based Control System**, integrating mechanical engineering, electronics, and embedded programming. The rover is compactly designed with dimensions of **1.2 × 1.2 × 1.2 ft** and features a lightweight yet durable body fabricated using **POP moulds reinforced with high-density thermosetting plastics**. Mechanical engineering principles were applied in structural design, load distribution, material selection, and the development of a **stainless-steel suspension system**, enabling the rover to traverse uneven and rugged terrains efficiently. The system is powered by a **Raspberry Pi Zero 2 W** microcontroller, which acts as the central processing unit for motor control, sensor communication, and wireless operation using **Python-based programming**. A **5 MP surveillance camera** provides real-time video streaming, while additional modules such as a thermal camera, fire and smoke detection sensors, and an integrated microphone enhance environmental monitoring capabilities. The rover also includes **miniature robotic arms** for remote interaction and sample collection in hazardous environments. The project demonstrates the integration of mechanical fabrication, electronic system design, and software control. The resulting rover is capable of **multi-terrain mobility, remote surveillance, hazard detection, heat mapping, and robotic manipulation**, making it suitable for applications in **defense surveillance, disaster management, and environmental monitoring**.

Keywords

Multi-Terrain Rover, Surveillance Robotics, Python Programming, Embedded Systems, Raspberry Pi, Wireless Control, Thermal Imaging, Fire Detection, Mechatronics, Remote Monitoring.

1.INTRODUCTION

In recent years, the rapid advancement of robotics and automation has significantly transformed various fields such as defence, surveillance, disaster management, and industrial operations. The demand for intelligent systems capable of operating in complex and hazardous environments has led to the development of multi- terrain robotic platforms. These systems are designed to navigate diverse landscapes while performing critical tasks remotely, reducing human risk and increasing operational efficiency. In this context, the present project focuses on the design and fabrication of a "Multi-Terrain Spy Rover with a Python-Based Control System," integrating mechanical engineering principles with modern electronics and embedded programming.

1.1 Problem Statement

In many real-world scenarios such as disaster management, military surveillance, industrial inspection, and hazardous environment monitoring, human involvement is often associated with high levels of risk, inefficiency, and limited accessibility. Conventional methods of surveillance and data collection rely heavily on manual intervention, which not only exposes individuals to dangerous conditions but also restricts the ability to gather accurate and real-time information from

complex terrains. Environments such as rocky landscapes, fire-affected zones, confined spaces, and structurally unstable areas present significant challenges for human operation as well as for traditional robotic systems.

Existing robotic solutions often face limitations in terms of mobility, adaptability, and integration of multiple functionalities. Many robots are designed for specific environments and fail to perform efficiently across varied terrains. Additionally, the lack of seamless integration between mechanical components, electronic systems, and software control leads to reduced performance and reliability. Issues such as poor navigation on uneven surfaces, limited remote control capabilities, insufficient sensor integration, and lack of real-time monitoring further restrict their practical applications.

Another critical challenge is the absence of cost-effective and compact systems that can perform multiple operations simultaneously, such as surveillance, environmental monitoring, hazard detection, and remote interaction. Most advanced robotic systems are expensive and complex, making them less accessible for academic, research, and small- scale applications. Furthermore, the need for user-friendly control systems and efficient communication between hardware and software remains a key concern in modern robotic development.

1.2 Objectives

1 To design and develop a compact multi-terrain spy rover capable of navigating uneven and rugged surfaces efficiently.

2 To implement a Python-based control system for effective operation and real-time control of the rover.

3 To integrate Raspberry Pi and Raspberry Pi Pico W for central control, communication, and wireless navigation.

1.3 Scope of The Project

The scope of the "Multi-Terrain Spy Rover with a Python-Based Control System" focuses on the design, fabrication, and implementation of a compact and efficient robotic platform capable of operating across different types of terrains. The project primarily aims to demonstrate the integration of mechanical design, embedded systems, and software control in developing a functional surveillance rover.

The project covers the development of a robust mechanical structure that allows the rover to move smoothly on uneven, rough, and inclined surfaces. It includes the design of the chassis, wheel arrangement, and suspension system to ensure stability and durability under varying environmental conditions. The fabrication process emphasizes lightweight construction while maintaining sufficient strength for reliable operation.

1.4 Applications

The "Multi-Terrain Spy Rover with a Python-Based Control System" has a wide range of practical applications in various fields where human access is difficult, risky, or limited.

The system is designed to perform surveillance, monitoring, and basic operational tasks in challenging environments.

4 Military and defence Surveillance: The rover can be used for border monitoring, reconnaissance missions, and spying in sensitive areas without risking human lives.

5 Disaster Management: It can be deployed in disaster-affected areas such as earthquake zones, collapsed buildings, and flood regions to search for survivors and assess damage.

6 Fire and Hazard Detection: The rover can be used in fire-prone or hazardous environments to detect smoke, temperature variations, and fire presence.

7 Industrial Inspection: It can inspect industrial sites, pipelines, and restricted zones where human entry is unsafe or not feasible.

8 Security and Monitoring: The system can be used for surveillance in public places, offices, and high-security areas for continuous monitoring.

9 Search and Rescue Operations: The rover can assist rescue teams by entering confined or dangerous spaces and providing real-time information.

10 Environmental Monitoring: It can be used to monitor environmental conditions such as temperature, gas levels, and pollution in remote areas.

2. LITERATURE SURVEY

2.1 Literature Survey

The rapid advancement in robotics, Internet of Things (IoT), and embedded systems has significantly contributed to the development of intelligent surveillance and security systems. In recent years, unmanned ground vehicles (UGVs) and robotic platforms have gained importance in military, industrial, and disaster management applications. These systems are designed to operate in hazardous and inaccessible environments where human intervention is risky. The integration of technologies such as Raspberry Pi, wireless communication, computer vision, and sensor networks has enabled the development of multifunctional surveillance robots capable of real-time monitoring and threat detection.

Modern surveillance robots are equipped with features such as live video streaming, audio recording, motion detection, and environmental sensing. Researchers have also incorporated advanced techniques like face recognition, object detection, and machine learning to enhance system intelligence and accuracy. However, despite these advancements, many systems still face challenges such as limited functionality, high cost, and lack of integration.

This chapter reviews various research works related to IoT-based surveillance robots, spy rovers, and intelligent monitoring systems to understand existing technologies and identify research gaps.

2.2 Review Of Existing Systems

Several research works have been carried out in the field of surveillance robotics and IoT-based monitoring systems.

Mandar Kulkarni et al. proposed an IoT-based multifunctional robot using Raspberry Pi capable of performing multiple tasks such as face detection, voice recognition, and live video streaming. The system supports both Bluetooth-based and web-based control, allowing users to operate the robot remotely.

The integration of WebIOPi enables internet-based control, making it a flexible IoT-enabled system. However, the system is mainly designed for home automation and lacks advanced threat detection capabilities.

2.3 Research Gap

From the above literature review, it is observed that significant progress has been made in the development of surveillance robots and IoT-based monitoring systems. However, several limitations still exist in current systems:

- Many systems focus on **single functionality** such as video streaming, face detection, or environmental monitoring, rather than integrating multiple features.
- Early systems using **RF or Bluetooth communication** suffer from limited range and reliability.
- Lack of **real-time multi-sensor integration**,

combining video, audio, human detection, and metal detection in a single system.

3.METHODOLOGY



3.1 Planning Phase

The planning phase involves defining the objectives and selecting suitable components for the project. The main aim is to develop a spy rover capable of surveillance, environmental monitoring, and location tracking.

Planning steps:

- Identification of project objective (multi-terrain spy rover)
- Selection of Raspberry Pi Zero 2 W as controller
- Selection of MQ-2 gas sensor for gas detection
- Selection of temperature sensor for environmental monitoring
- Selection of GPS tracker for location tracking
- Selection of motors and motor driver
- Designing system architecture
- Considering cost and component availability

3.2 Robot Type and Design

The proposed system is a mobile multi-terrain robotic rover designed to operate in different environmental conditions.

The rover is capable of performing surveillance and monitoring tasks efficiently.

Design features:

- Tank chassis structure for stability
- DC motor-based locomotion system
- Robotic arm for object handling
- Camera with pan-tilt mechanism
- Integration of gas, temperature, and GPS sensors
- Compact and lightweight design

3.3 Material Collection

All required components were collected based on the system design and requirements. Proper selection ensured compatibility and efficient system performance.

Materials used:

- Raspberry Pi Zero 2 W
- DC motors and L298N motor driver
- MQ-2 gas sensor
- Temperature sensor
- GPS tracker module
- Pi camera module
- Robotic arm components
- Power supply (battery and buck converter)
- Connecting wires and accessories

3.4 Fabrication of Multi-Terrain Spy Rover

This phase involves assembling all hardware components to build the rover system.

Fabrication steps:

- Preparing the tank chassis and mounting motors
- Fixing Raspberry Pi at the center
- Connecting motor driver with DC motors
- Installing MQ-2 gas sensor on the rover
- Mounting temperature sensor for environment

monitoring

- Connecting GPS module for location tracking
- Installing camera with pan-tilt mechanism
- Fixing robotic arm on the chassis
- Completing wiring and ensuring proper connections

3.5 Programming and Testing

The system is programmed using Python and tested for proper functioning of all modules.

Programming steps:

- Installing required libraries (OpenCV, GPIO, GPS libraries)
- Writing code for motor control
- Programming sensor data reading (gas, temperature, GPS)
- Implementing live video streaming

Testing steps:

- Testing MQ-2 gas sensor response
- Verifying temperature readings
- Checking GPS location accuracy
- Testing motor movement and control
- Testing complete system integration

3.6 orking and Implementation

The working of the system is based on real-time monitoring and remote control.

Working process:

- System initializes all components after power ON
- Camera starts live video streaming
- User sends commands through Wi-Fi interface
- Rover moves according to user input
- MQ-2 sensor detects gas presence
- Temperature sensor monitors environment
- GPS tracker provides real-time location
- Alerts are generated when abnormal conditions are detected
- Robotic arm performs object handling

3.7 System Response and Performance

The system performance is evaluated based on its response time and accuracy.

Performance factors:

- Fast response of MQ-2 gas sensor
- Accurate temperature monitoring
- Reliable GPS location tracking
- Smooth video streaming
- Efficient rover movement control
- Stable wireless communication

3.8 Summary

In this chapter, the overall methodology of the spy rover system is presented. The planning, design, and selection of components such as Raspberry Pi, MQ-2 gas sensor, temperature sensor, and GPS tracker are explained. The fabrication process includes assembling all hardware components onto the chassis. Programming and testing are carried out to ensure proper working of sensors, motors, and camera.

The system works by monitoring the environment, providing live video, and tracking location in real time. Finally, the performance of the system is evaluated based on its accuracy and response.

4.MATERIAL COLLECTION

4.1 Core Control Unit Raspberry Pi Zero 2 W




Fig 4.1 Raspberry Pi Zero 2 W

The **Raspberry Pi Zero 2 W** serves as the **main control unit (brain)** of the spy rover system. It is a compact, low-cost single-board computer that is responsible for controlling and coordinating all hardware and software operations of the rover. The primary purpose of this component is to process input data from various sensors, execute programmed instructions, and control output devices such as motors, camera, and robotic arm.

In this project, the Raspberry Pi Zero 2 W handles multiple tasks simultaneously. It receives data from sensors like the gas sensor, ultrasonic sensor, and metal detector, and processes this data using Python programs. Based on the sensor inputs, it makes decisions such as obstacle avoidance, alert generation, or object detection. It also controls the movement of the rover by sending signals to the motor driver, enabling forward, backward, and directional movements.

Another important function of the Raspberry Pi is **real-time video processing and streaming**. The camera module is connected directly to the Raspberry Pi, which captures live video and transmits it wirelessly to the user through Wi-Fi. Additionally, it supports advanced features like human detection using computer vision (OpenCV).

The built-in Wi-Fi capability of the Raspberry Pi Zero 2 W enables **remote control and communication**, allowing the user to operate the rover from a mobile or web interface. Overall, this component acts as the central processing and decision-making unit, ensuring smooth and efficient operation of the entire spy rover system.

4.2 Locomotion System – (Diy Tank Chassis, Dc Motors, L298n Driver)




Fig 4.2 Locomotion System

The locomotion system is responsible for the **movement of the spy rover** across different terrains. The **DIY tank chassis** provides a strong and stable base structure for mounting all components. The **two DC motors** are used to drive the wheels or tracks, enabling forward and backward motion.

These motors convert electrical energy into mechanical motion for rover movement. The **L298N motor driver** acts as an interface between the Raspberry Pi and DC motors. It controls the **direction and speed** of the motors based on input signals. The motor driver allows movements like **forward, backward, left, and right turns**. This system enables the rover to navigate through **rough and uneven terrains**. It ensures smooth and controlled motion during surveillance operations. Overall, the locomotion system provides **mobility and flexibility** to the entire robot.

4.3 Robotic Arm System – (6-Dof Arm, Servos, Pca9685 Driver)




Fig 4.3 Robotic Arm

- The robotic arm system is used for **advanced object handling and manipulation** in the spy rover.
- The **6-DOF (Degrees of Freedom) acrylic arm** provides greater flexibility with multiple directional movements.
- It allows actions like **lifting, rotating, extending, and precise positioning** of objects.
- The **MG996R high torque servos** control the major joints of the arm, providing strong and stable movement.
- These servos enable the arm to handle **heavier loads with accuracy**.
- The **SG90 micro servos** are used in the gripper for opening and closing operations.
- The gripper helps in **picking, holding, and releasing objects remotely**.
- The **PCA9685 servo driver** controls multiple servos using PWM signals efficiently.
- It reduces processing load on the Raspberry Pi and ensures smooth coordination.

Overall, this system improves the rover's ability to perform **complex and precise tasks in real-time environments**.

4.4 Vision and Audio System – (Pi Camera, Pan-Tilt, Usb Microphone)



Fig 4.4 Camera and Microphone

The **Vision and Audio System** plays a crucial role in enabling real-time surveillance and environmental awareness for the spy rover. The **Pi Camera Module V2** is used to capture high-quality images and live video streams. It is directly connected to the Raspberry Pi, allowing efficient data processing and transmission. This camera provides continuous visual monitoring of the surroundings, which is essential for security, reconnaissance, and remote observation tasks.

It also supports image processing applications such as motion detection and human detection using computer vision techniques.

The **pan-tilt mechanism** enhances the functionality of the camera by allowing it to rotate both horizontally and vertically. This enables a wider field of view without physically moving the entire rover. The camera can be adjusted remotely, making it easier to monitor different angles and directions in real time. This feature is particularly useful in surveillance applications where full-area coverage is required.

The **USB microphone** is used to capture audio signals from the environment. It allows the system to detect sounds such as human voices, movements, or unusual noises. The audio data can be recorded or transmitted along with the video feed, providing a more comprehensive understanding of the surroundings.

Overall, the vision and audio system enables the rover to perform effective **real- time monitoring, situational awareness, and remote surveillance**, making it a vital component.

4.5 Sensor System – (Mq-2, Temperature Sensor, Gps Tracker)




Fig 4. Sensors (MQ-2, Temperature, GPS Tracker)

The sensor system is an essential part of the spy rover, as it provides real-time environmental monitoring and enhances the overall safety and intelligence of the system.

In addition to this, the **temperature sensor** is used to measure the surrounding temperature and detect abnormal increases, which may indicate unsafe or hazardous environments. The **GPS tracker module** is responsible for determining the real-time location of the rover by providing accurate latitude and longitude coordinates, allowing users to track the rover remotely. This is particularly useful in military, surveillance, and rescue operations where location tracking is important. Overall, the sensor system enables the rover to perform effective hazard detection, environmental monitoring, and real-time location tracking, making it a crucial component of the entire system.

4.6 Power Supply Unit – (12v Adapter / Li-Ion Battery, Lm2596 Buck Converter)






Fig 4.6 12V Adapter / Li-ion Battery, LM2596 Buck Converter

The **Power Supply Unit** is responsible for providing stable and reliable electrical power to all components of the spy rover system. It ensures that each module operates efficiently without voltage fluctuations or power interruptions. The system uses a **12V power adapter or Li-ion battery pack** as the primary power source. This high-voltage supply is mainly used to drive components like DC motors, which require more power for movement and operation.

However, different components in the system require different voltage levels. The Raspberry Pi and sensors typically operate at **5V**, while motors may require **12V**. To manage this, the **LM2596 buck converter** is used. This device steps down the voltage from 12V to a regulated 5V output, ensuring safe operation of sensitive components like the Raspberry Pi.

The buck converter also helps in improving power efficiency and prevents overheating or damage due to excess voltage. It provides a constant and adjustable output voltage, which is essential for stable system performance. Additionally, when a battery is used, it allows the rover to operate in remote locations without the need for a direct power connection. Overall, the power supply unit plays a critical role in maintaining **stable**

voltage distribution, energy efficiency, and uninterrupted operation of the entire spy rover system.

4.7 Summary

In this chapter, the complete setup of the spy rover is presented. All the components like Raspberry Pi, motors, sensors, camera, and robotic arm are assembled on the chassis. The connections between hardware components are made and configured properly. The working of sensors like MQ-2, temperature sensor, and GPS tracker is also included. The movement of the rover and control system is explained. Programming and testing of the system are carried out to check proper functioning. Finally, the complete working model of the rover is obtained.

5.PERFORMANCE AND COST ANALYSIS

Cost Analysis and Overall Cost

Financially, the project operates under a highly specific, total fixed valuation of ₹50,000. This encompasses an estimated hardware Bill of Materials (BOM) of

₹15000—which intelligently includes a predetermined budgetary buffer for minor market price fluctuations, consumable wiring, and structural standoffs—as well as professional service fees totaling ₹50,000 (apportioned precisely as ₹30,000 for hardware development, machining, and assembly, and ₹20,000 for software coding, testing, and network configuration).

Category	Component Breakdown	Approx. Cost (INR)
Core Control	Raspberry Pi Zero 2 W + Adapter Kit + 32GB Class 10 SD Card	₹3,274
Locomotion	DIY Tank Chassis + 2x High-Torque DC Motors + L298N Driver	₹3,062
Robotic Arm	4-DOF Acrylic Frame + Servos (4x MG996R, 2x SG90) + PCA9685	₹3,538
Vision & Audio	Generic Pi Camera V2 + Pan/Tilt Bracket + USB Mini Microphone	₹2,257
Sensor Suite	ADS1115 ADC + MQ-2 + HC-SR04 + Inductive Proximity Sensor	₹1,518
Power System	12V Adapter/Rechargeable Battery + LM2596 Buck Converter	₹1,331
TOTAL	**Estimated Hardware Material Cost (including variance buffer)**	**₹15,000**

The total project operates under a **fixed budget of ₹50,000**, covering both hardware and professional services. The **hardware Bill of Materials (BOM)** is estimated at ₹15,000, which includes a buffer for minor price fluctuations, wiring, and structural supports. The **core control** is based on a Raspberry Pi Zero 2 W with SD card and adapter, costing ₹3,274. **Locomotion** uses a DIY tank chassis with 2 high-torque DC motors and an L298N driver at ₹3,062. The **robotic arm**, comprising a 4-DOF acrylic frame, six servos, and a PCA9685 controller, is ₹3,538. **Vision and audio** components, including a Pi Camera V2, pan/tilt bracket, and USB microphone, total ₹2,257. The **sensor suite** (ADS1115 ADC, MQ-2, HC- SR04, inductive sensor) costs ₹1,518, while the **power system** with a 12V adapter/battery and LM2596 converter is ₹1,331. Professional service fees are ₹35,000, split as ₹30,000 for hardware assembly and ₹20,000 for software development and testing. The total ensures **all components, sensors, and services are**

covered while keeping the project within the budget. This allocation allows a fully functional, reliable, and cost-effective multi-terrain robotic system.

RESULTS & CONCLSION

Result

- ✓ The Multi-Terrain Spy Rover with a Python-Based Control System was successfully Fabricated and implemented.
- ✓ The rover responds accurately to wireless commands with minimal delay.
- ✓ Real-time video streaming is achieved using a camera module for effective surveillance.
- ✓ Environmental hazards such as fire and smoke are detected using sensors with reliable performance.
- ✓ The thermal sensing feature helps in identifying temperature variations and heat sources.
- ✓ The servo motor-based robotic arm performs basic object handling and interaction tasks.
- ✓ The system provides real-time monitoring and control through wireless communication.
- ✓ The project is suitable for applications such as surveillance, disaster management, and industrial inspection.

Conclusion

- ✓ The Multi-Terrain Spy Rover with a Python-Based Control System has been successfully fabricated, and tested.
- ✓ The project effectively integrates mechanical design, electronics, and Python programming into a single system.
- ✓ Real-time video streaming and sensor-based hazard detection enhance the system's surveillance capability.
- ✓ The integration of a robotic arm and thermal sensing adds advanced functionality to the system.
- ✓ The project reduces human risk in hazardous environments by enabling remote inspection and monitoring.
- ✓ This project provides a strong foundation for future advancements in robotics and automation.

Future Scope

- ✓ Enhancement of robotic arm for advanced handling and operations
- ✓ Addition of more advanced sensors for improved environmental monitoring
- ✓ Improvement in battery capacity for longer operation time

Project Images









REFERENCES

- M. Kulkarni, A. Mishra, P. Barabde, and D. Shah, "IoT Based Multifunctional Robot Using Raspberry Pi," *International Journal of Advances in Electronics and Computer Science*, vol. 4, no. 3, pp. 111–115, Mar. 2017.
- M. A. Navarrete-Sanchez et al., "IoT-Based Classroom Temperature Monitoring and Missing Data Prediction Using Raspberry Pi and ESP32," *Journal of Robotics and Control*, vol. 6, no. 1, 2025.
- P. Kitchagiri et al., "Night Vision Patrolling Robot for Security Using Raspberry Pi," *International Journal of Engineering Research and Applications*, vol. 11, no. 5, pp. 01–07, May 2021.
- Mohana et al., "Design and Development of Web Controlled Surveillance Robot Using Computer Vision," 2023.
- R. Kumar et al., "Smart Spy Rover Using Raspberry Pi for Surveillance and Threat Detection," *IARJSET*, vol. 12, no. 5, 2025.
- H. Panchangam, "Robotic Arm Using IoT and Raspberry Pi," *IJCRT*, vol. 8, no. 9, 2020.
- V. Vijaya Durga et al., "IoT Based Weather and Air Pollution Monitoring System Using Raspberry Pi Pico," *IJCRT*, vol. 13, no. 4, 2025.
- A. Jhon Presin Kumar et al., "Design and Fabrication of Long Range Spy Robot with Night Vision Using Ultrasonic Sensor," *IJIREEICE*, vol. 13, no. 4, 2025.
- A. M. Valentino and J. T. Leonen, "IoT-Based Smart Security Robot with Android App, Night Vision and Enhanced Threat Detection," *IEEE Conference*, 2023.