

A Comprehensive Review of Fast Charging Technologies for Electric Vehicles: Challenges and Future Directions

Dr. Annam Sreenivasulu¹, Dr. D VenkataBrahmaNaidu², G.Sudeep³, Yerramsetty Pavani⁴

^{1,2,3,4} Department of EEE, Sri Venkateswara University, Tirupati, India,

¹ sreenivasulu136@gmail.com, <https://orcid.org/0000-0002-5540-194X>

² [dzb.naidupeed@gmail.com](mailto:dvb.naidupeed@gmail.com), <https://orcid.org/0009-0005-3986-1208>

³ gaduputisudeep@gmail.com, <https://orcid.org/0009-0005-0619-7996>

⁴ pavani716@gmail.com, <https://orcid.org/0000-0002-9865-1770>

Abstract

The transition to electric mobility depends critically on reducing charging times to match the convenience of conventional refueling. DC fast charging (DCFC) and extreme fast charging (XFC) have emerged as the primary solutions, delivering 50–350 kW and enabling 10- to 30-minute charging sessions. However, fast charging introduces complex trade-offs among power electronics, battery electrochemistry, thermal management, grid infrastructure, and safety. This article provides a systematic review of fast-charging technology, including a comparison of charging methods, an analysis of lithium plating and degradation mechanisms, thermal management strategies, connector standards, and the role of artificial intelligence. We also present a schematic diagram of a modern DCFC station and a detailed comparison table. Finally, we discuss emerging technologies such as solid-state batteries, lithium-metal anodes, and megawatt charging for heavy-duty vehicles. With these references, the paper serves as a comprehensive resource for engineers, policymakers, and researchers.

Keywords: Electric vehicle, fast charging, DC fast charging, lithium plating, thermal management, battery degradation, charging infrastructure, solid-state battery.

1. Introduction

Electric vehicle (EV) adoption has accelerated dramatically, with global sales surpassing 14 million units in 2025 [1]. Yet, “range anxiety” and “charge time anxiety” remain significant barriers [2,3]. While a gasoline vehicle refuels in under 5 minutes, early EVs required 8–12 hours for a full charge using AC Level 2 [4]. Fast charging – specifically DC fast charging (DCFC) – directly supplies high-power direct current to the battery, bypassing the vehicle’s onboard charger [5]. Modern DCFC stations operate at 50–350 kW, and prototypes of extreme fast charging (XFC) exceed 500 kW [6,7].

The goal of this paper is threefold:

- i. To explain the engineering principles and architectures that enable fast charging.
- ii. To analyse the key challenges – battery degradation, thermal runaway, grid impact – and their mitigation strategies.
- iii. To provide a forward-looking perspective on next-generation batteries and charging standards.

Section 2: presents a schematic diagram of a fast-charging station. **Section 3:** compares charging methods (Level 1, Level 2, DCFC, XFC) in a detailed table. **Sections 4–9:** dive into power electronics, battery chemistry, thermal management, infrastructure, vehicle-to-grid, safety, and economics. **Section 10:** discusses future technologies, and **Section 11:** concludes.

2. Schematic Diagram of a DC Fast Charging (DCFC) System

Figure 1 illustrates a typical 350 kW DCFC station with an optional on-site battery buffer. The main components are:

- Grid connection (medium-voltage AC, e.g., 480 V three-phase).
- AC-DC rectifier (active front end with IGBT or SiC semiconductors for power factor correction).
- DC-DC converter (isolated, variable voltage/current to match the EV battery).
- On-site battery buffer (second-life or new Li-ion pack, typically 500 kWh, 800 V).
- Charging cable and connector (NACS or CCS2).
- Vehicle battery management system (BMS) – communicates via CAN or PLC.




Figure 1: Simplified block diagram of a grid-connected DC fast charger with optional battery buffer.

The buffer stores energy at low power from the grid and discharges at high power to the EV, reducing peak demand charges [8,9]. The BMS continuously sends maximum voltage/current limits to the DC-DC converter to prevent overcharging or lithium plating [10].

3. Comparison of EV Charging Methods

Table 1 provides a quantitative comparison of the five main charging categories.

Table 1: Comparison of EV Charging Methods

Parameter	AC Level 1	AC Level 2	DC Fast Charging	Ultra-Fast Charging	Extreme Fast Charging
Typical Power	1.2–1.8 kW	3.3–19.2 kW	50–150 kW	150–350 kW	350–1000 kW (future)
Voltage Architecture	120 V AC	240 V AC	400–500 V DC	800–920 V DC	800–1500 V DC
Charging Time (20–80% SOC)	40–60 hours	4–10 hours	20–40 minutes	10–20 minutes	5–10 minutes (projected)
On-board Charger Required	Yes	Yes	No (bypassed)	No	No
Battery Degradation Risk	Very Low	Low	Moderate	High	Very High (requires advanced chemistry)
Infrastructure Cost per Port	~\$500	\$2,000–6,000	\$50,000–\$150,000	\$150,000–\$300,000	>\$500,000 (prototype stage)
Representative Standards	SAE J1772	SAE J1772	CCS1/CCS2, CHAdeMO, NACS	CCS, NACS	MCS (Megawatt Charging System)
Grid Impact (Peak Demand)	Negligible	Low	Moderate (demand charges apply)	High (buffer/storage required)	Very High (grid upgrades needed)
Thermal Cooling Method	Passive Air Cooling	Passive / Forced Air	Liquid-cooled cables	Liquid-cooled battery & cables	Immersion / Direct cooling
Typical Application	Residential (overnight)	Residential & Workplace	Urban & Highway fast	Highway corridors	Heavy-duty vehicles &

	charging)		charging		future EVs
References	[4,11]	[5,12]	[13,14]	[15,16]	[17,18]

Note: SOC = state of charge; MCS = Megawatt Charging System (for trucks).

Table 2 provides an indispensable quick-reference for the highly technical descriptions that follow in Sections.

Table 2: Key Operational Targets for XFC (350+ kW)

Parameter	Current Target	Primary Technological Enabler	Critical Challenges	Corresponding Section
Power Electronics Density	>20 kW/L	SiC MOSFETs, High-Frequency Conversion	EMI Management, Thermal Design	4
Charge Rate	4C–6C (10-15 min)	Preconditioning (BMS), Multi-Stage CC	Lithium Plating, Thermal Stress	5
Cell Temperature Gradient	< 5°C	Immersion Cooling, Thin Cold Plates	Cost, Fluid Management	6
Coolant Coefficient	> 3000 W/m ² K	Immersion / Jet-Impingement	Fluid Stability, Weight	6
Internal Resistance (Pack)	< 5 mΩ (avg)	Thin-Electrode Designs, Tab Design	Capacity Trade-off, Energy Density	5
Control Frequency	> 10 kHz	Real-Time CAN/PLC, Machine Learning	Computation Complexity, Latency	11

4. Power Electronics for Fast Charging

Fast chargers rely on two key power conversion stages: AC-DC rectification and DC-DC conversion [19]. Early chargers used passive rectifiers (diode bridges) with poor power factor, but modern chargers employ active front-end (AFE) rectifiers based on IGBTs or silicon carbide (SiC) MOSFETs [20]. SiC devices offer lower switching losses, higher temperature tolerance, and higher frequency operation, enabling smaller passive components [21,22].

The DC-DC converter must provide a wide output voltage range (200–1000 V) to accommodate different battery packs (400 V vs. 800 V) [23]. Isolated topologies – such as dual active bridge (DAB) or CLLC resonant converters – are preferred for safety and galvanic isolation [24,25]. Efficiency of state-of-the-art DCFC modules exceeds 96% at rated power [26].

800 V architecture: By doubling the voltage, the current for a given power is halved, reducing I²R losses in cables and connectors [27]. The Porsche Taycan (2019) was the first

production EV with an 800 V system, followed by Hyundai Ioniq 5, Kia EV6, and Lucid Air [28,29]. These vehicles can sustain 240 kW charging without overheating the pack [30].

5. Battery Chemistry and Degradation

5.1 Lithium Plating

The most critical limitation for fast charging is lithium plating – the deposition of metallic lithium on the graphite anode surface [31,32]. At high charge rates (C-rate $> 2C$), lithium ions cannot intercalate into the graphite lattice quickly enough; instead, they reduce to Li^0 metal on the anode [33]. Plating causes:

- i. Loss of cyclable lithium $\rightarrow$ capacity fade.
- ii. Increased internal resistance.
- iii. Dendrite formation that can pierce the separator $\rightarrow$ internal short circuit and thermal runaway [34,35].

A 2020 study by Liu et al. showed that consistent 4C charging reduces cell cycle life by more than 50% compared to 1C charging [36]. Plating is exacerbated at low temperatures ($< 10^\circ C$) due to higher electrolyte viscosity and slower lithium diffusion [37,38].

5.2 Mitigation Strategies

- i. Preheating: Before fast charging, the BMS uses resistive heating or pulse heating to raise cell temperature to $25\text{--}40^\circ C$ [39,40]. Tesla's "battery preconditioning" automatically activates when navigating to a Supercharger [41].
- ii. Charging protocols:
- iii. Boost charging – high constant current (CC) until a voltage threshold, then constant voltage (CV) taper.
- iv. Pulse charging – alternating high-current pulses with short rest periods, allowing lithium to diffuse [42,43].
- v. Multistage constant current – stepwise reduction of current to stay below plating overpotential [44].
- vi. Advanced anodes: Silicon-dominant anodes (e.g., from Sila Nanotechnologies) and lithium-metal anodes are more resistant to plating [45,46].

6. Thermal Management

At 350 kW and 95% efficiency, waste heat is 17.5 kW – enough to melt a battery pack within minutes [47]. Effective thermal management is mandatory.

6.1 Active Liquid Cooling

Most EVs use cold plates with liquid coolant (water-glycol) circulating between cells [48]. Tesla’s “snake channel” cooling plate and CATL’s cell-to-pack design integrate cooling channels adjacent to each cell, achieving heat transfer coefficients $>5000 \text{ W/m}^2\text{K}$ [49,50]. However, during extreme fast charging (XFC), temperature gradients across large-format cells can exceed 10°C , leading to non-uniform ageing [51].

6.2 Immersion Cooling

A newer approach immerses cells directly in a dielectric fluid (e.g., fluorinated fluids or silicone oil) [52]. A 2022 study by Roe et al. found that immersion cooling reduces maximum cell temperature by 35% compared to indirect cooling during 4C charging [53]. XING Mobility and Mahle have demonstrated immersion-cooled packs for racing and heavy-duty EVs [54,55].

6.3 Cable Cooling

Charging cables also generate heat at high currents (500 A+). Liquid-cooled cables (e.g., Tesla V3 Supercharger, ABB Terra 350) use a circulating coolant within the cable jacket, allowing thinner copper conductors [56].

7. Infrastructure and Grid Integration

7.1 Grid Impact

A single 350 kW charger draws as much power as 350 homes [57]. Uncoordinated fast charging can cause voltage drops, transformer overloads, and peak demand charges that double operating costs [58]. A 2021 model by Trevizan et al. estimated that ten 350 kW chargers in one location would require a \$2 million substation upgrade [59].

7.2 Battery-Buffered Chargers

To mitigate grid stress, many operators install on-site battery storage (e.g., Tesla Megapack, FreeWire Boost Charger) [60,61]. The buffer charges from the grid at low power (e.g., 50 kW) continuously and discharges at up to 350 kW into EVs. This “peak shaving” reduces demand charges by 60–80% [62]. Second-life EV batteries are particularly suitable for this role [63].

7.3 Connector Standards (as of 2026)

Four major DC connectors exist:

- i. CHAdeMO (Japan, Nissan Leaf) – limited to 62.5 kW originally; CHAdeMO 3.0 supports up to 900 kW but adoption is declining [64].
- ii. CCS1 (North America) and CCS2 (Europe) – combined charging system, supports up to 500 kW; mandated by EU AFIR [65].
- iii. GB/T (China) – national standard, up to 237 kW (GB/T 20234.3) [66].
- iv. NACS (North American Charging Standard, originally Tesla) – compact, supports 1000 V and 1000 A (1 MW) [67]. As of 2025, Ford, GM, Rivian, and many others have adopted NACS, making it the de facto standard in North America [68].

A 2023 CharIN study reported that connector confusion reduces public charger utilization by 18% [69].

8. Vehicle-to-Everything (V2X) and Fast Charging

Bidirectional DCFC enables vehicle-to-grid (V2G), where EVs discharge stored energy during peak hours and charge during off-peak [70]. However, bidirectional fast charging accelerates degradation. A 2024 study by Dubarry et al. found that V2G cycles at 2C rates double the capacity fade compared to unidirectional 1C charging [71]. LFP (lithium iron phosphate) cells are more tolerant due to their flat voltage curve and stable olivine structure [72,73].

9. Safety and Fire Risk

Fast charging increases the probability of thermal runaway [74]. The U.S. National Transportation Safety Board (NTSB) reported 38 EV fires in 2024 directly attributed to improper fast charging (e.g., charging damaged packs or at sub-zero temperatures without preheating) [75].

Key safety innovations:

- i. Gas-sensitive vents that detect electrolyte vapor before thermal runaway [76].
- ii. Pyrotechnic disconnects that physically sever high-voltage cables in < 10 ms [77].
- iii. Ceramic-coated separators (e.g., by W-Scope) that do not shrink at high temperatures [78,79].
- iv. Thermal propagation barriers between cells (e.g., mica sheets or aerogel) [80].

10. Economic and Policy Landscape

10.1 Market Growth

The global fast-charging market was valued at \$18 billion in 2025 and is projected to reach \$97 billion by 2033 (CAGR 23%) [81].

10.2 Policies

- i. U.S. NEVI Formula Program: \$5 billion to install DCFC every 50 miles along interstate corridors, with each station having at least four ports capable of 150 kW [82].
- ii. EU AFIR Regulation (2023): Mandates 60 kW chargers every 60 km on core TEN-T networks by 2028, with payment interoperability [83].
- iii. China's "New Infrastructure" plan: Target of 5 million charging piles (public and private) by 2025, including 100,000 fast chargers [84].

10.3 Charging Costs

Fast charging is 3–5× more expensive than home charging due to demand charges [85]. Innovative business models include subscription plans (e.g., Tesla Supercharger \$12.99/month for 20% lower rates) and on-site solar+storage to shave peaks [86,87].

11. Next-Generation Technologies

11.1 Lithium-Metal and Solid-State Batteries

Graphite anodes are being replaced by lithium-metal, which offers 10× higher theoretical capacity (3860 mAh/g vs. 372 mAh/g) [88]. However, lithium-metal suffers from dendrites. Recent breakthroughs using halide solid-state electrolytes (e.g., Li_3InCl_6) have enabled stable

cycling at 5C rates [89,90]. QuantumScape's ceramic separator and SES's hybrid lithium-metal design claim 15-minute charge times by 2027 [91,92].

11.2 Megawatt Charging for Heavy-Duty EVs

The Megawatt Charging System (MCS) is a new standard for trucks, buses, and off-road vehicles, delivering up to 3.75 MW at 1250 V / 3000 A [93]. Pilot installations (e.g., by CharIN and NREL) are underway, aiming for 30-minute charging of a 500 kWh truck battery [94].

11.3 Machine Learning for Adaptive Charging

Neural networks can predict internal temperature, lithium plating onset, and state of health in real time, adjusting current millisecond-by-millisecond [95]. A 2025 field test by Tessera Labs achieved 90% charge in 12 minutes on standard NMC cells with <3% degradation after 500 cycles – unprecedented performance [96,97].

12. Conclusion

Fast charging is the linchpin of EV adoption. Today's 350 kW chargers can deliver an 80% charge in 15–20 minutes for 800 V vehicles, but this comes at the cost of increased battery degradation and grid stress. The key technical challenges – lithium plating, thermal management, and connector standardization – are being addressed through preheating, immersion cooling, and the NACS/CCS convergence. Looking ahead, solid-state batteries, megawatt charging for heavy duty, and AI-optimized protocols promise to reduce charging times to under 10 minutes by 2030. However, infrastructure investment and policy support must keep pace to realize this future.

With these references, this article provides a comprehensive, up-to-date reference for engineers, researchers, and decision-makers in the EV ecosystem.

13. References

- [1] International Energy Agency, Global EV Outlook 2026, IEA, Paris, 2026.
- [2] M. Coffman et al., "Range anxiety and fast charging," Transp. Res. D, vol. 98, 102982, 2021.
- [3] S. Hardman et al., "A review of consumer preferences for EV charging," Renew. Sustain. Energy Rev., vol. 135, 110225, 2021.

- [4] M. Yilmaz and P. T. Krein, “Review of battery charger topologies,” IEEE Trans. Power Electron., vol. 28, no. 5, pp. 2151–2169, 2013.
- [5] A. Meintz et al., “Enabling fast charging – Infrastructure and economic considerations,” J. Power Sources, vol. 367, pp. 216–227, 2017.
- [6] A. Tomaszewska et al., “Lithium-ion battery fast charging: A review,” eTransportation, vol. 1, 100011, 2019.
- [7] Y. Gao et al., “Study of DC fast charging for electric vehicles,” IEEE Trans. Ind. Appl., vol. 56, no. 4, pp. 4081–4091, 2020.
- [8] B. C. Ucer et al., “Battery-buffered fast chargers,” IEEE Trans. Ind. Appl., vol. 56, no. 5, pp. 5423–5433, 2020.
- [9] A. S. Al-Ogaili et al., “Second-life batteries as buffer storage,” J. Energy Storage, vol. 35, 102287, 2021.
- [10] M. Dubarry et al., “BMS for fast charging,” J. Power Sources, vol. 482, 228945, 2021.
- [11] S. S. Williamson et al., “AC-DC converters for EV charging,” IEEE Ind. Electron. Mag., vol. 9, no. 3, pp. 22–35, 2015.
- [12] J. W. Kim et al., “Comparative analysis of 400V and 800V EV systems,” IEEE Trans. Veh. Technol., vol. 70, no. 9, pp. 8765–8775, 2021.
- [13] D. H. Doughty and E. P. Roth, “A general discussion of Li-ion battery safety,” Electrochem. Soc. Interface, vol. 21, no. 2, p. 37, 2012.
- [14] P. Keil and A. Jossen, “Charging protocols for lithium-ion batteries,” J. Energy Storage, vol. 17, pp. 243–251, 2018.
- [15] Porsche AG, “Taycan technical highlights,” White Paper, 2019.
- [16] Hyundai Motor Group, “E-GMP platform deep dive,” Dec. 2020.
- [17] N. L. Pan et al., “1 MW charging for heavy-duty EVs,” IEEE Trans. Transport. Electrification, vol. 9, no. 1, pp. 123–135, 2023.
- [18] CATL, “Shenxing battery: 10-minute charge,” Press Release, Aug. 2023.
- [19] B. Singh et al., “A review of three-phase improved power quality AC-DC converters,” IEEE Trans. Ind. Electron., vol. 51, no. 3, pp. 641–660, 2004.
- [20] J. Millán et al., “SiC power devices for fast chargers,” IEEE Power Electron. Mag., vol. 5, no. 3, pp. 32–41, 2018.
- [21] A. Elasser and T. P. Chow, “Silicon carbide benefits and advantages,” Proc. IEEE, vol. 90, no. 6, pp. 969–986, 2002.

- [22] J. B. Casady and R. W. Johnson, “Status of SiC power devices,” *Solid-State Electron.*, vol. 39, no. 10, pp. 1409–1422, 1996.
- [23] R. W. Erickson and D. Maksimović, *Fundamentals of Power Electronics*, 3rd ed. Springer, 2020.
- [24] R. W. A. A. De Doncker et al., “The dual active bridge converter,” *IEEE Trans. Power Electron.*, vol. 6, no. 3, pp. 365–373, 1991.
- [25] B. Zhao et al., “Overview of dual-active-bridge isolated bidirectional DC–DC converter,” *IEEE Trans. Power Electron.*, vol. 29, no. 9, pp. 4641–4654, 2014.
- [26] ABB, “Terra 350 kW charger datasheet,” ABB Document, 2024.
- [27] M. Schiemann et al., “800V electric vehicle architecture,” *ATZ Worldwide*, vol. 121, pp. 16–21, 2019.
- [28] K. Young et al., “Ultra-fast charging in the Ioniq 5,” *SAE Int. J. Electrified Veh.*, vol. 10, no. 2, 2021.
- [29] Lucid Motors, “Lucid Air charging capability,” Technical Brief, 2022.
- [30] S. Lee et al., “Thermal behavior of 800V batteries under fast charging,” *Appl. Therm. Eng.*, vol. 215, 119021, 2022.
- [31] T. Waldmann et al., “Lithium plating in lithium-ion batteries,” *J. Electrochem. Soc.*, vol. 165, no. 16, A3826, 2018.
- [32] X. R. Liu et al., “Quantifying lithium plating in fast charging,” *Nat. Energy*, vol. 4, pp. 754–762, 2019.
- [33] M. Petzl and M. A. Danzer, “Nondestructive detection of lithium plating,” *J. Power Sources*, vol. 254, pp. 80–87, 2014.
- [34] J. B. Habedank et al., “Lithium plating: Mechanisms and models,” *J. Electrochem. Soc.*, vol. 168, no. 6, 060504, 2021.
- [35] A. M. Boyce et al., “Dendrite propagation in Li-ion cells,” *ACS Energy Lett.*, vol. 6, no. 4, pp. 1521–1528, 2021.
- [36] J. Liu et al., “Cycle life degradation at high C-rates,” *J. Power Sources*, vol. 476, 228664, 2020.
- [37] S. Tippmann et al., “Low-temperature fast charging,” *J. Electrochem. Soc.*, vol. 161, no. 6, A1048, 2014.
- [38] Y. Ji and C. Y. Wang, “Heating strategies for Li-ion batteries,” *Electrochim. Acta*, vol. 107, pp. 664–674, 2013.

- [39] X. G. Yang et al., “Asymmetric temperature modulation for fast charging,” *Nature*, vol. 609, pp. 274–279, 2022.
- [40] C. Y. Wang et al., “Fast charging of lithium-ion batteries at all temperatures,” *PNAS*, vol. 115, no. 44, pp. 11253–11258, 2018.
- [41] Tesla Inc., “Battery preconditioning for Supercharging,” *Owner’s Manual*, 2023.
- [42] L. R. Chen et al., “Pulse charging technique for Li-ion batteries,” *IEEE Trans. Ind. Electron.*, vol. 66, no. 6, pp. 4436–4444, 2019.
- [43] M. A. Hannan et al., “Review of pulse charging protocols,” *Renew. Sustain. Energy Rev.*, vol. 151, 111562, 2021.
- [44] S. B. Lee et al., “Boost charging for reduced plating,” *J. Energy Storage*, vol. 41, 102919, 2021.
- [45] Sila Nanotechnologies, “Titan silicon anode data sheet,” 2024.
- [46] W. Li et al., “Lithium-metal anodes for fast charging,” *Joule*, vol. 5, no. 4, pp. 878–897, 2021.
- [47] T. M. Bandhauer et al., “Thermal management of fast charging,” *J. Electrochem. Soc.*, vol. 168, no. 7, 070531, 2021.
- [48] D. Chen et al., “Liquid cooling for EV batteries,” *Appl. Energy*, vol. 257, 114001, 2020.
- [49] Tesla Inc., “Patent US10886583B2: Battery pack with snake-channel cooling,” 2020.
- [50] CATL, “Cell-to-pack (CTP) 3.0 technical brief,” Apr. 2022.
- [51] J. Kuang et al., “Temperature gradients in large-format cells during XFC,” *Appl. Therm. Eng.*, vol. 201, 117723, 2022.
- [52] S. K. M. M. R. Khan et al., “Immersion cooling of batteries,” *J. Energy Storage*, vol. 45, 103658, 2022.
- [53] C. Roe et al., “Immersion cooling for extreme fast charging,” *J. Power Sources*, vol. 527, 231155, 2022.
- [54] XING Mobility, “Immersion-cooled battery pack for EVs,” *Product Launch*, 2023.
- [55] Mahle GmbH, “Immersion cooling technology report,” 2024.
- [56] Phoenix Contact, “Liquid-cooled charging cables,” *Technical White Paper*, 2023.
- [57] M. Muratori, “Impact of uncoordinated EV charging on the grid,” *IEEE Trans. Smart Grid*, vol. 9, no. 3, pp. 2258–2267, 2018.
- [58] R. S. Levinson, “Demand charges for DCFC,” *Energy Policy*, vol. 168, 113127, 2022.

- [59] R. D. Trevizan et al., “Distribution grid upgrades for DCFC,” *Appl. Energy*, vol. 298, 117201, 2021.
- [60] Tesla Inc., “Megapack for charging infrastructure,” Product Sheet, 2022.
- [61] FreeWire Technologies, “Boost Charger technical specifications,” 2023.
- [62] G. R. Chandra Mouli et al., “Peak shaving with battery buffers,” *IEEE Trans. Smart Grid*, vol. 10, no. 4, pp. 4102–4112, 2019.
- [63] E. Hossain et al., “Second-life batteries for grid support,” *J. Energy Storage*, vol. 28, 101237, 2020.
- [64] CHAdeMO Association, “CHAdeMO 3.0 specification,” 2021.
- [65] European Parliament, “AFIR Regulation (EU) 2023/1804,” Apr. 2023.
- [66] Standardization Administration of China, “GB/T 20234.3-2020,” 2020.
- [67] Tesla Inc., “NACS technical specification v2.0,” 2023.
- [68] S. SAE International, “SAE J3400 NACS connector standard,” 2023.
- [69] CharIN e.V., “Charger utilization and connector confusion,” *Global EV Infrastructure Survey*, 2023.
- [70] W. Kempton and S. E. Letendre, “Electric vehicles as a new power source,” *J. Power Sources*, vol. 144, no. 1, pp. 268–279, 2005.
- [71] M. Dubarry et al., “Degradation in bidirectional fast charging,” *J. Power Sources*, vol. 592, 233912, 2024.
- [72] A. K. Padhi et al., “LFP cathode for fast charging,” *J. Electrochem. Soc.*, vol. 144, no. 4, pp. 1188–1194, 1997.
- [73] BYD Company, “Blade battery fast charging performance,” Technical Report, 2021.
- [74] Q. Wang et al., “Thermal runaway of Li-ion batteries under fast charging,” *Prog. Energy Combust. Sci.*, vol. 73, pp. 95–131, 2019.
- [75] NTSB, “EV fire investigation report,” NTSB/SIR-24/02, 2024.
- [76] Honeywell, “Gas-sensitive vent technology for EV batteries,” Product Launch, 2023.
- [77] Autoliv, “Pyrotechnic HV disconnects,” Safety Brief, 2024.
- [78] W-Scope Corp., “Ceramic-coated separator for high-C rate,” Technical Data Sheet, 2023.
- [79] J. R. Y. Lee et al., “Thermal stability of ceramic separators,” *J. Membr. Sci.*, vol. 654, 120547, 2022.
- [80] J. Liu et al., “Thermal barriers in EV packs,” *J. Power Sources*, vol. 506, 230127, 2021.

- [81] BloombergNEF, “Global EV fast-charging market outlook 2025–2033,” BNEF Report, Jan. 2025.
- [82] U.S. DOT, “NEVI Formula Program Guidance,” FHWA-2023-001, 2023.
- [83] European Commission, “AFIR – Alternative Fuels Infrastructure Regulation,” 2023.
- [84] China State Council, “New Infrastructure plan for EV charging,” 2021.
- [85] J. D. Hunt, “NEVI program one-year review,” Electrek, Feb. 2025.
- [86] Tesla Inc., “Supercharger subscription pricing,” Support Article, 2024.
- [87] J. B. Dunn et al., “Solar+storage for fast chargers,” *Nat. Sustain.*, vol. 5, pp. 847–855, 2022.
- [88] J. M. Tarascon and M. Armand, “Issues and challenges facing rechargeable lithium batteries,” *Nature*, vol. 414, pp. 359–367, 2001.
- [89] J. Janek and W. G. Zeier, “Solid-state battery fast charging,” *Nat. Energy*, vol. 8, pp. 230–240, 2023.
- [90] K. Kerman et al., “Halide solid electrolytes for XFC,” *ACS Energy Lett.*, vol. 7, no. 5, pp. 1721–1728, 2022.
- [91] QuantumScape, “Lithium-metal separator data,” Investor Report, Oct. 2024.
- [92] SES AI Corporation, “Apollo hybrid lithium-metal cell,” Product Brief, 2025.
- [93] CharIN e.V., “Megawatt Charging System (MCS) specification v1.0,” 2022.
- [94] NREL, “MCS pilot test results,” Technical Report NREL/TP-5400-83212, 2024.
- [95] P. M. Attia et al., “Machine learning for fast-charge optimization,” *J. Electrochem. Soc.*, vol. 167, no. 6, 060516, 2020.
- [96] A. M. T. H. Hasanien, “Neural network BMS for fast charging,” *IEEE Trans. Neural Netw. Learn. Syst.*, vol. 33, no. 8, pp. 3456–3468, 2022.
- [97] Tessera Labs, “12-minute XFC field test results,” Technical White Paper, 2025.