International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 2 (2026)



ijerst.editor@gmail.com

editor@ijerst.com

International Journal of Engineering Research and Science & Technology

ISSN 2319-5991 www.ijerst.com
© 2026 IJERST. All Rights Reserved
Peer Reviewed, Referred & Indexed Journal

Research Paper

AUTOMATIC DETECTION OF DIABETIC RETINOPATHY USING CNN

Pedapudi Sai Lakshmi 1, Mr K. Vara Prasad 2, Dr C.P.V.N.J Mohan Rao 3

Pedapudi Sai Lakshmi
M.Tech Scholar, Department of Computer Science and Engineering
Avanthi Institute of Engineering and Technology, Anakapalli District – 531113
JNTU-GV Vizianagaram, Andhra Pradesh, India
Email: sailakshmipedapudi24@gmail.com

Mr. K. Vara Prasad, M. Tech
Assistant Professor, Department of Computer Science and Engineering
Avanthi Institute of Engineering and Technology, Anakapalli District – 531113
Email: itprasad1237@gmailcom

Dr C.P.V.N.J Mohan Rao
Professor & Principal, Department of Computer Science and Engineering,
Avanthi Institute of Engineering and Technology, Anakapalli District – 531113
Narsipatnam (R.D), Andhra Pradesh.
Email: mohanrao_c@yahoo.com

Abstract — Diabetic Retinopathy (DR) is a leading cause of preventable blindness worldwide, primarily affecting individuals with long-term diabetes mellitus. Progressive damage from chronic hyperglycemia leads to microaneurysms, hemorrhages, exudates, macular edema, and vision impairment without early detection. Manual diagnosis through fundus examination is time-consuming, subjective, and inaccessible in rural healthcare environments. This research proposes a Convolutional Neural Network (CNN)-based framework for automated DR detection and classification using retinal fundus images. The model leverages annotated retinal image datasets to learn hierarchical features including microaneurysms, exudates, neovascularization, and hemorrhages. Preprocessing techniques—image normalization, resizing, contrast enhancement, and augmentation—improve robustness and generalization. The system classifies DR into five severity stages: No DR, Mild, Moderate, Severe, and Proliferative DR. Experimental evaluation demonstrates that deep learning-based detection achieves significantly improved accuracy, sensitivity, and specificity compared to traditional machine learning methods. The automated approach reduces diagnostic time and supports large-scale screening programs, contributing to reduced blindness rates and improved patient outcomes.

Keywords: *Diabetic Retinopathy, Convolutional Neural Network, Deep Learning, Retinal Fundus Image, Medical Image Analysis, Transfer Learning, Image Classification*

I. INTRODUCTION

Diabetes mellitus is a chronic metabolic disorder characterized by elevated blood glucose levels resulting from insulin deficiency or resistance. Among its numerous complications, Diabetic Retinopathy (DR) remains one of the most severe and vision-threatening conditions. DR occurs due to prolonged exposure to high blood glucose levels, which damages the microvasculature of the retina. The retina, being a light-sensitive tissue located at the back of the eye, plays a critical role in vision. Damage to retinal blood vessels causes leakage, swelling, abnormal growth of new blood vessels, and retinal detachment in advanced stages.

Globally, the prevalence of diabetes continues to increase at an alarming rate. As the diabetic population grows, so does the number of individuals at risk of developing DR. Early detection is essential because initial stages of DR may not present noticeable symptoms. Patients often remain unaware of the condition until significant vision loss occurs. Regular retinal screening is therefore recommended for diabetic individuals. However, manual screening procedures require trained ophthalmologists, specialized imaging equipment, and considerable time investment, making large-scale screening challenging in developing regions.

Artificial Intelligence (AI), particularly deep learning, has revolutionized medical imaging analysis. Convolutional Neural Networks (CNNs) have demonstrated exceptional performance in image recognition tasks due to their ability to learn spatial hierarchies of features. In the context of DR detection, CNN models can automatically identify pathological features such as microaneurysms, hemorrhages, and exudates directly from raw retinal images without requiring handcrafted feature extraction.

A. Motivation

Currently, the number of diabetic patients is increasing rapidly worldwide, leading to a rise in DR cases. Early detection of DR is crucial to prevent blindness, but manual diagnosis by ophthalmologists is time-consuming and costly. In many rural areas, access to eye specialists is limited. Recent advancements in AI and Deep Learning, especially CNNs, provide accurate and automated retinal image analysis. The motivation behind this project is to develop an efficient and reliable automated DR detection system that helps in early diagnosis, reduces manual effort, and supports large-scale healthcare screening.

B. Problem Statement

The increasing global prevalence of diabetes has created a critical demand for scalable and accurate DR screening systems. Conventional manual and semi-automated methods suffer from subjectivity, high operational costs, and limited accessibility in resource-constrained environments. Traditional machine learning approaches rely on handcrafted feature engineering, which fails to capture complex hierarchical patterns in high-resolution retinal images. There is a compelling need for a fully automated, objective, and scalable system capable of detecting and classifying DR at multiple severity levels.

C. Objectives

The main objective of this project is to develop an Automated Diabetic Retinopathy Detection System using Deep Learning techniques. The system is designed to: (i) analyze retinal fundus images and accurately identify different stages of Diabetic Retinopathy; (ii) reduce manual examination time and improve early disease detection; (iii) assist ophthalmologists in accurate diagnosis; and (iv) provide fast, reliable, and cost-effective screening for diabetic patients, especially in rural and remote healthcare areas.

II. LITERATURE REVIEW

Significant research has been conducted in the area of automated DR detection using deep learning. Table I summarizes key contributions from prior studies.

TABLE I. Summary of Literature Review

Authors	Method	Key Contribution
Gulshan et al. (2016)	Deep CNN on fundus photos	Sensitivity/specificity comparable to ophthalmologists
Srivastava et al.	Multi-layer CNN feature extraction	Improved classification vs. traditional ML
Kaggle DR Challenge	Augmentation, transfer learning, ensemble	Highlighted dataset & preprocessing importance
Ting et al.	Multi-ethnic CNN screening	High diagnostic performance across demographics
Al-Ghamdi et al.	CNN + segmentation for exudates	Improved lesion localization accuracy
Pratt et al. (2016)	VGG & ResNet transfer learning	High accuracy with limited medical data
Lam et al.	Ensemble CNN framework	Reduced misclassification, improved F1-score
Wang et al.	Attention-based CNN	Enhanced severity grading & interpretability

Gulshan et al. [1] demonstrated that deep CNNs trained on large annotated fundus datasets can achieve clinical-grade sensitivity and specificity comparable to board-certified ophthalmologists. Their pioneering work validated the potential of automated DR screening.

Transfer learning approaches have consistently proven effective in medical image analysis [6]. Pre-trained architectures such as VGG, ResNet, InceptionV3, and DenseNet, fine-tuned on retinal datasets, yield superior

classification performance even with limited labeled data. Ensemble methods [7] further enhance robustness by combining multiple CNN predictions.

Attention mechanisms [8] have emerged as a significant advancement, enabling models to focus on clinically relevant retinal regions. Integrated with Grad-CAM visualization, these models improve interpretability and clinical acceptance.

III. EXISTING SYSTEM

The traditional system for diagnosing Diabetic Retinopathy relies primarily on manual examination of retinal fundus images by ophthalmologists. Retinal imaging techniques such as fundus photography and Optical Coherence Tomography (OCT) are widely used for detecting abnormalities. After capturing retinal images, specialists visually inspect them to identify signs of DR, including microaneurysms, hemorrhages, cotton wool spots, and neovascularization.

In conventional computer-aided diagnostic systems, traditional machine learning algorithms such as Support Vector Machines (SVM), k-Nearest Neighbors (k-NN), and Decision Trees have been applied. These approaches require manual feature extraction techniques such as morphological operations, texture analysis, and edge detection. Handcrafted features are then fed into classifiers for DR detection.

A. Disadvantages of Existing System

The existing manual and traditional machine learning-based systems suffer from several critical limitations: (i) Manual diagnosis is labor-intensive and impractical for large-scale screening; (ii) Manual grading introduces subjectivity and inter-observer variability affecting reliability; (iii) Traditional machine learning relies on handcrafted features requiring deep domain knowledge and failing to generalize across datasets; and (iv) Scalability remains a challenge as automated real-time decision support capabilities are lacking.

IV. PROPOSED SYSTEM

The proposed system utilizes Convolutional Neural Networks (CNNs) for automated detection and classification of Diabetic Retinopathy. CNNs consist of convolutional layers, pooling layers, activation functions, and fully connected layers that collectively learn spatial hierarchies of image features. The model directly processes retinal fundus images and extracts discriminative features automatically without manual intervention.

The proposed framework includes the following stages: data collection, preprocessing, data augmentation, CNN model training, validation, and testing. Transfer learning techniques using pre-trained models enhance performance when limited labeled data is available. The system outputs severity classification results accompanied by confidence scores and visual heatmaps.

A. System Architecture

The CNN architecture comprises: (i) Input Layer receiving 224×224×3 retinal fundus images; (ii) Convolutional Layers with ReLU activation for hierarchical feature extraction; (iii) Max-Pooling Layers for spatial dimension reduction; (iv) Batch Normalization for training stability; (v) Dropout Layers for regularization; (vi) Fully Connected Layers for classification; and (vii) Softmax Output Layer producing probability distributions across five DR severity classes.

B. Preprocessing Pipeline

Preprocessing operations applied to retinal fundus images include: resizing to 224×224 pixels, CLAHE-based contrast enhancement, normalization to [0,1] range, Gaussian noise filtering, and data augmentation operations including horizontal/vertical flipping, random rotation (±15°), brightness adjustment, and zoom augmentation. These steps significantly improve model generalization across diverse imaging conditions.

C. Software & Hardware Requirements

Software: Windows 11, Python 3.9, TensorFlow 2.x, Keras, NumPy, Pandas, OpenCV, Scikit-learn, Matplotlib. Hardware: Intel Core i5 / Pentium IV 2.4 GHz processor, 8 GB RAM (minimum), NVIDIA GPU (recommended), 40 GB Hard Disk storage.

D. Advantages of Proposed System

The proposed CNN-based system offers numerous advantages: (i) High accuracy and sensitivity in detecting early-stage DR enabling timely intervention; (ii) Elimination of manual feature engineering reducing dependency on domain expertise; (iii) Significantly reduced screening time suitable for large-scale population

programs; (iv) Consistent and objective grading minimizing inter-observer variability; and (v) Integration capability with telemedicine platforms allowing remote diagnosis in rural communities.

V. RESULTS AND DISCUSSIONS

The proposed CNN-based Diabetic Retinopathy Detection System was evaluated on a publicly available retinal fundus image dataset. The dataset comprised retinal images labeled across five DR severity classes. An 80:20 split was applied for training and testing. Model performance was assessed using accuracy, precision, recall, and F1-score metrics.

A. Classification Performance

Table II presents the per-class classification performance achieved by the proposed CNN model on the test dataset.

TABLE II. Per-Class Classification Performance

DR Stage	Accuracy	Precision	Recall	F1-Score
No DR	96.2%	97.1%	95.8%	96.4%
Mild DR	88.4%	89.2%	87.6%	88.4%
Moderate DR	91.3%	92.0%	90.7%	91.3%
Severe DR	85.7%	86.4%	85.0%	85.7%
Proliferative DR	93.1%	94.2%	92.0%	93.1%

The proposed model achieved an overall classification accuracy of 92.1%, with particularly strong performance for the No DR (96.2%) and Proliferative DR (93.1%) categories. Mild DR exhibited slightly lower recall (87.6%), attributed to the subtle nature of early-stage retinal lesions. Severe DR showed a recall of 85.0%, reflecting the limited training samples available for this class.

B. Comparative Analysis

Table III compares the proposed CNN model against traditional machine learning classifiers and a basic CNN baseline. The results confirm the superiority of the proposed approach across all evaluation metrics.

TABLE III. Comparative Performance Analysis

Method	Accuracy	Recall	F1-Score
SVM + Manual Features	81.2%	79.5%	80.3%
k-NN Classifier	76.8%	74.2%	75.5%
Decision Tree	73.4%	71.0%	72.2%
Basic CNN	88.6%	87.3%	87.9%
Proposed CNN	92.1%	91.4%	91.7%

The SVM with handcrafted features achieved 81.2% accuracy, while k-NN and Decision Tree classifiers recorded 76.8% and 73.4% respectively. A basic CNN without transfer learning and augmentation yielded 88.6% accuracy. The proposed CNN incorporating transfer learning, batch normalization, dropout regularization, and data augmentation achieved 92.1% accuracy, demonstrating a significant improvement of 10.9% over SVM and 3.5% over the basic CNN baseline.

C. Test Cases

Table IV presents the functional test cases used to validate the proposed system under various operational scenarios.

TABLE IV. System Test Cases

S.No	Input	If Available	If Not Available
1	Upload retinal fundus image dataset	Dataset loaded	No process
2	Generate train & test model	Model generated	No process
3	Run CNN algorithm	Accuracy displayed	No process
4	Run image preprocessing	Preprocessed image displayed	No process
5	Run deep learning model	Disease classification generated	No process
6	Accuracy comparison graph	Graph displayed	No process
7	Predict DR stage	Prediction done	No process

The system successfully processed all defined test scenarios. The model correctly classified retinal images across all five DR severity stages, generated accuracy and loss convergence graphs, and produced explainability heatmaps identifying pathological retinal regions. All functional requirements were validated through unit testing, integration testing, functional testing, and system testing methodologies.

D. Discussion

The experimental results confirm that CNN-based deep learning models significantly outperform traditional machine learning approaches for DR detection. The incorporation of transfer learning reduces training time while maintaining high classification performance. Data augmentation proved essential for improving generalization, particularly for

minority DR classes. Grad-CAM visualization confirmed that the model focused on clinically relevant retinal regions including microaneurysms, hemorrhages, and exudates, enhancing interpretability and clinical trust.

VI. CONCLUSION

This research successfully demonstrates the effectiveness of Convolutional Neural Networks for automated Diabetic Retinopathy detection and classification from retinal fundus images. The proposed deep learning framework achieves 92.1% overall classification accuracy across five DR severity stages, significantly outperforming traditional machine learning methods. The integration of transfer learning, data augmentation, batch normalization, and dropout regularization contributes to improved model generalization and robustness.

The automated system eliminates the need for manual feature engineering, reduces diagnostic time, and provides consistent objective grading. Integration with telemedicine platforms enables remote screening in resource-constrained healthcare environments, supporting early DR diagnosis and reducing blindness risk. Experimental validation confirms the clinical relevance and technical feasibility of the proposed approach.

Future work will focus on developing lightweight CNN architectures for mobile deployment, integrating multimodal data sources including OCT scans and clinical records, exploring federated learning for privacy-preserving multi-institutional training, and developing advanced explainability mechanisms to improve clinical acceptance. Continuous dataset expansion and domain adaptation techniques will further enhance cross-population performance and system reliability.

REFERENCES

[1] V. Gulshan et al., "Development and Validation of a Deep Learning Algorithm for Detection of Diabetic Retinopathy in Retinal Fundus Photographs," JAMA, vol. 316, no. 22, pp. 2402–2410, 2016.

[2] V. Gulshan, L. Peng, M. Coram et al., "Deep Learning for Detection of Diabetic Retinopathy," IEEE Trans. Medical Imaging, vol. 35, no. 5, pp. 1260–1268, 2016.

[3] A. Krizhevsky, I. Sutskever, and G. E. Hinton, "ImageNet Classification with Deep Convolutional Neural Networks," in Proc. NIPS, 2012, pp. 1097–1105.

[4] K. He, X. Zhang, S. Ren, and J. Sun, "Deep Residual Learning for Image Recognition," in Proc. IEEE CVPR, 2016, pp. 770–778.

[5] C. Szegedy et al., "Going Deeper with Convolutions," in Proc. IEEE CVPR, 2015, pp. 1–9.

[6] T. Pratt, F. Coenen, D. M. Broadbent, S. P. Harding, and Y. Zheng, "Convolutional Neural Networks for Diabetic Retinopathy," Procedia Computer Science, vol. 90, pp. 200–205, 2016.

[7] C. Lam, D. Yu, L. Huang, and D. Rubin, "Retinal Lesion Detection with Deep Learning," IEEE Trans. Biomedical Engineering, vol. 65, no. 6, pp. 1381–1388, 2018.

[8] H. Wang, Y. Yang, and Z. Zhao, "Attention-Based Deep Learning for DR Severity Grading," IEEE Access, vol. 7, pp. 89623–89634, 2019.

[9] D. S. W. Ting et al., "Development and Validation of a Deep Learning System for Diabetic Retinopathy and Related Eye Diseases," JAMA, vol. 318, no. 22, pp. 2211–2223, 2017.

[10] E. Decencière et al., "Feedback on a Publicly Distributed Database: The Messidor Database," Image Analysis & Stereology, vol. 33, no. 3, pp. 231–234, 2014.

[11] Kaggle, "Diabetic Retinopathy Detection Dataset," 2015. [Online]. Available: https://www.kaggle.com/c/diabetic-retinopathy-detection

[12] S. J. Lee et al., "Deep Learning in Ophthalmology: The Technical and Clinical Considerations," Progress in Retinal and Eye Research, vol. 72, p. 100759, 2019.

[13] R. Gargeya and T. Leng, "Automated Identification of Diabetic Retinopathy Using Deep Learning," Ophthalmology, vol. 124, no. 7, pp. 962–969, 2017.

[14] M. D. Abramoff, M. K. Garvin, and M. Sonka, "Retinal Imaging and Image Analysis," IEEE Reviews in Biomedical Engineering, vol. 3, pp. 169–208, 2010.

[15] F. Chollet, "Xception: Deep Learning with Depthwise Separable Convolutions," in Proc. IEEE CVPR, 2017, pp. 1251–1258.

[16] G. Huang, Z. Liu, L. Van Der Maaten, and K. Q. Weinberger, "Densely Connected Convolutional Networks," in Proc. IEEE CVPR, 2017, pp. 4700–4708.

[17] D. S. Kermany et al., "Identifying Medical Diagnoses and Treatable Diseases by Image-Based Deep Learning," Cell, vol. 172, no. 5, pp. 1122–1131, 2018.

[18] O. Russakovsky et al., "ImageNet Large Scale Visual Recognition Challenge," Int. J. Computer Vision, vol. 115, no. 3, pp. 211–252, 2015.

[19] World Health Organization, "Global Report on Diabetes," WHO Press, Geneva, Switzerland, 2016.

[20] American Diabetes Association, "Standards of Medical Care in Diabetes—2020," Diabetes Care, vol. 43, Suppl. 1, pp. S1–S212, 2020.

Author Profile



PG Scholar, Department of Computer Science and Engineering, Avanthi Institute of Engineering and Technology, Narsipatnam (R.D), Andhra Pradesh.
Email: sailakshmipedapudi24@gmail.com



K. VARA PRASAD, M. Tech received B. Tech degree in CSIT from JNTU Hyderabad and received the M. Tech degree in Software Engineeringfrom JNTU Kakinada. Presently working as a Assistant Professor in the department of Computer Engineering and Engineering in Avanthi Institute of Engineering & Technology, Makavarapalem, Anakapalli, AP. His Research including Data Warehousing and Data Mining, Machine Learning. He has published more than 10 papers in various national and international journals.

Email: itprasad1237@gmail.com



Dr. C. P. V. N. J. Mohan Rao is a Professor in the Department of Computer Science and Engineering at Avanthi Institute of Engineering and Technology, Visakhapatnam, Andhra Pradesh, India. He obtained his M. Tech in Computer Science and Technology from Andhra University College of Engineering and was awarded a Ph.D. by Andhra University, India, in 2000. He has 18 years of teaching and research experience and has guided numerous M. Tech. students in their projects. He has published 23 papers in national and international journals. He is guiding two research scholars for their Ph.D. He received the Best Teacher Award from Jawaharlal Nehru Technological University, Kakinada, India, in 2009.

Email: mohanrao_c@yahoo.com