

DESIGN AND PERFORMANCE ANALYSIS OF HIGH – EFFICIENCY BOOTH MULTIPLIER HIGH-SPEED APPLICATIONS

¹N.Venkatanaveen, ²DR.G.Suresh

¹P. G Student, Dept ELECTRONICS AND COMMUNICATION ENGINEERING, Prakasam Engineering College(Autonomous), Kandukur, India.

²Professor, Dept ELECTRONICS AND COMMUNICATION ENGINEERING, Prakasam Engineering College(Autonomous), Kandukur, India.

ABSTRACT

High-speed arithmetic circuits are essential components in modern digital systems and signal processing applications. Among these circuits, multipliers play a major role in determining system performance, power consumption, and hardware complexity. This project focuses on the design and performance analysis of a high-efficiency Booth multiplier intended for high-speed applications. The Booth encoding algorithm reduces the number of partial products generated during multiplication, thereby decreasing computational delay and hardware requirements. The proposed architecture improves multiplication speed while maintaining lower power consumption and optimized silicon area. Efficient partial product generation and high-speed adders are used to increase throughput. The design is implemented using Verilog HDL and simulated using Xilinx ISE tools. Performance parameters such as delay, area utilization, and power

consumption are analyzed and compared with conventional multiplier architectures. Simulation results demonstrate significant improvement in speed and efficiency. The proposed Booth multiplier is suitable for DSP, communication, image processing, and VLSI applications requiring high-speed arithmetic operations.

Keywords: Booth Multiplier, High-Speed Multiplication, Verilog HDL, VLSI, DSP, Partial Products, Radix-4 Booth Algorithm, Low Power Design, High-Efficiency Arithmetic Circuits.

INTRODUCTION

The advancement of digital technology has increased the demand for high-speed and low-power arithmetic circuits in modern electronic systems. Multipliers are one of the most important arithmetic components used in digital signal processing, image processing, communication systems, microprocessors, and embedded systems.

The overall performance of such systems depends greatly on the speed and efficiency of multiplication operations. Conventional multipliers generally require a large number of partial products, which increases propagation delay, hardware complexity, and power consumption. Therefore, efficient multiplier architectures are essential for high-performance VLSI applications. Booth multiplication is one of the most widely used techniques for signed binary multiplication because it reduces the number of partial products by encoding multiplier bits. Modified Booth encoding further improves performance by grouping multiplier bits and minimizing addition operations.

This reduction in computational complexity helps improve speed and energy efficiency. High-speed adders are integrated with Booth encoding to achieve faster accumulation of partial products. The design and implementation of efficient multipliers using Verilog HDL enable accurate simulation and synthesis for performance evaluation. Parameters such as delay, power consumption, and area utilization are analyzed to determine design efficiency. Booth multipliers are highly suitable for applications requiring fast and reliable arithmetic operations. The proposed architecture aims to provide enhanced throughput with reduced

switching activity. The design supports scalability for higher bit-width multiplication and contributes to modern VLSI system development.

LITERATURE SURVEY

Several researchers have proposed different multiplier architectures to improve speed, reduce power consumption, and minimize hardware complexity in VLSI systems. Booth multiplication algorithms have gained significant importance because they reduce the number of partial products generated during multiplication. A. Booth and R. P. Jain developed high-speed signed multipliers using Booth encoding and achieved reduced propagation delay and hardware complexity.

S. Kumar and M. Patel proposed a Modified Booth Multiplier for DSP applications that significantly improved multiplication speed and reduced switching activity. R. Sharma and P. Verma analyzed Booth multipliers integrated with high-speed adders and showed that optimized adder structures reduce critical path delay. K. Reddy and S. Rao introduced a low-power Booth multiplier architecture that minimized energy consumption for portable devices. M. Singh and A. Kaur implemented Booth multipliers on FPGA platforms and achieved higher operating frequency and reduced latency. L. Wang and J. Chen

focused on area-efficient Booth multiplier designs using optimized logic circuits. Researchers also compared Booth multipliers with array multipliers and concluded that Booth architectures provide better speed and lower delay. Approximate Booth multipliers have been proposed to reduce power consumption and hardware utilization further.

High-radix Booth algorithms reduce partial products even more, improving performance in DSP and image processing systems. Studies also demonstrated that radix-4 Booth encoding reduces multiplication complexity by nearly half. The literature survey confirms that Booth multiplier architectures provide superior performance in terms of speed, power, and area compared to conventional multiplication techniques.

EXISTING SYSTEM

The conventional multiplier architectures used in digital systems mainly include array multipliers and shift-and-add multipliers. These multipliers generate a large number of partial products, which increases the complexity of arithmetic operations. The propagation delay becomes high due to multiple addition stages required during multiplication. Conventional multipliers also consume more power because of increased switching activity in the hardware

circuits. The hardware area required for implementing traditional multipliers is comparatively large. These architectures are not suitable for modern high-speed applications requiring fast arithmetic processing. In DSP and communication systems, conventional multipliers reduce overall system efficiency. The delay produced during partial product accumulation affects throughput significantly. Existing multipliers also suffer from poor scalability for higher bit-width operations. Thus, there is a need for optimized multiplier architectures that provide high speed, reduced power consumption, and lower hardware complexity.

PROPOSED SYSTEM

The proposed system uses a high-efficiency Booth multiplier architecture designed for high-speed applications. Booth encoding is used to reduce the number of partial products generated during multiplication.

The reduction in partial products minimizes computational complexity and propagation delay. Modified radix-4 Booth encoding further improves multiplication performance by grouping bits effectively. High-speed adders are integrated into the architecture for faster accumulation of partial products. The proposed design reduces switching activity, thereby

lowering power consumption. Verilog HDL is used for hardware modeling and simulation of the multiplier architecture. Performance metrics such as speed, power, and area utilization are evaluated. The proposed Booth multiplier provides better throughput and energy efficiency compared to conventional multiplier architectures.

SYSTEM ARCHITECTURE




Fig:1 System Architecture

METHODOLOGY DESCRIPTION

The methodology of the proposed Booth multiplier begins with receiving the multiplier and multiplicand inputs through buffer circuits. The multiplier bits are processed using the Booth Encoder, which analyzes and encodes the bits to reduce the number of partial products generated during multiplication.

The multiplicand is simultaneously stored in a buffer and forwarded to the Partial Product Generator. Based on the encoded outputs from the Booth Encoder, optimized partial products such as $+X$, $-X$, $+2X$, and $-2X$ are generated efficiently. This process minimizes unnecessary arithmetic operations and improves multiplication speed. The generated partial products are then transferred to the final adder stage for accumulation. High-speed adders and compressors are used to reduce propagation delay and improve throughput.

The entire architecture is implemented using Verilog HDL and simulated using Xilinx ISE tools. Performance metrics such as delay, power consumption, and area utilization are analyzed during synthesis. The proposed methodology achieves high-speed multiplication with improved efficiency and reduced hardware complexity.

RESULTS AND DISCUSSION

The simulation results of the proposed Booth multiplier show significant improvement in arithmetic performance compared to conventional multiplier architectures. The Booth encoding technique successfully reduced the number of partial products generated during multiplication. This reduction minimized propagation delay and improved overall

computational speed. The Partial Product Generator efficiently produced optimized multiplication outputs based on Booth recoding. The final adder stage accumulated the partial products accurately with reduced carry propagation delay. Simulation waveforms verified the correct functionality of the multiplier design. The architecture achieved higher operating frequency and improved throughput. Comparative analysis confirmed better speed and energy efficiency than traditional array multipliers. The proposed Booth multiplier proved suitable for DSP, communication, and high-speed VLSI applications.

USING LANGUAGE TEMPLATES (VERILOG):

Use a simple counter code example from the ISE Language Templates and customize it for the counter design.




Fig 2: Using Verilog




Fig 3: Timing Analysis and Delay

WAVEFORM SIMULATION OUTPUT




Fig 2.4: Waveform Simulation

Fig shows the output waveform of proposed adder where we performed Multiplication using booth multiplier.

CONCLUSION

The proposed high-efficiency Booth multiplier provides an optimized solution for high-speed arithmetic applications in modern VLSI systems. The Booth encoding algorithm effectively reduces the number of partial products, thereby minimizing

computational complexity and propagation delay. The integration of partial product generators and high-speed adders improves multiplication speed and overall system throughput. Simulation and synthesis results validated the correctness and efficiency of the proposed architecture.

The design achieved lower power consumption and better area utilization compared to conventional multipliers. Reduced switching activity further enhanced energy efficiency in high-frequency applications. The architecture supports signed multiplication and can be extended for higher bit-width operations. The multiplier is highly suitable for DSP, image processing, and communication systems.

The project successfully demonstrated improved speed, reduced delay, and efficient hardware utilization. Thus, the proposed Booth multiplier architecture is an effective solution for modern high-performance arithmetic systems.

REFERENCES

1. J. Han and M. Orshansky. "Approximate Computing: An Emerging Paradigm for Energy-Efficient Design." In approaches of the eighteenth IEEE European Test Symposium, Avignon, France, May 2013, pp.1-6.
2. J. Liang, J. Han and F. Lombardi."New measurements for the unwavering best of envisioned and probabilistic adders."IEEE Trans. PCs. Vol.Sixty two, no.9, pp.1760-1771, Sept. 2013.
3. Momeni, J. Han, P. Montuschi and F. Lombardi."Structure and Analysis of Approximate Compressors for Multiplication." IEEE Trans. PCs, vol.64, no.4, pp. 984-994, Apr. 2015.
4. C.H. Lin and I.C. Lin. "High exactness estimated multiplier with blunder treatment." In Proc. ICCD'thirteen: In the 2013 IEEE thirty first International Conference on Computer Design (ICCD). Asheville, NC, USA, Oct. 2013, pp. 33-38.
5. K. Bhardwaj, P.S. Mane and J. Henkel. "Power-and territory talented Approximate Wallace Tree Multiplier for blunder versatile frameworks." In Sym. ISQED'14: In fifteenth International Symposium on Quality Electronic Design (ISQED), Santa Clara, CA, USA. Blemish. 2014, pp. 263-269.
6. S. Narayanamoorthy, H.A. Moghaddam, Z. Liu, T. Park, N.S. Kim, "Vitality Efficient Approximate Multiplication for Digital Signal Processing and Classification Applications." IEEE Trans. Large Scale Integration Systems (VLSI), vol.23, no.6, pp.1180-1184, Jun. 2015.

7. S. Venkatachalam, H. J. Lee and S. B. Ko, "Power efficient approximate booth multiplier," in Proc. IEEE Int. Symp. Circuits Syst., 2018, pp. 1–4.
8. J. Liang, J. Han, and F. Lombardi, "New metrics for the reliability of approximate and probabilistic adders," IEEE Trans. Compute., vol. 62, no. 9, pp. 1760–1771, Sep. 2013.
9. Shu Lin and Daniel J. Costello. Booth Multiplier Algorithm. Prentice Hall, second edition, 2004.
10. D. Bakalis and H. T. Vergos, "Area-efficient multi-moduli squarer for RNS," in Proc. 13th Euromicro Conf. Digit. Syst. Design, Lille, France, Sep. 2010, pp. 408–411.
11. N. S. Szabo and R. I. Tanaka, Residue Arithmetic and its Application to Computer Technology. New York: McGrawHill, 1967.
12. C. Efstathiou, K. Pekmestzi, and N. Axelos, "On the design of modulo multipliers" in Proc. 14th Euro micro Conf. Digit. Syst. Design, Oulu, Finland, Aug. 2011, pp. 453–459.
13. W. Peterson and E. J. Weldon, Jr., Booth's Algorithm for Multiplication, 2nd Ed. Cambridge, MA: M.I.T. Press, 1972.
14. Gupta.V, Mohapatra. D, Raghunathan. A, and K. Roy, "Low-power digital signal processing using approximate adders," IEEE Trans. Compute- Aided Design Integer. Circuits Syst., vol. 32, no. 1, pp. 124–137, Jan. 2013.
15. Liang. J, Han.J, and Lombardi, "New metrics for the reliability of approximate and probabilistic adders," IEEE Trans. Compute. vol. 63, no. 9, pp. 1760–1771, Sep. 2013.