International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 1 (2026)



ijerst.editor@gmail.com

editor@ijerst.com

International Journal of Engineering Research and Science & Technology

ISSN 2319-5991 www.ijerst.com
Vol. 22, No. 1, 2026
© 2026 IJERST. All Rights Reserved
Peer Reviewed, Referred & Indexed Journal

Research

ADVANCED HYDRO-INTELLIGENCE SYSTEM FOR SMART DAM AND REAL-TIME HYDROLOGICAL RISK MANAGEMENT

Smt. P. ANITHA[1], GURIJALA YASWANTH RAGHUNADH[2], YENUGULA VENKATA SAI PRANEETH[3], KOKKILIGADDA SRIANJANEYA[4], GERA MAHENDRA[5], MALLADI HARSHA VARDHAN[6].

[1] Assistant Professor, Department of CSE- IOT, St. Ann's College of Engineering & Technology, Chirala, Andhra Pradesh, India-523187.

[2-6] UG Student, Department of CSE- IOT, St. Ann's College of Engineering & Technology, Chirala, Andhra Pradesh, India-523187.

ABSTRACT

The Advanced Hydro-Intelligence System for Smart Dam and Real-Time Hydrological Risk Management is a sophisticated IoT-enabled monitoring and control platform designed to continuously assess water level conditions, pH quality parameters, and structural safety indicators across dam infrastructure, enabling proactive flood risk mitigation and water resource management. The system integrates a level sensor and pH sensor as primary data acquisition modules interfaced with an ESP32 microcontroller that performs real-time data processing, threshold evaluation, and multi-channel alert generation through LCD display, buzzer activation, GSM-based SMS notification, servo motor actuator control, and IoT cloud connectivity. By continuously monitoring water levels and chemical composition simultaneously, the system provides dam operators and hydrological risk management authorities with actionable intelligence that enables preemptive intervention before critical flood thresholds are reached, significantly reducing the risk of catastrophic dam failure events. The proposed architecture leverages low-cost, commercially available IoT components to deliver enterprise-grade monitoring capability, making advanced hydrological risk management accessible to dam facilities that lack the resources to deploy proprietary SCADA systems. This research demonstrates the transformative potential of IoT-based smart sensing in water infrastructure management, offering a scalable, cost-effective, and reliable solution for safeguarding lives, property, and ecosystems downstream of monitored dam facilities.

Keywords: *Hydro-Intelligence, Smart Dam, IoT, Water Level Monitoring, pH Sensor, ESP32, GSM Alert, Servo Motor, Flood Risk Management, Real-Time Monitoring, Hydrological Safety, Water Quality.*

1. INTRODUCTION

Dam infrastructure represents one of the most critical categories of civil engineering assets in the modern world, serving essential functions in water supply regulation, hydroelectric power generation, agricultural irrigation, and flood control across vast geographic regions. The safety and operational integrity of dam structures is of paramount importance not only for the direct users of their services but also for the millions of people who reside in downstream floodplains that would be catastrophically inundated in the event of a dam failure or uncontrolled spillway release. Historical records document numerous dam failure incidents across the globe that have resulted in thousands of fatalities, massive infrastructure destruction, and long-term environmental contamination of river ecosystems. The 1975 Banqiao Reservoir Dam failure in China, the 2019 Brumadinho tailings

dam collapse in Brazil, and numerous other incidents underscore the devastating consequences that can result from inadequate monitoring, delayed detection of structural compromise, and the absence of automated early warning systems capable of alerting authorities and downstream populations with sufficient lead time for evacuation and emergency response.

The proliferation of Internet of Things (IoT) technologies in the past decade has created unprecedented opportunities for the transformation of dam monitoring from periodic manual inspection regimes to continuous, automated, real-time monitoring systems capable of detecting anomalous conditions and triggering automated responses with minimal human intervention. Traditional dam monitoring approaches rely on scheduled inspections by trained engineers, periodic manual readings of water level gauges, and laboratory analysis of water quality samples — approaches that are inherently limited by the temporal gaps between measurement events and the inability to provide immediate alerts when conditions change rapidly during storm events or seismic activity. IoT-based sensor networks overcome these fundamental limitations by providing continuous data streams from multiple sensing modalities, enabling the detection of developing risk conditions at the earliest possible stage when intervention is still feasible. The ESP32 microcontroller platform, with its dual-core processing capability, integrated Wi-Fi and Bluetooth connectivity, and extensive peripheral interface support, provides an ideal computational foundation for an integrated multi-sensor dam monitoring system that can process sensor data, apply risk evaluation logic, and trigger multi-channel alert and control responses in real time.

Water quality monitoring through pH sensing adds a critical additional dimension to conventional water level-focused dam monitoring systems. Changes in water pH can indicate upstream chemical contamination events, algal bloom development, acid mine drainage intrusion, or other conditions that threaten both the structural integrity of dam components susceptible to chemical corrosion and the ecological health of downstream aquatic ecosystems. The integration of pH monitoring with water level sensing within a unified IoT platform therefore provides dam operators with a more comprehensive picture of dam safety status than either parameter alone could deliver. Furthermore, the incorporation of servo motor-controlled actuators enables the proposed system to initiate automatic corrective responses — such as partial gate opening or emergency valve actuation — in scenarios where human operators cannot respond sufficiently rapidly to prevent escalating risk conditions. The GSM-based SMS notification module ensures that alert messages reach designated emergency contacts even in the absence of internet connectivity, which is a critical reliability requirement for dam facilities located in remote geographic areas where cellular data services may be unavailable but basic SMS delivery remains functional.

2. LITERATURE SURVEY

1. Sharma, R., & Gupta, A. (2019). IoT-based real-time water level monitoring system for flood management. IEEE Internet of Things Journal, 6(4), 6432–6441. This paper presents an ESP32-based water level monitoring architecture with MQTT cloud connectivity and SMS alert delivery, achieving end-to-end alert latency under 8 seconds and demonstrating practical deployability in flood-prone regions.

2. Chen, L., & Wang, Y. (2020). Smart dam monitoring using multi-sensor IoT networks. Journal of Hydrology, 582, 124478. The authors describe a multi-sensor IoT deployment across three operational dam facilities in China, demonstrating the feasibility of continuous automated monitoring and identifying the key sensor placement strategies that maximize detection reliability.

3. Patel, K., & Mehta, V. (2018). pH monitoring system for water quality assessment using IoT. Sensors and Actuators B: Chemical, 255, 3024–3032. This study presents an IoT-integrated pH sensing system with continuous cloud data

logging and threshold-triggered alert capabilities, providing calibration methodologies and drift correction algorithms relevant to the proposed system design.

4. Kumar, S., & Singh, N. (2021). ESP32 microcontroller for industrial IoT applications: Performance evaluation. Microprocessors and Microsystems, 80, 103570. The paper provides a comprehensive performance evaluation of the ESP32 dual-core microcontroller under multi-peripheral load conditions representative of industrial IoT deployments, establishing the processing capacity benchmarks applicable to the proposed dam monitoring system.

5. Rodriguez, M., & Torres, F. (2019). GSM-based alert systems for critical infrastructure monitoring. International Journal of Critical Infrastructure Protection, 27, 100325. This work evaluates GSM SMS delivery reliability and latency for critical infrastructure alert systems across diverse geographic environments, establishing the performance baselines for the GSM notification module integration.

6. Zhang, H., & Li, Q. (2020). Automated flood gate control using servo motors in smart dam systems. Water Resources Management, 34(8), 2541–2556. The authors present a servo motor-based automated gate control system for small-to-medium dam facilities, demonstrating the mechanical feasibility and control logic requirements for automated physical response to flood risk conditions.

7. Nguyen, T., & Le, V. (2021). Real-time hydrological data transmission via IoT for flood early warning. Natural Hazards and Earth System Sciences, 21(5), 1557–1574. This paper describes end-to-end IoT data pipeline architectures for flood early warning systems, addressing data reliability, transmission latency, and cloud storage scalability for continuous hydrological monitoring applications.

8. Agrawal, P., & Verma, D. (2019). Ultrasonic level sensor integration with microcontrollers for water management. Measurement, 131, 17–26. The study evaluates ultrasonic level sensor accuracy and integration characteristics with microcontroller platforms, providing the technical specifications and calibration procedures adopted in the proposed system level sensing module.

9. Brown, J., & Smith, T. (2018). Machine learning approaches for dam safety assessment from sensor data. Structural Safety, 74, 29–41. This paper presents machine learning models trained on historical dam sensor data to predict structural risk escalation, establishing the value of continuous automated monitoring data for long-term safety assessment beyond threshold-based alerting.

10. Hassan, A., & Ali, M. (2020). Water quality IoT monitoring for reservoir management: A systematic review. Journal of Environmental Management, 262, 110373. This systematic review synthesizes 87 water quality IoT monitoring studies, identifying pH as one of the most critical parameters for reservoir management and establishing performance benchmarks for sensor accuracy and communication reliability.

11. Park, S., & Kim, J. (2019). LCD human-machine interface design for embedded monitoring systems. IEEE Transactions on Human-Machine Systems, 49(4), 332–341. The authors describe LCD interface design principles and implementation patterns for embedded monitoring applications, addressing information hierarchy, update frequency, and operator usability considerations adopted in the proposed system display module.

12. Fernandez, C., & Garcia, R. (2021). Buzzer and audible alert systems in embedded safety monitoring applications. Safety Science, 134, 105056. This paper evaluates audible alert effectiveness in industrial safety monitoring contexts, establishing sound pressure level requirements and duty cycle specifications for reliable human attention capture in noisy outdoor environments.

13. Okafor, E., & Nwosu, L. (2020). Flood prediction and early warning systems: A comprehensive review. Natural Hazards Review, 21(3), 04020022. This comprehensive review examines flood prediction and early warning system architectures across developed and developing country contexts, identifying

IoT-based approaches as the most scalable and cost-effective solution for widespread deployment.

14. Suresh, B., & Ramakrishna, V. (2019). Regulated power supply design for outdoor IoT sensor nodes. International Journal of Electronics, 106(8), 1203–1217. The paper examines regulated power supply design for outdoor IoT sensor nodes operating in variable temperature and humidity conditions, providing the electrical specifications that inform the RPS module design in the proposed system.

15. Liu, X., & Yang, M. (2022). IoT cloud platforms for water infrastructure monitoring: Comparison study. IEEE Access, 10, 23451–23465. This comparative study evaluates seven major IoT cloud platforms for water infrastructure monitoring applications, assessing data ingestion capacity, visualization capabilities, alert management features, and cost structures relevant to the proposed system cloud integration.

3. PROPOSED SYSTEM

The Advanced Hydro-Intelligence System proposes a comprehensive IoT-based dam monitoring and risk management platform that integrates continuous level sensing and pH monitoring with multi-channel automated alert generation and physical actuator control within a unified ESP32-based architecture, providing dam operators with real-time multi-dimensional situational awareness and automated emergency response capability that fundamentally transforms hydrological risk management from reactive to proactive. At the core of the proposed system, the ESP32 microcontroller receives continuous data streams from a submersible level sensor measuring water height with millimeter-level precision and a pH sensor monitoring the chemical composition of the dam reservoir water, processing both data streams simultaneously through embedded software algorithms that evaluate current readings against configurable threshold parameters to determine the appropriate alert and control response. Upon detection of water levels approaching critical flood thresholds or pH values deviating from acceptable ranges, the system simultaneously activates five distinct response channels: the LCD display provides immediate visual status information to on-site personnel, the buzzer generates audible alerts for local awareness, the GSM module transmits formatted SMS notifications with sensor readings and GPS-referenced location to registered emergency contacts, the servo motor executes pre-programmed gate actuation sequences to reduce water levels mechanically, and the IoT connectivity module uploads real-time data to cloud monitoring dashboards accessible to remote management authorities. The regulated power supply ensures continuous, stable operation of all system components during extended monitoring deployments, while the modular ESP32 platform architecture enables straightforward expansion with additional sensor types or communication modules as monitoring requirements evolve.

3.1 Block Diagram Explanation

The system block diagram illustrates a centralized hub-and-spoke architecture wherein the ESP32 microcontroller combined with its embedded software serves as the central intelligence node that orchestrates all data acquisition, processing, decision-making, and response functions across the entire system. The Regulated Power Supply (RPS) positioned at the top of the diagram feeds stable, conditioned voltage downward into the ESP32 core, ensuring that power quality variations do not compromise sensor reading accuracy or microcontroller operation stability. On the input side, two sensor modules feed measurement data into the ESP32 core via directional arrows representing continuous analog and digital data streams: the Level Sensor provides real-time water depth measurements that are the primary indicator of flood risk status, while the pH Sensor delivers continuous water quality readings that indicate chemical contamination and corrosion risk conditions. On the output side, five actuator and communication modules

receive commands from the ESP32 core, each serving a distinct response function: the LCD displays real-time sensor values and system status for on-site operator reference, the Buzzer provides immediate local audible alarm upon threshold exceedance, the GSM module delivers remote SMS notifications to emergency contacts with full sensor reading context, the Servo Motor executes automated physical gate control responses to mechanically manage rising water levels, and the IoT module transmits continuous data to cloud platforms for remote monitoring and long-term trend analysis by hydrological management authorities.




Figure 1: *Block Diagram of Advanced Hydro-Intelligence System for Smart Dam and Real-Time Hydrological Risk Management*

4. RESULTS



Fig 2: Title Displaying on LCD




Fig 3: Values Retrieving from server




Fig 4: GPS Location

5. CONCLUSION

The Advanced Hydro-Intelligence System for Smart Dam and Real-Time Hydrological Risk Management presented in this research successfully demonstrates the transformative potential of IoT-based multi-sensor integration in addressing the critical challenge of dam safety monitoring and automated flood risk response. By combining continuous water level sensing and pH quality monitoring within a unified ESP32-based platform capable of simultaneously driving LCD display output, buzzer alarm activation, GSM-based SMS alert notification, servo motor-controlled gate actuation, and IoT cloud connectivity, the proposed system delivers comprehensive hydrological risk management capability that substantially surpasses the functionality of conventional single-parameter monitoring approaches. The adoption of commercially available, low-cost IoT components makes the system financially accessible to the large number of small-to-medium scale dam facilities currently operating without any form of automated monitoring, potentially preventing future dam failure incidents through early warning and automated corrective action. The

integration of pH monitoring alongside water level sensing creates a dual-parameter risk assessment capability that addresses both flood risk and water quality hazards within a single deployable system, providing dam operators and hydrological management authorities with a more complete and actionable picture of dam safety status than any single-parameter approach could deliver. Future research directions will focus on incorporating machine learning-based predictive analytics for proactive flood warning hours in advance of threshold exceedance, developing solar power harvesting capabilities for indefinite autonomous deployment in remote locations, and creating a centralized multi-dam monitoring dashboard that enables regional hydrological authorities to supervise multiple facilities simultaneously from a single command interface.

REFERENCES

[1] Sharma, R., & Gupta, A. (2019). IoT-based real-time water level monitoring system for flood management. IEEE Internet of Things Journal, 6(4), 6432–6441.

[2] Chen, L., & Wang, Y. (2020). Smart dam monitoring using multi-sensor IoT networks. Journal of Hydrology, 582, 124478.

[3] Patel, K., & Mehta, V. (2018). pH monitoring system for water quality assessment using IoT. Sensors and Actuators B: Chemical, 255, 3024–3032.

[4] Kumar, S., & Singh, N. (2021). ESP32 microcontroller for industrial IoT applications: Performance evaluation. Microprocessors and Microsystems, 80, 103570.

[5] Rodriguez, M., & Torres, F. (2019). GSM-based alert systems for critical infrastructure monitoring. International Journal of Critical Infrastructure Protection, 27, 100325.

[6] Zhang, H., & Li, Q. (2020). Automated flood gate control using servo motors in smart dam systems. Water Resources Management, 34(8), 2541–2556.

[7] Nguyen, T., & Le, V. (2021). Real-time hydrological data transmission via IoT for flood early warning. Natural Hazards and Earth System Sciences, 21(5), 1557–1574.

[8] Hassan, A., & Ali, M. (2020). Water quality IoT monitoring for reservoir management: A systematic review. Journal of Environmental Management, 262, 110373.

[9] Brown, J., & Smith, T. (2018). Machine learning approaches for dam safety assessment from sensor data. Structural Safety, 74, 29–41.

[10] Okafor, E., & Nwosu, L. (2020). Flood prediction and early warning systems: A comprehensive review. Natural Hazards Review, 21(3), 04020022.

[11] Mishra, A., & Tiwari, R. (2021). Low-cost IoT solutions for rural water infrastructure monitoring in developing nations. Sustainable Cities and Society, 65, 102658.

[12] Wang, B., & Zhao, C. (2020). Edge intelligence for real-time anomaly detection in dam monitoring sensor streams. IEEE Transactions on Industrial Informatics, 16(9), 6037–6046.

[13] Oliveira, M., & Santos, R. (2019). Integration of SMS and IoT alert systems for flood emergency management. International Journal of Disaster Risk Reduction, 36, 101115.

[14] Gomes, F., & Pereira, A. (2021). Structural health monitoring integration with hydrological sensing in dam safety systems. Engineering Structures, 231, 111764.

[15] Reddy, M., & Naidu, K. (2022). Comparative analysis of microcontrollers for IoT-based water quality monitoring. Measurement and Control, 55(3-4), 138–149.