



International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 4 (2026)



ijerst.editor@gmail.com
editor@ijerst.com

Research Paper

Aqua mangrove Tetrapod-2

Prof. Sakshi Sanjay Dhongade

Dwip Ganesh Nawale

Sparsh Rahul Bende

Suyog Lahane

Gokul Devanand Bhore

Sayali Ravindra Sambre

DRGITR (Poly), Amravati, Maharashtra , India

Abstract: Coastal erosion and land degradation are increasingly critical challenges caused by rising sea levels and intense ocean wave dynamics. While conventional concrete tetrapods offer immediate structural defense by dissipating wave energy, their reliance on heavy Ordinary Portland Cement (OPC) and steel reinforcement causes severe ecological damage, marine toxicity, and carbon emissions. Conversely, natural mangrove bio-shields provide excellent long-term shoreline protection, but young saplings frequently experience high mortality on open coasts due to wave shear forces and soil washout. To bridge this gap between hard infrastructure and ecological restoration, this project introduces the Aqua-Mangrove Tetrapod—a hybrid, bio-engineered three-legged structural unit. Designed with a low-cement bio-concrete shell and reinforced with non-corrosive bamboo, the structure features an upper planting cavity filled with cocopeat briquettes and internal water-passage chambers. This configuration acts as a temporary incubator that breaks high-energy waves while sheltering young mangrove saplings during early root growth. As the mangrove root system expands through the internal channels and anchors firmly into the sea sand, the bio-matrix naturally decomposes over approximately 10 years, leaving a fully established, self-sustaining mangrove forest in its place. The proposed system effectively reduces wave impact, eliminates toxic metal corrosion, restores marine biodiversity, and provides a sustainable, blue-carbon alternative for modern coastal engineering.

Keywords: Bio-engineered tetrapod, Coastal protection, Wave attenuation, Mangrove restoration, Bamboo reinforcement, Low-carbon concrete, Blue carbon.

Sustainability of Tetrapods

Although tetrapods can provide effective coastal protection, they are not environmentally neutral.

Concrete production requires significant energy and raw materials. A 2025 life-cycle assessment of tetrapod armour units examined production, transportation and placement and found that cast production was the dominant contributor to the assessed environmental impacts. The study particularly highlighted the importance of concrete and steel-related production impacts

Consequently, the proposed hybrid system should follow the principle:

Use engineered protection where it is necessary, while maximizing natural protection where ecological conditions allow.

Potential strategies for reducing environmental impact include:

- Optimizing tetrapod size and quantity.
- Using locally sourced aggregates where appropriate.
- Investigating lower-carbon concrete mixtures.
- Minimizing transportation distances.
- Designing structures for long service life.
- Reusing suitable materials where technically feasible.
- Avoiding unnecessary construction within mangrove habitats.

Design Methodology

A site-specific design should follow a multidisciplinary process.

Step 1: Site investigation

Collect:

Functional arrangement

Zone 1 – Offshore/outer armour zone

A rubble-mound breakwater or submerged/low-crested structure is protected with tetrapod armour units.

Zone 2 – Transition zone

Zone 3 – Mangrove restoration zone

Existing mangroves are conserved and degraded areas are restored using appropriate native species.

Working Principle

systems can support fisheries and aquaculture while encouraging communities to maintain designed breakwater can alter tidal exchange, sediment transport and mangrove dominant contributor to the assessed environmental impacts. The study particularly highlighted the importance of concrete and steel-related production impacts. Tetrapod size should be selected according to the design wave conditions, water depth, slope, placement arrangement and hydraulic stability alone is insufficient; armour units must also have adequate include mud crabs and selected shrimp species, subject to local regulations and environmental suitability. SEAFDEC documentation. Research has specifically identified breakage as a potential failure mechanism for slender. Damaged tetrapods may need replacement, while mangrove areas require protection from cutting, pollution and resistance and are particularly useful where wave forces are too large to be managed by vegetation alone. Their interlocking geometry and rough surface can dissipate wave energy effectively. However, their production has an environmental footprint, particularly because of concrete and associated as living infrastructure, providing habitat, sediment stabilization, carbon storage and livelihood opportunities should focus on developing quantitative design procedures specifically for hybrid mangrove– that encourage marine defence. The approach uses tetrapod armour to provide resistance against severe wave attack while Advantages of the Integrated Approach

Improved coastal resilience

Step 1:

- Bathymetric data.
- Topographic data.
- Tidal levels.

- Wave characteristics.
- Current velocity.
- Sediment characteristics.
- Shoreline-change data.
- Existing mangrove distribution.
- Aquaculture conditions.
- Ground conditions.

Step 2. These parameters are then used in hydraulic stability calculations and/or physical modelling.

Step 3: Tetrapod design

Tetrapod size should be selected according to the design wave conditions, water depth, slope, placement arrangement and accepted coastal-engineering design procedures.

The design should also consider structural breakage. Previous research has demonstrated that hydraulic stability alone is insufficient; armour units must also have adequate structural strength.

Step 4: Mangrove assessment

Identify existing mangrove species and determine:

Design Methodology

A site-specific design should follow a multidisciplinary process.

Step 1: Site investigation

Collect:

- Bathymetric data.
- Topographic data.
- Tidal levels.
- Wave characteristics.
- Current velocity.
- Sediment characteristics.
- Shoreline-change data.
- Existing mangrove distribution.
- Aquaculture conditions.
- Ground conditions.
- Vegetation density.
- Stem diameter.
- Height.
- Root characteristics.
- Age structure.
- Natural regeneration.
- Sediment elevation.
- Salinity.
- Tidal inundation.

Step 5: Aqua-mangrove planning

Aquaculture areas should be located and designed so that mangrove vegetation remains functional.

Potential cultured organisms include mud crabs and selected shrimp species, subject to local regulations and environmental suitability. SEAFDEC documentation specifically discusses *Scylla serrata*, *Scylla tranquebarica* and *Scylla olivacea* in aqua-mangrove systems.

Step 6: Numerical and physical modelling

Hydrodynamic modelling should be used to investigate:

Step 6: Numerical and physical modelling

- Wave transmission.
- Wave reflection.
- Overtopping.
- Current patterns.
- Sediment transport.
- Mangrove inundation.
- Tetrapod stability.

Future Research

Further research should focus on developing quantitative design procedures specifically for hybrid mangrove–tetrapod systems.

Recommended research areas include:

1. Laboratory wave-flume experiments comparing bare tetrapod structures with tetrapod–mangrove combinations.
2. Numerical modelling of wave attenuation through mangrove vegetation behind tetrapod armour.
3. Long-term monitoring of sediment accumulation.
4. Life-cycle assessment comparing tetrapod structures with conventional seawalls and nature-based alternatives.
5. Low-carbon concrete for armour-unit production.
6. Development of ecological designs that encourage marine organisms to colonize armour structures.
7. Economic analysis of construction, maintenance and ecosystem-service benefits.
8. Investigation of performance during cyclones and extreme storm events.
9. Development of India-specific design guidelines for hybrid coastal protection.
10. Community-based monitoring and management of aqua-mangrove systems.

Conclusion

The Aqua-Mangrove–Tetrapod Integrated Coastal Protection System provides a conceptual framework for combining engineered and nature-based coastal defence. The approach uses tetrapod armour to provide resistance against severe wave attack while retaining or restoring mangrove ecosystems behind the structure.

Aqua-mangrove farming demonstrates that mangrove conservation can be integrated with productive aquaculture and community livelihood development. Repository Tetrapods, meanwhile, provide an established form of concrete armour for breakwaters and can contribute substantially to wave-energy dissipation.

The principal advantage of the hybrid approach is that it does not rely exclusively on either concrete infrastructure or natural vegetation. Instead, it combines the immediate protective capacity of engineered structures with the long-term ecological functions of mangroves.

However, the system must be designed according to local hydrodynamic, geomorphological and ecological conditions. Particular attention should be given to tetrapod stability, structural breakage, sediment transport, tidal exchange, mangrove health and the environmental footprint of concrete production.

Overall, the concept has potential as a sustainable coastal-management strategy for tropical and subtropical coastlines, particularly where communities require both coastal protection and livelihood opportunities. Future laboratory experiments, numerical modelling and field-scale demonstrations are necessary before standardized design guidelines can be established.

References

1. Triño, A. T. (2000). *Aqua-mangrove integrated farming: Shrimp and mud crab culture in coastal and inland tidal flats with existing reforested or natural growth of mangroves*. In Technologies in Mangrove-Friendly Aquaculture, pp. 157–188. Southeast Asian Fisheries Development Center, Aquaculture Department.
2. Mikhail, E., Younes, N., Al Adab, M. A., Tarnini, A. B., Atabay, S. A., & Mortula, M. M. (2025). Life cycle assessment of tetrapod concrete armour units. *Frontiers in Sustainable Cities*, 7, 1592987. <https://doi.org/10.3389/frsc.2025.1592987>.
3. Burcharth, H. F., Jensen, J. B., Liu, Z., van der Meer, J. W., & d'Angremond, K. *Design Formula for Breakage of Tetrapods*. Aalborg University. Aalborg Universitets forskningsportal
4. Burcharth, H. F., & others. *Empirical formula for breakage of Dolosse and Tetrapods*. *Coastal Engineering*, 40(3), 183–206, 2000.
5. Sayao, O. J., & da Silva, R. F. (2018). Physical modelling of breakwater roundheads armoured with tetrapods. *Coasts, Marine Structures and Breakwaters*.
6. Roy, S. D., & Trivedi, S. (2023). Geospatial assessment of long-term changes (1937–2019) in mangrove vegetation and shoreline dynamics of Godavari Estuary, East Coast of India. *Journal of the Indian Society of Remote Sensing*, 51, 1309–1327.
7. Kudale, A. M., Kudale, M. D., & Kulkarni, P. B. (2021). Performance of concrete armour units of breakwaters in India – A review. *International Journal of Civil Engineering and Technology*, 12(6).