



International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 4 (2026)



ijerst.editor@gmail.com
editor@ijerst.com

Research Paper**SEISMIC RESPONSE OF ELEVATED WATER TANK-2**

Prof. G. G. Meshram

Om bhiwagade,

Syed Arman Malik

Mohammad Talha

Partik Gawhale

Om Raut

DRGITR (Poly), Amravati, Maharashtra , India

ABSTRACT Elevated water tanks are important components of water supply systems, particularly in areas where reliable water storage and distribution are required. Due to their considerable height, mass distribution, and supporting structure, elevated water tanks are vulnerable to lateral forces generated during earthquakes. The movement of water inside the tank can produce a sloshing effect, which increases the dynamic load and may affect the stability of the supporting structure. Therefore, understanding the seismic behaviour of elevated water tanks is essential for improving their safety and structural performance. This project presents a physical model of an elevated water tank to study its response under simulated earthquake loading. The model consists of a water tank supported on a structural frame with X-bracing, mounted on a manually or motor-operated shake table. The model is subjected to controlled lateral movement to simulate earthquake forces. The water inside the tank demonstrates the sloshing effect and its influence on the movement and stability of the structure. Different structural conditions, particularly with and without bracing, can be observed and compared. The study focuses on parameters such as lateral movement, tank tilting, structural stability, and the effectiveness of bracing and base isolation in reducing earthquake-induced movement. The observations indicate that a properly braced supporting frame provides greater resistance to lateral forces and reduces excessive movement and tilting of the tank. Rubber pads used as an optional base-isolation arrangement can further help in reducing the transmission of vibrations to the structure. The project provides a simple and practical demonstration of the principles of earthquake-resistant design of elevated water tanks. It helps in understanding the interaction between structural response and water sloshing during seismic loading and highlights the importance of adequate bracing, stable foundations, and suitable structural design for safer water storage systems in earthquake-prone areas.

Keywords: Elevated Water Tank, Earthquake Loading, Seismic Response, Water Sloshing, Lateral Forces, Structural Stability, X-Bracing, Base Isolation, Earthquake-Resistant Design, Seismic Safety.

Fluid-Structure Interaction

Fluid-structure interaction (FSI) is one of the most important aspects of seismic analysis of water tanks.

A detailed FSI model can account for:

- Fluid pressure
- Structural deformation
- Free-surface movement
- Hydrodynamic pressure

- Tank-wall flexibility
- Interaction between fluid and structure

Numerical Modeling Methodology

A numerical study may be conducted using structural-analysis software such as ETABS, SAP2000, STAAD.Pro, or another finite-element platform.

The following procedure is recommended.

Step 1: Define Tank Geometry

The following parameters are required:

- Tank capacity
- Tank diameter/width
- Water depth
- Tank wall thickness
- Roof geometry
- Bottom slab thickness
- Staging height
- Column dimensions
- Bracing dimensions

Step 2: Define Material Properties

Typical parameters include:

- Concrete grade
- Reinforcement grade
- Young's modulus
- Poisson's ratio
- Unit weight
- Damping ratio

Step 3: Model the Staging

The columns and braces are modeled using frame elements.

The tank container can be modeled using shell elements where detailed structural behaviour is required.

Step 4: Define Water Mass

The water should not simply be treated as a single rigid lumped mass for a detailed seismic study.

The impulsive and convective components should be represented separately according to IS 1893 (Part 2).

Step 5: Modal Analysis

Modal analysis is performed to obtain:

- Natural frequencies
- Natural periods
- Mode shapes
- Modal participating mass

Step 6: Response Spectrum Analysis

A response-spectrum analysis can be conducted using the applicable design spectrum.

Separate impulsive and convective responses should be considered.

Step 7: Load Combinations

The seismic load should be combined with appropriate gravity and other applicable load cases.

Step 8: Evaluate Structural Response

The following response quantities should be extracted:

- Base shear

- Overturning moment
- Storey/staging displacement
- Column axial force
- Column bending moment
- Bracing force
- Tank-wall stresses
- Foundation reactions

Conclusions

The seismic response of elevated water tanks is a complex structural problem involving interaction between the tank container, supporting staging, foundation, and stored liquid. The elevated position of the water mass results in significant inertia and overturning effects during earthquakes.

The study establishes that the seismic analysis of an elevated water tank should not treat the stored water merely as a rigid static load. The liquid should be represented using impulsive and convective components in accordance with the applicable seismic provisions.

The following conclusions are drawn:

1. Two-mass idealization is essential for realistic code-based seismic analysis of elevated water tanks.
2. Impulsive liquid mass significantly contributes to seismic base shear and overturning moment.
3. Convective liquid mass governs important sloshing-related effects and must be considered for adequate freeboard.
4. Staging stiffness strongly influences the natural period and lateral displacement of the tank.
5. Increasing staging height generally makes the system more flexible and may increase seismic displacement demands.
6. Bracing systems can significantly improve lateral stiffness and seismic performance when appropriately designed.
7. Tank filling level should be investigated because both inertial and sloshing characteristics depend on the amount of stored water.
8. Fluid–structure interaction becomes increasingly important for detailed and research-level analyses.
9. Overturning moment and foundation response must be checked carefully because the elevated liquid mass generates substantial lateral eccentric effects.
10. Ductile detailing and appropriate structural configuration are essential for preventing sudden collapse during severe earthquakes.

Overall, a safe elevated water tank requires an integrated approach involving seismic analysis, structural design, hydrodynamic considerations, ductile detailing, and appropriate foundation design.

Scope for Future Research

Future studies may focus on:

- Nonlinear time-history analysis of elevated water tanks.
- Computational fluid dynamics (CFD) modeling of sloshing.
- Coupled fluid–structure interaction analysis.
- Performance-based seismic design.
- Soil–structure interaction.
- Effect of tank-wall flexibility.
- Comparison of RCC and steel staging.
- Optimization of staging geometry.

- Seismic response under near-fault ground motions.
- Effects of vertical earthquake excitation.
- Seismic fragility assessment.
- Experimental shake-table testing.
- Development of machine-learning models for predicting seismic response.
- Evaluation of existing aging elevated water tanks and seismic retrofitting techniques.

References

1. Bureau of Indian Standards, IS 1893 (Part 2): 2014, Criteria for Earthquake Resistant Design of Structures – Part 2: Liquid Retaining Tanks, Fifth Revision, New Delhi.
2. Bureau of Indian Standards, Amendment No. 1 to IS 1893 (Part 2): 2014, March 2022. The amendment includes changes to the spring-mass-model provisions for circular and rectangular tanks.
3. Bureau of Indian Standards, IS 1893 (Part 1), Criteria for Earthquake Resistant Design of Structures – General Provisions and Buildings.
4. Bureau of Indian Standards, IS 456:2000, Plain and Reinforced Concrete – Code of Practice.
5. Bureau of Indian Standards, IS 3370, Concrete Structures for the Storage of Liquids.
6. Bureau of Indian Standards, IS 11682:1985, Criteria for Design of RCC Staging for Overhead Water Tanks.
7. Bureau of Indian Standards, IS 13920, Ductile Design and Detailing of Reinforced Concrete Structures Subjected to Seismic Forces.
8. IITK-GSDMA, Guidelines for Seismic Design of Liquid Storage Tanks, Indian Institute of Technology Kanpur. The guidelines employ the two-mass representation for elevated tanks and provide parameters for impulsive and convective components.
9. Housner, G. W., *The Dynamic Behavior of Water Tanks*, Bulletin of the Seismological Society of America.
10. Seismic Response of Liquid-Filled Elevated Tanks, *Engineering Structures*, Volume 33, Issue 6, 2011, pp. 2074–2084. The study examines finite-element, modal, and time-history approaches and considers impulsive, convective, wall-flexibility, and sloshing effects.
11. Seismic Assessment of Different Vertical Bracing Systems in Staging of Elevated Liquid Retaining Tank, *Materials Today: Proceedings*, 2023. The study compares different staging-bracing configurations using seismic response-spectrum analysis.