



International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 4 (2026)



ijerst.editor@gmail.com
editor@ijerst.com

Research Paper

Aqua mangrove Tetrapod-1

Prof. Sakshi Sanjay Dhongade

Dwip Ganesh Nawale

Sparsh Rahul Bende

Suyog Lahane

Gokul Devanand Bhore

Sayali Ravindra Sambre

DRGITR (Poly), Amravati, Maharashtra, India

Abstract: Coastal erosion and land degradation are increasingly critical challenges caused by rising sea levels and intense ocean wave dynamics. While conventional concrete tetrapods offer immediate structural defense by dissipating wave energy, their reliance on heavy Ordinary Portland Cement (OPC) and steel reinforcement causes severe ecological damage, marine toxicity, and carbon emissions. Conversely, natural mangrove bio-shields provide excellent long-term shoreline protection, but young saplings frequently experience high mortality on open coasts due to wave shear forces and soil washout. To bridge this gap between hard infrastructure and ecological restoration, this project introduces the Aqua-Mangrove Tetrapod—a hybrid, bio-engineered three-legged structural unit. Designed with a low-cement bio-concrete shell and reinforced with non-corrosive bamboo, the structure features an upper planting cavity filled with cocopeat briquettes and internal water-passage chambers. This configuration acts as a temporary incubator that breaks high-energy waves while sheltering young mangrove saplings during early root growth. As the mangrove root system expands through the internal channels and anchors firmly into the sea sand, the bio-matrix naturally decomposes over approximately 10 years, leaving a fully established, self-sustaining mangrove forest in its place. The proposed system effectively reduces wave impact, eliminates toxic metal corrosion, restores marine biodiversity, and provides a sustainable, blue-carbon alternative for modern coastal engineering.

Keywords: Bio-engineered tetrapod, Coastal protection, Wave attenuation, Mangrove restoration, Bamboo reinforcement, Low-carbon concrete, Blue carbon.

1. Introduction

Coastal zones are among the most productive and densely populated environments in the world. They support fisheries, aquaculture, tourism, ports, settlements, agriculture, and important ecological habitats. However, these areas are increasingly threatened by shoreline erosion, coastal flooding, cyclones, storm surges and changing sea levels.

Mangrove forests form one of the most important natural coastal-defence ecosystems. Their roots increase sediment retention and their stems and branches create resistance to water movement. Mangroves also provide nursery habitat for fish and crustaceans and support the livelihoods of coastal communities.

At the same time, engineered structures remain necessary where high levels of protection are required. Rubble-mound breakwaters commonly use large rock or artificial concrete armour units. Tetrapods are one of the most established forms of artificial concrete armour. They were developed in France during the 1950s and are designed to provide interlocking, roughness and void spaces that contribute to wave-energy dissipation. Frontiers+1

The challenge is therefore not simply to choose between natural and engineered coastal protection. A more sustainable strategy may be to combine the two. The proposed Aqua-Mangrove–Tetrapod system uses mangroves as a biological and ecological defence while employing tetrapod armour where greater immediate hydraulic resistance is necessary.

2. Aqua-Mangrove System

2.1 Concept

Aqua-mangrove integrated farming, also known as mangrove–aquaculture integration or aqua-silviculture, combines aquaculture production with the conservation of mangrove vegetation.

SEAFDEC describes aqua-mangrove farming as an approach in which aquaculture can be developed around existing, reforested or naturally growing mangroves while maintaining much of the ecological integrity of the mangrove area. The approach has been applied to shrimp and mud-crab culture and incorporates community participation and co-management. SEAFDEC Repository+1

The fundamental principle is:

Mangrove conservation + aquaculture production + community livelihood
rather than clearing mangroves to create conventional aquaculture ponds.

2.2 Ecological functions

Mangrove vegetation can contribute to:

- Reduction of wave and current energy.
- Sediment trapping and shoreline stabilization.
- Provision of fish and crustacean habitat.
- Improvement of coastal biodiversity.
- Carbon storage.
- Nutrient cycling.
- Support for fisheries and local livelihoods.

Research on Indian mangrove systems has also demonstrated the importance of mangroves for shoreline stabilization and coastal protection. Long-term analysis of the Godavari estuary, for example, identified mangroves as an important component of coastal protection while documenting substantial land-use conversion associated with aquaculture development. Springer

3. Tetrapod Coastal-Protection Technology

3.1 Definition

A tetrapod is a four-legged, irregularly shaped concrete armour unit used primarily in rubble-mound breakwaters and coastal protection structures.

The unusual geometry allows adjacent units to interlock and creates a rough, porous armour layer. The resulting structure dissipates part of the incoming wave energy rather than reflecting all of it.

Recent literature describes tetrapods as one of the earliest irregularly shaped concrete armour units, developed in France in the 1950s. When arranged appropriately, tetrapods create substantial void space and a rough surface that contributes to wave-energy dissipation. Frontiers

3.2 Function in breakwaters

A typical rubble-mound breakwater contains:

1. Core material.
2. Filter or underlayer.
3. Primary armour layer.
4. Crest and toe protection.

Tetrapods are generally used as the primary armour layer.

Their function is to resist displacement under wave attack while dissipating wave energy through turbulence, friction, interlocking and wave breaking.

3.3 Hydraulic stability

Tetrapod performance depends on several parameters, including:

- Significant wave height.
- Wave period.
- Water depth.
- Armour-unit weight.
- Concrete density.
- Breakwater slope.
- Placement pattern.
- Number of armour layers.
- Toe configuration.
- Wave direction.
- Construction quality.

Research on concrete armour units in India emphasizes that armour stability is influenced not only by unit weight but also by shape, interlocking, slope, packing density, placement method, wave characteristics and toe protection. Scribd

Tetrapods also have a known structural limitation: their slender geometry can make them susceptible to breakage under static, pulsating and impact loads. Research has therefore examined the relationship between hydraulic stability and structural strength Universitets forskningsportal+1

4. Proposed Aqua-Mangrove–Tetrapod System

The proposed system combines hard engineering and nature-based coastal protection.

A conceptual cross-section can be represented as:

Sea → Tetrapod armour → Rubble/filter layer → Intertidal zone → Mangrove belt → Aqua-mangrove pond/channel → Protected land

The tetrapod zone acts as the first line of defence against severe wave attack. Behind it, the mangrove zone provides additional wave attenuation, sediment retention and ecological functions.

4.1 Functional arrangement

The proposed system may consist of five zones:

Zone 1 – Offshore/outer armour zone

A rubble-mound breakwater or submerged/low-crested structure is protected with tetrapod armour units.

Zone 2 – Transition zone

A graded rock or filter layer connects the engineered structure with the intertidal environment.

Zone 3 – Mangrove restoration zone

Existing mangroves are conserved and degraded areas are restored using appropriate native species.

Zone 4 – Aqua-mangrove production zone

Where environmentally appropriate, controlled aquaculture of species such as mud crab or shrimp can be integrated without unnecessary mangrove clearing.

Zone 5 – Community and terrestrial protection zone

The landward area can include settlements, agricultural land, roads, fisheries infrastructure or other assets requiring protection.

5. Working Principle

The hybrid system operates through multiple mechanisms.

5.1 Wave-energy reduction by tetrapods

Incoming waves encounter the rough and porous tetrapod armour layer. The irregular geometry causes turbulence and interaction between the wave and armour units, reducing the energy transmitted toward the landward side.

5.2 Wave attenuation by mangroves

The remaining wave energy encounters mangrove stems, branches and roots. Vegetation increases hydraulic resistance and promotes energy dissipation.

5.3 Sediment trapping

Mangrove roots and low-flow conditions can promote sediment deposition. Over time, this may assist in maintaining or increasing the elevation of the intertidal platform, although the response depends strongly on sediment supply, tidal regime and local geomorphology.

5.4 Ecological buffering

Unlike a conventional concrete seawall, the mangrove component creates habitat and supports ecological processes.

5.5 Livelihood generation

An appropriately designed aqua-mangrove system can provide opportunities for sustainable aquaculture and local employment. SEAFDEC's aqua-mangrove model specifically identifies livelihood development and community co-management as important components.

6. Advantages of the Integrated Approach

6.1 Improved coastal resilience

Combining structural and biological protection can provide redundancy. If mangrove vegetation alone cannot withstand an extreme event, the tetrapod structure provides additional protection.

6.2 Ecosystem benefits

The mangrove component provides ecological services that conventional concrete structures do not normally provide.

6.3 Livelihood opportunities

Aqua-mangrove systems can support fisheries and aquaculture while encouraging communities to maintain mangrove ecosystems.

6.4 Reduced dependence on a single defence mechanism

A conventional seawall or breakwater relies primarily on engineered resistance. The hybrid system uses several mechanisms simultaneously.

6.5 Adaptability

Mangroves can grow and modify the intertidal environment over time, whereas conventional structures generally remain geometrically fixed.

Conclusion

The Aqua-Mangrove–Tetrapod Integrated Coastal Protection System provides a conceptual framework for combining engineered and nature-based coastal defence. The approach uses tetrapod armour to provide resistance against severe wave attack while retaining or restoring mangrove ecosystems behind the structure.

Aqua-mangrove farming demonstrates that mangrove conservation can be integrated with productive aquaculture and community livelihood development. Repository Tetrapods, meanwhile, provide an established form of concrete armour for breakwaters and can contribute substantially to wave-energy dissipation.

The principal advantage of the hybrid approach is that it does not rely exclusively on either concrete infrastructure or natural vegetation. Instead, it combines the immediate protective capacity of engineered structures with the long-term ecological functions of mangroves.

However, the system must be designed according to local hydrodynamic, geomorphological and ecological conditions. Particular attention should be given to tetrapod stability, structural breakage, sediment transport, tidal exchange, mangrove health and the environmental footprint of concrete production.

Overall, the concept has potential as a sustainable coastal-management strategy for tropical and subtropical coastlines, particularly where communities require both coastal protection and livelihood opportunities. Future laboratory experiments, numerical modelling and field-scale demonstrations are necessary before standardized design guidelines can be established.

References

1. Triño, A. T. (2000). *Aqua-mangrove integrated farming: Shrimp and mud crab culture in coastal and inland tidal flats with existing reforested or natural growth of mangroves*. In Technologies in Mangrove-Friendly Aquaculture, pp. 157–188. Southeast Asian Fisheries Development Center, Aquaculture Department.
 2. Mikhail, E., Younes, N., Al Adab, M. A., Tarnini, A. B., Atabay, S. A., & Mortula, M. M. (2025). Life cycle assessment of tetrapod concrete armour units. *Frontiers in Sustainable Cities*, 7, 1592987. <https://doi.org/10.3389/frsc.2025.1592987>.
 3. Burcharth, H. F., Jensen, J. B., Liu, Z., van der Meer, J. W., & d'Angremond, K. *Design Formula for Breakage of Tetrapods*. Aalborg University. Aalborg Universitets forskningsportal
 4. Burcharth, H. F., & others. *Empirical formula for breakage of Dolosse and Tetrapods*. *Coastal Engineering*, 40(3), 183–206, 2000.
 5. Sayao, O. J., & da Silva, R. F. (2018). Physical modelling of breakwater roundheads armoured with tetrapods. *Coasts, Marine Structures and Breakwaters*.
 6. Roy, S. D., & Trivedi, S. (2023). Geospatial assessment of long-term changes (1937–2019) in mangrove vegetation and shoreline dynamics of Godavari Estuary, East Coast of India. *Journal of the Indian Society of Remote Sensing*, 51, 1309–1327.
- Kudale, A. M., Kudale, M. D., & Kulkarni, P. B. (2021). Performance of concrete armour units of breakwaters in India – A review. *International Journal of Civil Engineering and Technology*, 12(6).