International Journal of Engineering Research and Science & Technology

www.ijerst.org

ISSN : 2319-5991

Vol. 22 No. 4 (2026)



ijerst.editor@gmail.com

editor@ijerst.com

ISSN 2319-5991 www.ijerst.com
© 2026 IJERST. All Rights Reserved
Peer Reviewed, Referred & Indexed Journal

Research Paper

STRUCTURAL ANALYSIS AND SIMULATION OF A G+20 MULTI-STOREY BUILDING

[1]MIDISALA SAIRAM, B.E. (Civil), M.E. (Structural),

[2] Dr, Vijay Kumar Halakatti
PhD (Structures)

[1,2] GLOBAL INSTITUTE OF ENGINEERING & TECHNOLOGY

Chilkur Village, Moinabad Mandal, Ranga Reddy District, Telangana, India.

ABSTRACT:

Structural analysis means determination of the general shape and all the particular measurements of a specific structure so it will play out the capacity for which it is made and will securely withstand the impacts which will follow up on it all through its valuable life. ETABS was utilized to make the numerical model of the BurjKhalifa, outlined by the Skidmore. ETABS are particularly intended to exploit the one of a kind physical and numerical qualities related with building compose structures. ETABS gives both static and dynamic examination for extensive variety of gravity, warm and sidelong loads. Dynamic examination may incorporate seismic reaction range or accelerogram time history. This investigation principally manages the investigation of Rectangular, L, C, I formed arrangement utilizing ETABS. A structure having 5m x 4m coves is demonstrated utilizing ETABS. The stature of every story is taken as 3m, making absolute tallness of structure. Burdens considered are taken as per the IS875 {part1, part2} and ASCE 7-10. Post examination of the structure, greatest shear powers, twisting minutes and most extreme story relocations are processed and afterward thought about for all the broke down cases.

1. INTRODUCTION

1.1 Background of Motivation

Natural calamities along with earthquakes, tsunamis, landslides, floods and so on. Reasons extreme harm and suffering to man or women with the aid of collapsing many structures, trapping or killing folks, slicing off transport systems, blocking off of navigation systems, animals hazards and many others. Such natural failures are massive challenges to the development of improvement. however, civil engineers play a chief position in minimizing the

damages by way of proper designing the systems or with the aid of right cloth selections or proper buildings technique and taking other useful selections. this consists of expertise the earthquakes, conduct of the substances of construction and structures and the extent to which structural engineers employ the understanding in taking right decisions in designing the systems fabricated from reinforced concrete. earthquakes are defined as a vibration of the earth's floor that takes place after a release of power within the earth's crust. due to the fact the earth's crust is made of severa plates that are constantly transferring slowly, vibrations can occur which bring about small earthquakes.

Maximum earthquakes are small however aren't effortlessly felt. large and violent earthquakes are the ones which occur in a launch of energy because the plates slide beyond or collide into one another. the characteristics inclusive of depth, duration, etc. of seismic floor vibrations predicted at any vicinity rely on the importance of earthquake, its intensity of focus, distance from the epicenter, characteristics of the direction via which the seismic waves travel, and the soil strata on which the shape stands. the fundamental path of ground vibration is generally horizontal. Reinforced concrete unique moment frames are used as part of seismic force resisting structures in homes which can be designed to resist earthquakes. Beams and columns in moment frames are proportioned and distinctive in one of these way that they have to withstand flexural, axial, and shearing actions that end result as a constructing sways through more than one displacement cycles in the course of robust earthquake ground shaking. unique proportioning and detailing necessities are answerable for body, able to resisting robust earthquake shaking without vast lack of stiffness or energy.

2. Objective of the Studies:

The principle objective of this take a look at is to deliver out the primary contributing elements which lead to negative performance during the earthquake and make hints which need to be taken into account in designing the multistoried bolstered concrete buildings to be able to attain their ok safe conduct below future earthquakes. earthquake codes have been revised and updated depending on the upgrades in the representation of floor motions, soils and systems. the indian trendy code is: 1893 become suitably up to date in 2002 to be able to address the various design issues brought out in the earthquake behavior of the rc homes. the selected standards are indian preferred code is: 1893, eurocode eight. a comparative analysis turned into executed

in terms of base shear, displacement, axial load, moments in y and z direction for decided on columns and additionally comparing displacement, axial load, moments in y and z route ground clever of different codes for same selected columns. observed with the aid of comparative analysis of displacement, shear y, moment z of selected beams on each ground for specific codes.

3. Methodology:

1. Modeling of the building in staad.pro v8i software.
2. Retrieved time period of structure from the software program.
3. Models as in keeping with the codes i.e. indian code, eurocode specification were made.
4. applied manually calculated lateral seismic forces and cargo mixtures as according to is 1893-2002, eurocode and
5. analyzed the fashions and graphical and tabular representation of the facts is offered

1.2 SCOPE OF THE WORK:

•Design using programming can be significant if any additional change must be done in the structure in the midst of its future life.

•To contemplate how examination and design is to be done in ETABS.

1.3 NEED OF THE WORK:

•Here we can design any sort of fragments by using ETABS programming

•Execution of the work easy to assemble the future of the structure to give the helper determining of the structure which makes the by following guidelines said in code books.

1.4 BUILDING PLAN

plan measurement- 27x17 s-m, quantity of testimonies- g+10, total height of constructing- 33m, top of each story- 3m, column length- 600x350sqmm, beam size- 500x300sqmm, grade of concrete- m20, body kind- smrf(special moment resisting frame), soil kind- medium soil, stay load- 2.5kn/m, inner wall- 150mm, outer wall- 250mm, slab thickness- 150mm, unit weight of concrete- 25kn/cum, unit weight of brick- 19kn/cum.

slaughtering humans, reducing shipping frameworks, hindering of bearing structures, creatures dangers and so forth. such catastrophic events are significant inquiring for for situations to the development of improvement. by means of and by, essential architects play a statute ability in limiting the harms through the usage of appropriate organizing the frameworks or by using techniques for proper material picks or valid structures manner and taking special beneficial judgments. this incorporates of taking

in the shivers, lead of the materials of age and structures and the aggregate to which important executives make usage of the statistics in taking

proper selections in masterminding the frameworks produced using maintained bond.

Seismic tremors are depicted as a vibration of the component floor that takes place after a touchdown of cost in the international huge's out of doors. because the area's outdoor layer is secured numerous plates which can be constantly changing little by using pretty a lot nothing, vibrations can upward push which achieve little shakes. Maximum seismic tremors are close to handiest are not effectively felt. Greater outstanding and savage seismic tremors are the ones which manifest in a dispatch of hugeness in mild of the fact that the plates slide beyond or crash into every different. the attributes regarding importance, duration, et cetera. of seismic ground vibrations foreseen at any assortment depend on the diploma of tremor, its power of care, remove from the epicenter, characteristics of the route via which the seismic waves go to, and the dirt strata on which the shape stands.

2. LITERATURE REVIEW

M.Anitha & B.Q.Rahman et al. researchers executed the assessment of layout of slab the usage of specific is code with other u . s . a . code and researchers finish that aci 318, nzs 3101& euro codes are only in designing of flat slabs. codes, under each static and dynamic forces in most reliable software program device –etabs‖

Dr. K . Subramanian& M. Velayutham et al. this paper presents a take a look at on have an effect on of zone factors and the various worldwide codal provisions for diverse lateral load resisting structures. special moment resisting frames, shear wall systems and dual structures are taken within the present have a look at. the seismic forces on the building, analytical have a look at is executed the usage of staad pro for the numerous structural systems and the similarities and variations are offered for numerous worldwide standards. The dynamic evaluation consequences along with modal taking part mass ratios, reaction spectrum base response, storey shears, storey displacements and storey drifts are mentioned in element. hence, it is important to do a comparison which will assess which constructing plays higher.

S. H. C. Santos et al, [2017] a comparative examine of codes from seismically energetic areas of numerous international locations is offered overlaying us, eu, italian, greek, romanian, brazilian and bulgarian requirements. the structure is subjected to the seismic enter in step with the above set of codes and acquired outcomes are compared highlighting the differences among the codes. ordinary this study objectives to help to the destiny development of the numerous seismic requirements. Also all of the tested codes agree on the need that the structural detailing need to provide enough ductility for the dissipation of power in the non- linear variety. variations in the shapes of the design spectra cause variations in the outcomes higher than a

hundred%, in some instances.

M. B. Waris [2017] the paper gives a evaluation of the recently evolved oman seismic code (osc) for homes with uniform building code 1997 (ubc) and international constructing code 2006 (ibc). osc is based totally on eurocode-8 (ec8), utilizes the seismic danger assessment of the united states and applies to buildings of peak as much as 60 m. the code categorizes the sultanate of oman into zones; a excessive seismic quarter (sector-1) and a low seismic zone (sector-2). muscat the capital of the united states of america falls in region- consequently, it's miles crucial that the countrywide seismic code be carried out, to make the seismic design more sensible and affordable.

result received, the have a look at supplied a contrast of the oman seismic code (osc) with international codes ubc 1997 and ibc 2006. osc become found to offer an awful lot smaller cost of base shear for each seismic zones and all building heights in comparison to ubc and ibc. for high seismic zone (osc: region-1), ubc furnished base shear three.2 - 7.6 instances that of osc, whilst ibc gave 2.6 - 6.3 instances the ones from osc. for low seismic area (osc: area-2), base shear the usage of ubc and ibc had been three.three - 7.eight instances and a pair of.4 - five.eight times better than osc, respectively.


Kamaldeep Kaur and Jaspal Singh, [2017] the seismic design of building is made to resist the earthquake effect without the lack of life and assets. the design of systems consistent with provision of seismic code presents good enough protection in opposition to the seismic forces due to earthquake. seismic codes are particular to particular region. the comparisons of the static and dynamic analysis on diverse sorts of structures using diverse codes are finished. it figures out the variations that happens in parameters together with displacement, base shear, storey float, axial and shear force, bending moments whilst using exclusive codes. this paper gives a evaluation on seismic behaviour of numerous systems the usage of diverse codal provisions as given in indian code, american code, eu code, new zealand code for earthquake evaluation.

TYPES OF SECTIONS:

- Rectangular segment
- I segment
- C segment
- L segment

2.5.1 Rectangular section:

FIG 2.5.1 RECTANGULAR SECTION



2.5.2 I SECTION




FIG 2.5.2 I SECTION

2.5.3 C SECTION




FIG 2.5.3C SECTION

2.5.4 L SECTION:




FIG 2.5.4 L SECTION

2.6 SOFTWARE:

This undertaking is for the most part in view of programming and it is basic to know the insights about the product utilized are ETABS.

ETABS:

E-TABS stay for extended three dimensional examination of building system. It is delivered by Computer science structure. Rule use of E-tabs is plotting of building systems. The association makes and passes on report computerization plans and organizations. The association was set up in 1993 as ISPC by one of the primary originators of quantize - a professional Data getting ready programming. Following an organization buyout in 1999 ISPC was rebranded as E-Tabs. E-Tabs programming thus populates outlines, graphs and reports in PowerPoint, surpass desires, word and HTML. Their things and organizations are used as a piece of market looks at as research broadens consistently incorporate reporting work. Automating frameworks, diagrams and reports improves exactness and neutralizes time and resources being wasted on data segment. Report robotization is important for adventures with repetitive segments, following examinations, ceaseless examinations, one-off multi-area mulls over transversely over brands or region, and thought testing considers. E-Tabs have won respects for progression including oneof the Queen's Awards for huge business and an ASC/MRS Award for Technology Effectiveness

LOAD COMBINTION:


1. For seismic load examination of a building the code alludes following burden blend.

1. 1.5(DL + IL)

2. 1.2(DL + IL ± EL)

3. 1.5(DL ± EL) 4. 0.9 DL ± 1.5 EL

2. For wind stack investigation of a building the code alludes following burden mix.



1. DL +LL

2. DL+WL

3. =DL+0.8LL±0.8WL

Both WL and EL are connected in X and Z bearing. These heaps are additionally connected further in negative X and Z bearing. So for Seismic investigation there are 18 stack blends and for Wind stack examination there are 11 stack mixes.

Outline OF SLABS:

Expect: fck = 20 N/mm2 fy = 415 N/mm2

Measurements of section: 4.39 × 3.65m

Let Short range = Lx = 3.65m
Longer range = Ly = 4.39m

Ly/L = 4.39/3.65 = 1.20 <2

Consequently, piece is to be planned as a two way chunk

Thickness of piece:

Successful profundity d=Span/28 = 3650/28 =130.35mm

Let take max profundity = 140mm

Add up to powerful profundity =140mm

By and large profundity = 165mm

Powerful ranges

Lx = 3.65+0.14 = 3.8m

Ly = 4.39+0.14 = 4.53m

Ly/Lx = 4.53m/3.8m = 1.20< 2 (Two way section)

METHODOLOGY

3.1 DESCRIPTION OF MULTISTOREY BUILDING (G+20)

Tallness =63m

- PLINTH AREA:

Length =25m

Width =20m

- Column gauge =300X230mm
- Beam gauge =230X230mm
- Grade of concrete =M30
- Grade of steel =Fe415
- Slab thickness =200mm.

4. WORK PROCEDURE

ASSIGNING OF PROPERTIES

FOR RECTANGULARSECTION:

FIG 4.1.15 BEAM, COLUMN AND SLAB

FOR I SECTION:




FIG 4.1.16 BEAM, COLUMN AND SLAB

FOR C SECTION:




FIG 4.1.17 BEAM, COLUMN AND SLAB

FOR L SECTION:




FIG 4.1.18 BEAM, COLUMN AND SLAB

4.3 LOADCOMBINATIONS:

DEAD LOADS:

Every single changeless development of the structure frame the dead loads. The dead load burdens might be computed from the measurements of different individuals and their unit weights. The unit weights of plain concrete and strengthened cement made with sand and rock or pounded normal stone total might be taken as 24 KN/m" and 25 KN/m

IMPOSED LOADS:

Forced load is delivered by the expected utilize or inhabitance of a building including the heaviness of portable segments, circulated and thought loads, stack because of effect and vibration and residue loads. Forced burdens do exclude stacks because of wind, seismic movement, snow, and loads forced because of temperature changes to which the structure will be subjected to, creep and shrinkage of the

structure, the differential settlements to which the structure may experience.

WIND LOAD:

Wind is air in movement in respect to the surface of the earth. The essential driver of wind is followed to earth's revolution and contrasts in earthbound radiation. The radiation impacts are basically in charge of convection either upwards or downwards.

SEISMIC LOAD:

Seismic load is like tremor stack.

REFERENCE CODE BOOKS FOR LOADS:

- Dead load : (IS875 PART1)
- Live load : (IS875 PART2)
- Wind load : (ASCE7-10)
- Seismic load: (ASCE7-10).

4.5 DEFORMATIONS:




FIG 4.5.1 DEFORMATION FOR RECTANGULARSECTION

FOR I SECTION:





FIG 4.5.2 DEFORMATION FOR I SECTION

FOR L



SECTION:

FIG 4.5.3 DEFORMATION FOR L SECTION

FOR C SECTION:




FIG 4.5.4 DEFORMATION FOR C SECTION

4.6 SAFE SECTIONS:




FIG 4.6.1 RECTANGULAR SECTION

I SECTION:





FIG 4.6.2 I SECTION

L SECTION:







FIG 4.6.2 L SECTION

C SECTION:



4.7 SHEAR FORCE DIAGRAM:

FOR RECTANGULAR




FIG 4.7.1 SHEAR FORCE FOR RECTANGULAR

SECTION

FOR I SECTION:





FIG 4.7.2 SHEAR FORCE FOR I SECTION

FOR L SECTION:



4.7.3 FIG SHEAR FORCE FOR L SECTION

FOR C SECTION:




FIG 4.7.4 SHEAR FORCE FOR C SECTION

4.8 AXIAL FORCE DIAGRAM




FIG 4.8.1 AXIAL FORCE FOR RECTANGULAR

SECTION

FOR I SECTION:





FIG 4.8.2 AXIAL FORCE FOR I SECTION

FOR L SECTION:



F

IG 4.8.3 AXIAL FORCE FOR L SECTION

FOR C SECTION:




FIG 4.8.4 AXIAL FORCE FOR C SECTION

4.9 BENDING MOMENT DIAGRAM:




FIG 4.9.1 BENDING MOMENT FOR RECTANGULAR

SECTION

FOR I SECTION




FIG 4.9.2 BENDING MOMENT FOR I SECTION

FOR L SECTION




FIG 4.9.3 BENDING MOMENT FOR L SECTION

FOR C SECTION




FIG 4.9.4 BENDING MOMENT FOR C SECTION

CONCLUSION

- As our venture manages the most temperate segment technique in this task we have plan the structure in a prudent path by lessening the sizes in the areas.

- As the heap is more at the base when contrasted with the best floors, there is no need of giving huge sizes at the best.

- Economizing the segment by methods for zone of steel according to code, the min level of steel is 0.8%gross cross sectional zone and max: 6% according to code.

- Economizing the segment by methods for section introduction is longer range longer bearing will lessen the measure of twisting accordingly the territory of steel is likewise decreased

- If the tallness of the structure is expanded, the solidness wonder (thinness impact) i.e. long section impact will come in to the photo. Thus the measure of diversions are far more noteworthy than the codal arrangements (Is – 456-2000).

REFERENCES

 Faizulla Z Shariff, Suma Devi “Comaparitive Study on RCC and CFST Multi-storey Buildings”, International Journal of Engineering and Technology Volume:02 Issue: 03 June-2015.

 VidhyaPurushothaman, ArchanaSukumaran“ Comparative Study on Seismic Analysis of Multi-Stored Buildings with

Composite Columns" International Journal of Engineering Research &Technology(IJERT) ISSN:2278-0181,Vol.6 Issue 06,
June-2016.

- Shilpa Sara Kurian, DinuPaulose, Sreepriya Mohan " Study on Concrete Filled Steel 0Tube"; IOSR Journal of Mechanical
and Civil Engineering(IOSR-JMCE) e-ISSN:2278-1684,p-ISSN:2320-334X,PP 25-33-2016
- AbhayGuleria "Structural Analysis of Multi-Storied Building using ETABS for different plan configarations" International
Journal of Engineering Research & Technology (IJERT) ISSN:2278-0181 IJERTV3IS051552 Vol. 3 Issue 5,may 14.
- Hajjar, J. F., and Gourley, B. C., "Representation of Concrete-Filled Steel Tube Cross-SectionStrength", Journal of Structural
Engineering, ASCE, V.122, No.11, November 1996.
- Knowles, R.B., and Park, R.•Strength of Concrete-Filled Tubular Columns, Journal of Structural Division, ASCE, V.95, No.12,
December 1969.
- Matsui, C., Tsuda, K., Ozaki, I., and Ishibashi, Y., "Strength of Slender Concrete Filled Steel Tubular Columns", J. Struct.
Cnstr. Eng., AIJ, No. 494, 1997. (in Japanese)
- Furlong, R. W., "Strength of Steel-Encased Bean-Columns", Journal of Structural Division, ASCE, V.93, No.5,May 1967.IS
11384: "Code of Practice for Composite Construction in Structural Steel and Concrete", Bureau of Indian Standards, New
Delhi, 1985.
- Nethercoat D. A.: "Composite Construction", Spon Press of the Taylor & Francis Group, London, 2004.Knowles P. R.:
"Composite Steel and Concrete Construction", Butterworth and Co.Publishers, 1973.